

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 11/04/2024
9.3	02/10/2025	1334687-00052	Date of first issue: 02/27/2017

### SECTION 1. IDENTIFICATION

Product name : Capstone™ FS-50 Fluorosurfactant

SDS-Identcode : 130000042667

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Fluoroaddivitive

Restrictions on use : For industrial use only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

#### GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.

Precautionary Statements : **Prevention:**  
P210 Keep away from heat, sparks, open flame and hot surfac-

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 11/04/2024
9.3	02/10/2025	1334687-00052	Date of first issue: 02/27/2017

es. No smoking.  
P233 Keep container tightly closed.  
P241 Use explosion-proof electrical, ventilating and lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P280 Wear protective gloves, eye protection and face protection.

### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

### Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

### Other hazards

Inhalation of decomposition products in high concentration may cause shortness of breath (lung edema).  
Vapors may form explosive mixture with air.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Ethanol	64-17-5	>= 30 - < 50

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	: Remove contaminated clothing and shoes.
In case of eye contact	: Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	: Dizziness Blurred vision Headache Irritation

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 11/04/2024
9.3	02/10/2025	1334687-00052	Date of first issue: 02/27/2017

Nausea  
Pain  
Lachrymation  
Vomiting  
Eye contact may provoke the following symptoms  
tearing  
Swelling of tissue  
Redness  
Impairment of vision

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides  
Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 11/04/2024
9.3	02/10/2025	1334687-00052	Date of first issue: 02/27/2017

- |   |   |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Remove all sources of ignition.<br>Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).   |
| Environmental precautions   | : Avoid release to the environment.<br>Prevent further leakage or spillage if safe to do so.<br>Prevent spreading over a wide area (e.g., by containment or oil barriers).<br>Retain and dispose of contaminated wash water.<br>Local authorities should be advised if significant spillages cannot be contained.   |
| Methods and materials for containment and cleaning up               | : Non-sparking tools should be used.<br>Soak up with inert absorbent material.<br>Suppress (knock down) gases/vapors/mists with a water spray jet.<br>For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.<br>Clean up remaining materials from spill with suitable absorbent.<br>Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.<br>Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. |

### SECTION 7. HANDLING AND STORAGE

- |                             |   |
|-----------------------------|---|
| Technical measures          | : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.   |
| Local/Total ventilation     | : If sufficient ventilation is unavailable, use with local exhaust ventilation.<br>Use explosion-proof electrical, ventilating and lighting equipment.  |
| Advice on safe handling     | : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment<br>Non-sparking tools should be used.<br>Keep container tightly closed.<br>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>Take precautionary measures against static discharges.<br>Take care to prevent spills, waste and minimize release to the environment.<br><br>Do not breathe decomposition products. |
| Conditions for safe storage | : Keep in properly labeled containers.  |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant

Version 9.3      Revision Date: 02/10/2025      SDS Number: 1334687-00052      Date of last issue: 11/04/2024  
Date of first issue: 02/27/2017

Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Self-reactive substances and mixtures  
Organic peroxides  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases  
Very acutely toxic substances and mixtures

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	STEL	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m <sup>3</sup>	OSHA Z-1

#### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		C	6 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3 ppm 2.5 mg/m <sup>3</sup>	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		ST	5 ppm 15 mg/m <sup>3</sup>	NIOSH REL

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant

Version 9.3      Revision Date: 02/10/2025      SDS Number: 1334687-00052      Date of last issue: 11/04/2024  
Date of first issue: 02/27/2017

Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NIOSH REL
		ST	30,000 ppm 54,000 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m <sup>3</sup>	NIOSH REL
		C	200 ppm 229 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 55 mg/m <sup>3</sup>	OSHA Z-1

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

### Personal protective equipment

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Hand protection

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

**Eye protection** : Wear the following personal protective equipment:  
Safety glasses

**Skin and body protection** : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 11/04/2024
9.3	02/10/2025	1334687-00052	Date of first issue: 02/27/2017

potential.

Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.

Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: clear, amber
Odor	: alcohol-like
Odor Threshold	: No data available
pH	: 5 - 7
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: 180 °F / 82 °C
Flash point	: 77 °F / 25 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: 53 hPa (68 °F / 20 °C)

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 11/04/2024
9.3	02/10/2025	1334687-00052	Date of first issue: 02/27/2017

Relative vapor density	:	No data available
Relative density	:	1
Solubility(ies)	:	
Water solubility	:	completely soluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	> 212 °F / > 100 °C
Decomposition temperature	:	> 392 °F / > 200 °C
Viscosity	:	
Viscosity, kinematic	:	9.7 mm <sup>2</sup> /s (68 °F / 20 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics	:	
Particle size	:	Not applicable

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents

#### Hazardous decomposition products

Thermal decomposition	:	Hydrogen fluoride Carbonyl difluoride Carbon dioxide Carbon monoxide
-----------------------	---	---



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 11/04/2024
9.3	02/10/2025	1334687-00052	Date of first issue: 02/27/2017

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### Ethanol:

Acute oral toxicity : LD50 (Rat): 10,470 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male): 116.9 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 15,800 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

#### Components:

##### Ethanol:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Components:

##### Ethanol:

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Method : OECD Test Guideline 405

#### Respiratory or skin sensitization

##### Skin sensitization

Not classified based on available information.

##### Respiratory sensitization

Not classified based on available information.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 11/04/2024
9.3	02/10/2025	1334687-00052	Date of first issue: 02/27/2017

---

### Components:

#### **Ethanol:**

Test Type	:	Mouse ear swelling test (MEST)
Routes of exposure	:	Skin contact
Species	:	Mouse
Result	:	negative

#### **Germ cell mutagenicity**

Not classified based on available information.

### Components:

#### **Ethanol:**

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
-----------------------	---	---

	:	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
--	---	--

	:	Test Type: Chromosome aberration test in vitro Result: negative
--	---	--

Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Ingestion Result: negative
----------------------	---	--

#### **Carcinogenicity**

Not classified based on available information.

<b>IARC</b>	No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
-------------	--

<b>OSHA</b>	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
-------------	--

<b>NTP</b>	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
------------	--

#### **Reproductive toxicity**

Not classified based on available information.

### Components:

#### **Ethanol:**

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Mouse Application Route: Ingestion
----------------------	---	---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 11/04/2024
9.3	02/10/2025	1334687-00052	Date of first issue: 02/27/2017

Result: negative

### STOT-single exposure

Not classified based on available information.

### STOT-repeated exposure

Not classified based on available information.

### Repeated dose toxicity

#### Components:

##### Ethanol:

Species	: Rat
NOAEL	: 1,730 mg/kg
LOAEL	: 3,200 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

### Aspiration toxicity

Not classified based on available information.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### Ethanol:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 14,200 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Ceriodaphnia dubia (water flea)): 5,012 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	: ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Exposure time: 72 h  EC10 (Chlorella vulgaris (Fresh water algae)): 11.5 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC (Oryzias latipes (Japanese medaka)): >= 79 mg/l Exposure time: 100 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 9.6 mg/l Exposure time: 9 d
Toxicity to microorganisms	: EC50 (Protozoa): 5,800 mg/l Exposure time: 4 h

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 11/04/2024
9.3	02/10/2025	1334687-00052	Date of first issue: 02/27/2017

### Persistence and degradability

#### Components:

##### Ethanol:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 84 %  
Exposure time: 20 d

### Bioaccumulative potential

#### Components:

##### Ethanol:

Partition coefficient: n-octanol/water : log Pow: -0.35

### Mobility in soil

No data available

### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 1170  
Proper shipping name : ETHANOL SOLUTION  
Class : 3  
Packing group : III  
Labels : 3  
Environmentally hazardous : yes

#### IATA-DGR

UN/ID No. : UN 1170  
Proper shipping name : Ethanol solution

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 11/04/2024
9.3	02/10/2025	1334687-00052	Date of first issue: 02/27/2017

Class	: 3
Packing group	: III
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 366
Packing instruction (passenger aircraft)	: 355

### IMDG-Code

UN number	: UN 1170
Proper shipping name	: ETHANOL SOLUTION (Carboxymethyldimethyl-3-[[[3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide)

Class	: 3
Packing group	: III
Labels	: 3
EmS Code	: F-E, S-D
Marine pollutant	: yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number	: UN 1170
Proper shipping name	: Ethanol solutions

Class	: 3
Packing group	: III
Labels	: FLAMMABLE LIQUID
ERG Code	: 127
Marine pollutant	: yes(Carboxymethyldimethyl-3-[[[3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide)

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	: Flammable (gases, aerosols, liquids, or solids)
----------------------	---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 11/04/2024
9.3	02/10/2025	1334687-00052	Date of first issue: 02/27/2017

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### US State Regulations

#### Pennsylvania Right To Know

Water	7732-18-5
Ethanol	64-17-5
Carboxymethyldimethyl-3-[[[(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide	34455-29-3
Propan-2-ol	67-63-0
Butanone	78-93-3

#### California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.

#### California List of Hazardous Substances

Ethanol	64-17-5
---------	---------

#### California Permissible Exposure Limits for Chemical Contaminants

Ethanol	64-17-5
---------	---------

#### Additional regulatory information

Carboxymethyldimethyl-3-[[[(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide	34455-29-3
---	------------

The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product.  
See 40 CFR § 721.10536

## SECTION 16. OTHER INFORMATION

### Further information

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant


Version  
9.3

Revision Date:  
02/10/2025

SDS Number:  
1334687-00052

Date of last issue: 11/04/2024  
Date of first issue: 02/27/2017

### NFPA 704:



### HMIS® IV:

HEALTH	/	0
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Capstone™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
ACGIH / C	: Ceiling limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	: Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-2 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 11/04/2024
9.3	02/10/2025	1334687-00052	Date of first issue: 02/27/2017

- International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 02/10/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8