

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/05/29
12.0	2024/11/25	1336750-00048	Date of first issue: 2017/02/27

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Capstone™ FS-63 Fluorosurfactant

SDS-Identcode : 130000051604

Manufacturer or supplier's details

Company : The Chemours Chemical (Shanghai) Co., Ltd.

Address : 9F, SCG Parkside, 868 Yinghua Road, Pudong New District
201204, Shanghai, China

Telephone : 86 400 8056 528

Emergency telephone number : 86 532 8388 9090

E-mail address : SDS.ChinaPSR@chemours.com

Telefax : 86 21 2612 0862

Recommended use of the chemical and restrictions on use

Recommended use : Surfactant

Restrictions on use : For industrial use only.
Do not use this product in consumer spray applications except in water-based coatings where the maximum concentration of active ingredient does not exceed 0.1 wt percent.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	: liquid
Colour	: clear, colourless, yellow
Odour	: alcohol-like

Flammable liquid and vapour. Causes serious eye irritation. Fatal if inhaled. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

GHS Classification

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue:
12.0	2024/11/25	1336750-00048	2024/05/29
			Date of first issue: 2017/02/27

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 1

Serious eye damage/eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3

Specific target organ toxicity - repeated exposure : Category 2

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H401 Toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/05/29
12.0	2024/11/25	1336750-00048	Date of first issue: 2017/02/27

P284 Wear respiratory protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P391 Collect spillage.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Physical and chemical hazards

Flammable liquid and vapour.

Health hazards

Fatal if inhaled. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

Environmental hazards

Toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Other hazards which do not result in classification

Inhalation of decomposition products in high concentration may cause shortness of breath (lung oedema).

Vapours may form explosive mixture with air.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts	Not Assigned	>= 30 -< 50
Propan-2-ol	67-63-0	>= 20 -< 30

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version 12.0	Revision Date: 2024/11/25	SDS Number: 1336750-00048	Date of last issue: 2024/05/29 Date of first issue: 2017/02/27
-----------------	------------------------------	------------------------------	---

4. FIRST AID MEASURES

- | | |
|---|---|
| General advice | : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice. |
| If inhaled | : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention immediately. |
| In case of skin contact | : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention if symptoms occur. |
| In case of eye contact | : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention. |
| If swallowed | : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : Inhalation may provoke the following symptoms:
Respiratory disorder
Shortness of breath
Lung oedema
Cough
Irritation
Eye contact may provoke the following symptoms
Lachrymation
Redness
Discomfort
Causes serious eye irritation.
Fatal if inhaled.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure. |
| Protection of first-aiders | : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8). |
| Notes to physician | : Treat symptomatically and supportively. |

5. FIREFIGHTING MEASURES

- | | |
|------------------------------|---|
| Suitable extinguishing media | : Water spray
Alcohol-resistant foam |
|------------------------------|---|

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version 12.0	Revision Date: 2024/11/25	SDS Number: 1336750-00048	Date of last issue: 2024/05/29 Date of first issue: 2017/02/27
-----------------	------------------------------	------------------------------	---

Carbon dioxide (CO₂)
Dry chemical

- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates
Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Only trained personnel should re-enter the area.
Remove all sources of ignition.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version 12.0	Revision Date: 2024/11/25	SDS Number: 1336750-00048	Date of last issue: 2024/05/29 Date of first issue: 2017/02/27
-----------------	------------------------------	------------------------------	---

Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

7. HANDLING AND STORAGE

Handling

- | | | |
|-------------------------|---|--|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment. |
| Advice on safe handling | : | Do not breathe mist or vapours.
Do not swallow.
Do not get in eyes.
Avoid prolonged or repeated contact with skin.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products. |
| Avoidance of contact | : | Oxidizing agents |

Storage

- | | | |
|-----------------------------|---|---|
| Conditions for safe storage | : | Keep in properly labelled containers.
Store locked up.
Keep tightly closed. |
|-----------------------------|---|---|

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue:
12.0	2024/11/25	1336750-00048	2024/05/29
			Date of first issue: 2017/02/27

Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable gases
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Poisonous gases
Explosives

Packaging material : Unsuitable material: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propan-2-ol	67-63-0	PC-TWA	350 mg/m ³	CN OEL
		PC-STEL	700 mg/m ³	CN OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
hydrofluoric acid	7664-39-3	MAC	2 mg/m ³ (Fluorine)	CN OEL
		TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
Carbonyl difluoride	353-50-4	PC-TWA	5 mg/m ³	CN OEL
		PC-STEL	10 mg/m ³	CN OEL
		TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
Carbon dioxide	124-38-9	PC-TWA	9,000 mg/m ³	CN OEL
		PC-STEL	18,000 mg/m ³	CN OEL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version 12.0 Revision Date: 2024/11/25 SDS Number: 1336750-00048 Date of last issue: 2024/05/29
Date of first issue: 2017/02/27

Carbon monoxide	630-08-0	PC-TWA	20 mg/m3	CN OEL
		PC-STEL	30 mg/m3	CN OEL
		MAC	20 mg/m3	CN OEL
		MAC	15 mg/m3	CN OEL
		TWA	25 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates, acidic gas/vapour and organic vapour type

Eye/face protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hand protection
Material : butyl-rubber
Break through time : 480 min
Glove thickness : 0.89 mm

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/05/29
12.0	2024/11/25	1336750-00048	Date of first issue: 2017/02/27

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear, colourless, yellow

Odour : alcohol-like

Odour Threshold : No data available

pH : 7 - 8.5

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : 26 °C

Method: Pensky-Martens closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/05/29
12.0	2024/11/25	1336750-00048	Date of first issue: 2017/02/27

Vapour pressure	: 13.79 hPa (20 °C)
Solvent	
Relative vapour density	: No data available
Density	: 1.1 g/cm ³
Solubility(ies)	
Water solubility	: soluble
Partition coefficient: n-octanol/water	: log Pow: 0.35 (for a component of this mixture)
Auto-ignition temperature	: No data available
Decomposition temperature	: > 200 °C
Viscosity	
Viscosity, kinematic	: No data available
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Particle characteristics	
Particle size	: Not applicable

10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Flammable liquid and vapour. Vapours may form explosive mixture with air. Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents

Hazardous decomposition products

Thermal decomposition	: hydrofluoric acid Carbonyl difluoride Carbon dioxide Carbon monoxide
-----------------------	---

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/05/29
12.0	2024/11/25	1336750-00048	Date of first issue: 2017/02/27

11. TOXICOLOGICAL INFORMATION

Exposure routes : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Fatal if inhaled.

Product:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : Acute toxicity estimate (Rat): 0.005 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Acute oral toxicity	: LD50 (Rat): > 1,000 mg/kg Method: OECD Test Guideline 425 Assessment: The substance or mixture has no acute oral toxicity
Acute inhalation toxicity	: Approximate Lethal Concentration (Rat): 0.047 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	: LD50 (Rat): > 1,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

Propan-2-ol:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 25 mg/l Exposure time: 6 h Test atmosphere: vapour

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/05/29
12.0	2024/11/25	1336750-00048	Date of first issue: 2017/02/27

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Propan-2-ol:

Species	: Rabbit
Result	: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Propan-2-ol:

Species	: Rabbit
Result	: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Test Type	: Local lymph node assay (LLNA)
Exposure routes	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/05/29
12.0	2024/11/25	1336750-00048	Date of first issue: 2017/02/27

Propan-2-ol:

Test Type	: Buehler Test
Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
	: Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
Germ cell mutagenicity - Assessment	: Weight of evidence does not support classification as a germ cell mutagen.

Propan-2-ol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
	: Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Propan-2-ol:

Species	: Rat
Application Route	: inhalation (vapour)
Exposure time	: 104 weeks
Method	: OECD Test Guideline 451

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/05/29
12.0	2024/11/25	1336750-00048	Date of first issue: 2017/02/27

||Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Effects on fertility	: Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 415 Result: negative Remarks: Based on data from similar materials
Effects on foetal development	: Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 414 Result: negative Remarks: Based on data from similar materials
Reproductive toxicity - Assessment	: Weight of evidence does not support classification for reproductive toxicity

Propan-2-ol:

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative
Effects on foetal development	: Test Type: Embryo-foetal development Species: Rat Application Route: Ingestion Result: negative

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Propan-2-ol:

||Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/05/29
12.0	2024/11/25	1336750-00048	Date of first issue: 2017/02/27

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Exposure routes	: Ingestion
Target Organs	: Liver
Assessment	: Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

Repeated dose toxicity

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Species	: Rat, male and female
LOAEL	: 3.6 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days
Method	: OECD Test Guideline 408
Remarks	: Based on data from similar materials

Species	: Rat, male
NOAEL	: 100 mg/kg
LOAEL	: 1,000 mg/kg
Application Route	: Skin contact
Exposure time	: 28 Days
Method	: OECD Test Guideline 410
Remarks	: Based on data from similar materials

Propan-2-ol:

Species	: Rat
NOAEL	: 12.5 mg/l
Application Route	: inhalation (vapour)
Exposure time	: 104 Weeks

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 36.4 mg/l Exposure time: 96 h
------------------	--

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue:
12.0	2024/11/25	1336750-00048	2024/05/29
			Date of first issue: 2017/02/27

	Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 3.24 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	: ErC50 (Pseudokirchneriella subcapitata (green algae)): > 22.44 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
	NOEC (Pseudokirchneriella subcapitata (green algae)): 22.44 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to fish (Chronic toxicity)	: NOEC (Oncorhynchus mykiss (rainbow trout)): 0.88 mg/l Exposure time: 90 d Method: OECD Test Guideline 210 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 0.0093 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
M-Factor (Chronic aquatic toxicity)	: 10

Propan-2-ol:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h
Toxicity to microorganisms	: EC50 (Pseudomonas putida): > 1,050 mg/l Exposure time: 16 h

Persistence and degradability

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Biodegradability	: Result: Not readily biodegradable.
------------------	--------------------------------------

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/05/29
12.0	2024/11/25	1336750-00048	Date of first issue: 2017/02/27

Method: OECD Test Guideline 301D

Remarks: Based on data from similar materials

Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1,19 (BOD5)
COD: 2,23
BOD/COD: 53 %

Bioaccumulative potential

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 4
Remarks: Based on data from similar materials

Propan-2-ol:

Partition coefficient: n-octanol/water : log Pow: 0.05

Mobility in soil

No data available

Other adverse effects

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Results of PBT and vPvB assessment : PBT substance

Additional ecological information : Information given is based on data on the components and the ecotoxicology of similar products.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/05/29
12.0	2024/11/25	1336750-00048	Date of first issue: 2017/02/27

Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number	: UN 1993
Proper shipping name	: FLAMMABLE LIQUID, N.O.S. (Propan-2-ol)
Class	: 3
Packing group	: III
Labels	: 3
Environmentally hazardous	: no

IATA-DGR

UN/ID No.	: UN 1993
Proper shipping name	: Flammable liquid, n.o.s. (Propan-2-ol)
Class	: 3
Packing group	: III
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 366
Packing instruction (passenger aircraft)	: 355

IMDG-Code

UN number	: UN 1993
Proper shipping name	: FLAMMABLE LIQUID, N.O.S. (Propan-2-ol, Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts)
Class	: 3
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

GB 6944/12268

UN number	: UN 1993
Proper shipping name	: FLAMMABLE LIQUID, N.O.S. (Propan-2-ol)

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/05/29
12.0	2024/11/25	1336750-00048	Date of first issue: 2017/02/27

Class	: 3
Packing group	: III
Labels	: 3
Marine pollutant	: no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Law on the Prevention and Control of Occupational Diseases

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : Listed

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

No. / Code	Chemical name / Category	Threshold quantity
J2	Acute toxic	50 t

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

No. / Code	Chemical name / Category	Threshold quantity
W5.4	Flammable liquids	5,000 t

Hazardous Chemicals for Priority Management under SAWS : Listed

Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not listed

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import and Export : Not listed

Regulation on the Administration of Precursor Chemicals

Catalogue and Classification of Precursor Chemicals : Not listed

Yangtze River Protection Law

This product does not contain any dangerous chemicals prohibited for inland river transport.

16. OTHER INFORMATION

Revision Date : 2024/11/25

Other information : Capstone™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/05/29
12.0	2024/11/25	1336750-00048	Date of first issue: 2017/02/27

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
CN OEL : Occupational exposure limits for hazardous agents in the workplace - Chemical hazardous agents.

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
ACGIH / C : Ceiling limit
CN OEL / PC-TWA : Permissible concentration - time weighted average
CN OEL / PC-STEEL : Permissible concentration - short term exposure limit
CN OEL / MAC : Maximum allowable concentration

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumu-

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/05/29
12.0	2024/11/25	1336750-00048	Date of first issue: 2017/02/27

lative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CN / EN