

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 25.11.2024
13.4	10.02.2025	1336779-00053	Date of first issue: 27.02.2017

---

### Section 1: Identification

Product name : Capstone™ FS-63 Fluorosurfactant

SDS-Identcode : 130000051604

#### Manufacturer or supplier's details

Company : The Chemours Malaysia Sdn. Bhd. (for use in New Zealand)

Address : Suite 20-01 & 20-02B, Level 20, The Pinnacle, Persiaran Lagoon, Bandar Sunway, Subang Jaya  
Selangor Darul Ehsan 47500 Malaysia

Telephone : +60 3 5021 0178

Emergency telephone number : NZ Poisons Information Centre: 0800 764766 ; NZ Transport  
Emergency: +64 9 801 0034

Telefax : +60 3 2178 4719

#### Recommended use of the chemical and restrictions on use

Recommended use : Surfactant

Restrictions on use : For industrial use only.  
Do not use this product in consumer spray applications except in water-based coatings where the maximum concentration of active ingredient does not exceed 0.1 wt percent.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

---

### Section 2: Hazard identification

#### GHS Classification

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 1

Serious eye damage/eye irritation : Category 2

Specific target organ toxicity - single exposure : Category 3

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version 13.4	Revision Date: 10.02.2025	SDS Number: 1336779-00053	Date of last issue: 25.11.2024 Date of first issue: 27.02.2017
-----------------	------------------------------	------------------------------	---

---

Specific target organ toxicity - repeated exposure : Category 2 (Liver)

Aspiration hazard : Category 1

Hazardous to the aquatic environment - chronic hazard : Category 1

### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H319 Causes serious eye irritation.  
H330 Fatal if inhaled.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs (Liver) through prolonged or repeated exposure.  
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe mist or vapours.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P284 Wear respiratory protection.

**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version 13.4	Revision Date: 10.02.2025	SDS Number: 1336779-00053	Date of last issue: 25.11.2024 Date of first issue: 27.02.2017
-----------------	------------------------------	------------------------------	---

easy to do. Continue rinsing.  
P314 Get medical advice/ attention if you feel unwell.  
P331 Do NOT induce vomiting.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P391 Collect spillage.

### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

Inhalation of decomposition products in high concentration may cause shortness of breath (lung oedema).

Vapours may form explosive mixture with air.

## Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts	Not Assigned	$\geq 30$ -< 50
Propan-2-ol	67-63-0	$\geq 20$ -< 30

## Section 4: First-aid measures

General advice	: In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
In case of skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
In case of eye contact	: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention.

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version 13.4	Revision Date: 10.02.2025	SDS Number: 1336779-00053	Date of last issue: 25.11.2024 Date of first issue: 27.02.2017
-----------------	------------------------------	------------------------------	---

---

- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Inhalation may provoke the following symptoms:  
Respiratory disorder  
Shortness of breath  
Lung oedema  
Cough  
Irritation  
Eye contact may provoke the following symptoms  
Lachrymation  
Redness  
Discomfort  
May be fatal if swallowed and enters airways.  
Causes serious eye irritation.  
Fatal if inhaled.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

---

### Section 5: Fire-fighting measures

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates  
Carbon oxides

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version 13.4	Revision Date: 10.02.2025	SDS Number: 1336779-00053	Date of last issue: 25.11.2024 Date of first issue: 27.02.2017
-----------------	------------------------------	------------------------------	---

---

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Hazchem Code : 3Y

---

### Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Only trained personnel should re-enter the area.  
Remove all sources of ignition.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### Section 7: Handling and storage

Technical measures : See Engineering measures under EXPOSURE

---

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 25.11.2024
13.4	10.02.2025	1336779-00053	Date of first issue: 27.02.2017

---

### CONTROLS/PERSONAL PROTECTION section.

- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not breathe mist or vapours.  
Do not swallow.  
Do not get in eyes.  
Avoid prolonged or repeated contact with skin.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Non-sparking tools should be used.  
Keep container tightly closed.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.
- Do not breathe decomposition products.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.
- Conditions for safe storage : Keep in properly labelled containers.  
Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable gases  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Poisonous gases  
Explosives

## SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version 13.4      Revision Date: 10.02.2025      SDS Number: 1336779-00053      Date of last issue: 25.11.2024  
Date of first issue: 27.02.2017

## Section 8: Exposure controls/personal protection

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propan-2-ol	67-63-0	WES-TWA	400 ppm 983 mg/m <sup>3</sup>	NZ OEL
		WES-STEEL	500 ppm 1,230 mg/m <sup>3</sup>	NZ OEL
		TWA	200 ppm	ACGIH
		STEEL	400 ppm	ACGIH

## Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
hydrofluoric acid	7664-39-3	WES-Ceiling	3 ppm 2.6 mg/m <sup>3</sup> (Fluorine)	NZ OEL
	Further information: Exposure can also be estimated by biological monitoring			
		TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
Carbonyl difluoride	353-50-4	WES-STEEL	5 ppm 13 mg/m <sup>3</sup>	NZ OEL
		WES-TWA	2 ppm 5.4 mg/m <sup>3</sup>	NZ OEL
		TWA	2 ppm	ACGIH
		STEEL	5 ppm	ACGIH
Carbon dioxide	124-38-9	WES-TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NZ OEL
		WES-STEEL	30,000 ppm 54,000 mg/m <sup>3</sup>	NZ OEL
		TWA	5,000 ppm	ACGIH
		STEEL	30,000 ppm	ACGIH
Carbon monoxide	630-08-0	WES-TWA	20 ppm	NZ OEL
	Further information: Ototoxin, Exposure can also be estimated by biological monitoring			
		WES-Ceiling	200 ppm	NZ OEL
	Further information: Ototoxin, Exposure can also be estimated by biological monitoring			
		WES-STEEL	100 ppm	NZ OEL
	Further information: Ototoxin, Exposure can also be estimated by biological monitoring			
		TWA	25 ppm	ACGIH

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version 13.4      Revision Date: 10.02.2025      SDS Number: 1336779-00053      Date of last issue: 25.11.2024  
Date of first issue: 27.02.2017

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

### Personal protective equipment

**Respiratory protection** : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

**Filter type** : Combined particulates, acidic gas/vapour and organic vapour type

#### Hand protection

**Material** : butyl-rubber  
**Break through time** : 480 min  
**Glove thickness** : 0.89 mm

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

**Eye protection** : Wear the following personal protective equipment:  
Safety goggles

**Skin and body protection** : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).



# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version 13.4	Revision Date: 10.02.2025	SDS Number: 1336779-00053	Date of last issue: 25.11.2024 Date of first issue: 27.02.2017
-----------------	------------------------------	------------------------------	---

### Section 9: Physical and chemical properties

Appearance	: liquid
Colour	: clear, colourless, yellow
Odour	: alcohol-like
Odour Threshold	: No data available
pH	: 7 - 8.5
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: 26 °C Method: Pensky-Martens closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: 13.79 hPa (20 °C) Solvent
Relative vapour density	: No data available
Density	: 1.1 g/cm <sup>3</sup>
Solubility(ies) Water solubility	: soluble
Partition coefficient: n-octanol/water	: log Pow: 0.35 (for a component of this mixture)
Auto-ignition temperature	: No data available

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version 13.4	Revision Date: 10.02.2025	SDS Number: 1336779-00053	Date of last issue: 25.11.2024 Date of first issue: 27.02.2017
-----------------	------------------------------	------------------------------	---

---

Decomposition temperature : > 200 °C

Viscosity  
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : Not applicable

---

### Section 10: Stability and reactivity

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Flammable liquid and vapour.  
Vapours may form explosive mixture with air.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

#### Hazardous decomposition products

Thermal decomposition : hydrofluoric acid  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide

---

### Section 11: Toxicological information

Exposure routes : Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Fatal if inhaled.

#### Product:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 25.11.2024
13.4	10.02.2025	1336779-00053	Date of first issue: 27.02.2017

---

Acute inhalation toxicity : Acute toxicity estimate (Rat): 0.005 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

### Components:

#### **Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:**

Acute oral toxicity : LD50 (Rat): > 1,000 mg/kg  
Method: OECD Test Guideline 425  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : Approximate Lethal Concentration (Rat): 0.047 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 1,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

#### **Propan-2-ol:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l  
Exposure time: 6 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

#### **Skin corrosion/irritation**

Not classified based on available information.

### Components:

#### **Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

#### **Propan-2-ol:**

Species : Rabbit  
Result : No skin irritation

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 25.11.2024
13.4	10.02.2025	1336779-00053	Date of first issue: 27.02.2017

---

### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Components:

#### Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

#### Propan-2-ol:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

#### Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Test Type	:	Local lymph node assay (LLNA)
Exposure routes	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative

#### Propan-2-ol:

Test Type	:	Buehler Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

### Chronic toxicity

#### Germ cell mutagenicity

Not classified based on available information.

#### Components:

#### Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES)
-----------------------	---	--

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 25.11.2024
13.4	10.02.2025	1336779-00053	Date of first issue: 27.02.2017

---

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

### Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

### Carcinogenicity

Not classified based on available information.

### Components:

#### Propan-2-ol:

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 104 weeks  
Method : OECD Test Guideline 451  
Result : negative

### Reproductive toxicity

Not classified based on available information.

### Components:

#### Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 415  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal develop- : Test Type: Reproduction/Developmental toxicity screening

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version 13.4	Revision Date: 10.02.2025	SDS Number: 1336779-00053	Date of last issue: 25.11.2024 Date of first issue: 27.02.2017
-----------------	------------------------------	------------------------------	---

---

ment

test

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

Reproductive toxicity - Assessment

: Weight of evidence does not support classification for reproductive toxicity

### Propan-2-ol:

Effects on fertility

: Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal development

: Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

Result: negative

### STOT - single exposure

May cause drowsiness or dizziness.

#### Components:

### Propan-2-ol:

Assessment

: May cause drowsiness or dizziness.

### STOT - repeated exposure

May cause damage to organs (Liver) through prolonged or repeated exposure.

#### Components:

**Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:**

Exposure routes

: Ingestion

Target Organs

: Liver

Assessment

: Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

### Repeated dose toxicity

#### Components:

**Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:**

Species

: Rat, male and female

LOAEL

: 3.6 mg/kg

Application Route

: Ingestion

Exposure time

: 90 Days

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version 13.4	Revision Date: 10.02.2025	SDS Number: 1336779-00053	Date of last issue: 25.11.2024 Date of first issue: 27.02.2017
-----------------	------------------------------	------------------------------	---

---

Method : OECD Test Guideline 408  
Remarks : Based on data from similar materials

Species : Rat, male  
NOAEL : 100 mg/kg  
LOAEL : 1,000 mg/kg  
Application Route : Skin contact  
Exposure time : 28 Days  
Method : OECD Test Guideline 410  
Remarks : Based on data from similar materials

### Propan-2-ol:

Species : Rat  
NOAEL : 12.5 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 104 Weeks

### Aspiration toxicity

May be fatal if swallowed and enters airways.

### Components:

#### Propan-2-ol:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

## Section 12: Ecological information

### Ecotoxicity

#### Components:

#### Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 36.4 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 3.24 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 22.44 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue:
13.4	10.02.2025	1336779-00053	25.11.2024
			Date of first issue: 27.02.2017

---

NOEC (Pseudokirchneriella subcapitata (green algae)): 22.44 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 0.88 mg/l  
Exposure time: 90 d  
Method: OECD Test Guideline 210  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.0093 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

M-Factor (Chronic aquatic toxicity) : 10

### Propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 24 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 1,050 mg/l  
Exposure time: 16 h

### Persistence and degradability

#### Components:

#### **Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:**

Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 301D  
Remarks: Based on data from similar materials

### Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1,19 (BOD5)  
COD: 2,23  
BOD/COD: 53 %



# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version 13.4	Revision Date: 10.02.2025	SDS Number: 1336779-00053	Date of last issue: 25.11.2024 Date of first issue: 27.02.2017
-----------------	------------------------------	------------------------------	---

---

### Bioaccumulative potential

#### Components:

#### Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
Bioconcentration factor (BCF): 4  
Remarks: Based on data from similar materials

#### Propan-2-ol:

Partition coefficient: n-octanol/water : log Pow: 0.05

### Mobility in soil

No data available

### Other adverse effects

#### Components:

#### Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Results of PBT and vPvB assessment : PBT substance

Additional ecological information : Information given is based on data on the components and the ecotoxicology of similar products.

---

## Section 13: Disposal considerations

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

---

## Section 14: Transport information

### International Regulations

UNRTDG

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 25.11.2024
13.4	10.02.2025	1336779-00053	Date of first issue: 27.02.2017

---

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Propan-2-ol)  
Class : 3  
Packing group : III  
Labels : 3  
Environmentally hazardous : no

### IATA-DGR

UN/ID No. : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(Propan-2-ol)  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

### IMDG-Code

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Propan-2-ol, Reaction mass of mixed  
(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### NZS 5433

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Propan-2-ol)  
Class : 3  
Packing group : III  
Labels : 3  
Hazchem Code : 3Y  
Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version 13.4	Revision Date: 10.02.2025	SDS Number: 1336779-00053	Date of last issue: 25.11.2024 Date of first issue: 27.02.2017
-----------------	------------------------------	------------------------------	---

### Section 15: Regulatory information

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

##### HSNO Approval Number

HSR100962 Capstone™ FS-63 Fluorosurfactant

##### Tolerable Exposure Limits (TEL)

Not applicable

##### Environmental Exposure Limits (EEL)

Not applicable

##### HSW Controls

Certified handler certificate not required.

Tracking hazardous substance is required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

### Section 16: Other information

Revision Date : 10.02.2025

Other information : Capstone™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.  
Chemours™ and the Chemours Logo are trademarks of The Chemours Company.  
Before use read Chemours safety information.  
For further information contact the local Chemours office or nominated distributors.

#### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
ACGIH / C : Ceiling limit  
NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average  
NZ OEL / WES-STEL : Workplace Exposure Standard - Short-Term Exposure Limit  
NZ OEL / WES-Ceiling : Workplace Exposure Standard - Ceiling

# SAFETY DATA SHEET



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 25.11.2024
13.4	10.02.2025	1336779-00053	Date of first issue: 27.02.2017

---

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

NZ / EN