

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Freon™ MO49 (R-413A) Refrigerant

SDS-Identcode : 130000000125

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Refrigerant

Recommended restrictions : For professional and industrial installation and use only.  
on use

#### 1.3 Details of the supplier of the safety data sheet

Company : Chemours Netherlands B.V.  
Baanhoekweg 22  
3313 LA Dordrecht Netherlands

Telephone : +31-(0)-78-630-1011

Telefax : +31-78-6163737

E-mail address of person  
responsible for the SDS : sds-support@chemours.com

#### 1.4 Emergency telephone number

+(44)-870-8200418 (CHEMTREC - Recommended)

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Gases under pressure, Liquefied gas	H280: Contains gas under pressure; may explode if heated.
-------------------------------------	---

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

Hazard pictograms :



Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.

Precautionary statements : **Storage:**  
P410 + P403 Protect from sunlight. Store in a well-ventilated place.

### Additional Labelling

Contains fluorinated greenhouse gases. (HFC-134a, PFC-218)

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

May displace oxygen and cause rapid suffocation.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
1,1,1,2-Tetrafluoroethane#	811-97-2 212-377-0 01-2119459374-33	Press. Gas Liquefied gas; H280	88
Octafluoropropane#	76-19-7 200-941-9	Press. Gas Liquefied gas; H280	9

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

Isobutane	75-28-5 200-857-2 601-004-00-0	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280 STOT SE 3; H336	3
-----------	--------------------------------------	--	---

For explanation of abbreviations see section 16.

# Voluntarily-disclosed substance

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- |                            |   |
|----------------------------|---|
| General advice             | : In the case of accident or if you feel unwell, seek medical advice immediately.<br>When symptoms persist or in all cases of doubt seek medical advice.              |
| Protection of first-aiders | : No special precautions are necessary for first aid responders.  |
| If inhaled                 | : If inhaled, remove to fresh air.<br>If not breathing, give artificial respiration.<br>If breathing is difficult, give oxygen.<br>Get medical attention immediately. |
| In case of skin contact    | : Thaw frosted parts with lukewarm water. Do not rub affected area.<br>Get medical attention immediately.   |
| In case of eye contact     | : Get medical attention immediately.  |
| If swallowed               | : Ingestion is not considered a potential route of exposure.  |

#### 4.2 Most important symptoms and effects, both acute and delayed

- |          |  |
|----------|--|
| Symptoms | : May cause cardiac arrhythmia.<br><br>Other symptoms potentially related to misuse or inhalation abuse are<br>Cardiac sensitisation<br>Anaesthetic effects<br>Light-headedness<br>Dizziness<br>confusion<br>Lack of coordination<br>Drowsiness<br>Unconsciousness |
| Risks    | : Gas reduces oxygen available for breathing.<br>Contact with liquid or refrigerated gas can cause cold burns and frostbite.   |

#### 4.3 Indication of any immediate medical attention and special treatment needed

- |           |   |
|-----------|---|
| Treatment | : Because of possible disturbances of cardiac rhythm, cate- |
|-----------|---|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

cholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Not applicable  
Will not burn

Unsuitable extinguishing media : Not applicable  
Will not burn

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Hydrogen fluoride  
carbonyl fluoride  
Carbon oxides  
Fluorine compounds

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fight fire remotely due to the risk of explosion.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Avoid skin contact with leaking liquid (danger of frostbite).  
Ventilate the area.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

#### 6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

---

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ventilate the area.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures	: Use equipment rated for cylinder pressure. Use a backflow preventative device in piping. Close valve after each use and when empty.
Local/Total ventilation	: Use only with adequate ventilation.
Advice on safe handling	: Avoid breathing gas. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment Wear cold insulating gloves/ face shield/ eye protection. Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point. Prevent backflow into the gas tank. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder. Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems. Close valve after each use and when empty. Do NOT change or force fit connections. Prevent the intrusion of water into the gas tank. Never attempt to lift cylinder by its cap. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.
Hygiene measures	: If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Separate full containers from empty containers. Do not store near combustible materials. Avoid area where salt or other corrosive materials are present. Keep in properly labelled containers. Keep in a cool, well-ventilated place. Keep away from direct sunlight. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable liquids  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures, which in contact with water, emit flammable gases  
Explosives  
Very acutely toxic substances and mixtures  
Acutely toxic substances and mixtures  
Substances and mixtures with chronic toxicity

Storage period : > 10 yr

Recommended storage temperature : < 52 °C

Further information on storage stability : The product has an indefinite shelf life when stored properly.

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
1,1,1,2-Tetrafluoroethane	Workers	Inhalation	Long-term systemic effects	13936 mg/m3
	Consumers	Inhalation	Long-term systemic effects	2476 mg/m3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version 7.4      Revision Date: 05.03.2025      SDS Number: 1324708-00048      Date of last issue: 07.01.2025  
Date of first issue: 27.02.2017

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
1,1,1,2-Tetrafluoroethane	Fresh water	0.1 mg/l
	Marine water	0.01 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	0.75 mg/kg dry weight (d.w.)
	Sewage treatment plant	73 mg/l

### 8.2 Exposure controls

#### Engineering measures

Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

#### Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:  
Chemical resistant goggles must be worn.  
Face-shield  
Equipment should conform to MSA EN 166

Hand protection  
Material : Heat resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Skin and body protection : Skin should be washed after contact.

Respiratory protection : Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown.

Protective measures : Wear cold insulating gloves/ face shield/ eye protection.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : Liquefied gas

Colour : colourless

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

---

Odour	:	slight, ether-like
Odour Threshold	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	-35 °C (1,013 hPa)
Flammability (solid, gas)	:	Will not burn
Upper explosion limit / Upper flammability limit	:	Upper flammability limit Method: ASTM E681 None.
Lower explosion limit / Lower flammability limit	:	Lower flammability limit Method: ASTM E681 None.
Flash point	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Vapour pressure	:	7,818 hPa (25 °C)
Relative density	:	1.16 (25 °C)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

---

Density : 1.214 g/cm<sup>3</sup> (20 °C)  
(as liquid)

Relative vapour density : 3.9

Particle characteristics  
Particle size : Not applicable

### 9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

### 10.4 Conditions to avoid

Conditions to avoid : This substance is not flammable in air at temperatures up to 100 °C (212 °F) at atmospheric pressure. However, mixtures of this substance with high concentrations of air at elevated pressure and/or temperature can become combustible in the presence of an ignition source. This substance can also become combustible in an oxygen enriched environment (oxygen concentrations greater than that in air). Whether a mixture containing this substance and air, or this substance in an oxygen enriched atmosphere become combustible depends on the inter-relationship of 1) the temperature 2) the pressure, and 3) the proportion of oxygen in the mixture. In general, this substance should not be allowed to exist with air above atmospheric pressure or at high temperatures; or in an oxygen enriched environment. For example this substance should NOT be mixed with air under pressure for leak testing or other purposes.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **1,1,1,2-Tetrafluoroethane:**

Acute oral toxicity : Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 567000 ppm  
Exposure time: 4 h  
Test atmosphere: gas  
Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 40000 ppm  
Test atmosphere: gas  
Remarks: Cardiac sensitisation

Lowest observed adverse effect concentration (Dog): 80000 ppm  
Test atmosphere: gas  
Symptoms: May cause cardiac arrhythmia.

Cardiac sensitisation threshold limit (Dog): 334,000 mg/m<sup>3</sup>  
Test atmosphere: gas  
Symptoms: May cause cardiac arrhythmia.

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity

##### **Octafluoropropane:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

---

### Isobutane:

Acute inhalation toxicity : LC50 (Rat): 570000 ppm  
Exposure time: 15 min  
Test atmosphere: gas

### Skin corrosion/irritation

Not classified based on available information.

### Components:

#### 1,1,1,2-Tetrafluoroethane:

Result : No skin irritation

#### Octafluoropropane:

Species : Rat  
Result : No skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

### Components:

#### 1,1,1,2-Tetrafluoroethane:

Result : No eye irritation

#### Octafluoropropane:

Result : No eye irritation  
Remarks : Based on data from similar materials

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

### Components:

#### 1,1,1,2-Tetrafluoroethane:

Exposure routes : Skin contact  
Result : negative

Exposure routes : Inhalation  
Species : Rat  
Result : negative

Exposure routes : Inhalation  
Species : Humans  
Result : negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

### Octafluoropropane:

Test Type	: Maximisation Test
Exposure routes	: Skin contact
Species	: Guinea pig
Result	: negative
Remarks	: Based on data from similar materials

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### 1,1,1,2-Tetrafluoroethane:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative  Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: inhalation (gas) Method: OECD Test Guideline 474 Result: negative  Test Type: Unscheduled DNA synthesis (UDS) test with mammalian liver cells in vivo Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 486 Result: negative
Germ cell mutagenicity- Assessment	: Weight of evidence does not support classification as a germ cell mutagen.

### Octafluoropropane:

Genotoxicity in vitro	: Test Type: Ames test Result: negative  Test Type: Chromosome aberration test in vitro Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Ingestion Result: negative Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

---

### Isobutane:

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative Remarks: Based on data from similar materials
	Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

### Carcinogenicity

Not classified based on available information.

#### Components:

##### 1,1,1,2-Tetrafluoroethane:

Species	: Rat
Application Route	: inhalation (gas)
Exposure time	: 2 Years
Method	: OECD Test Guideline 453
Result	: negative
Carcinogenicity - Assessment	: Weight of evidence does not support classification as a carcinogen

### Reproductive toxicity

Not classified based on available information.

#### Components:

##### 1,1,1,2-Tetrafluoroethane:

Effects on fertility	: Species: Mouse Application Route: Inhalation Result: negative
Effects on foetal development	: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rabbit Application Route: inhalation (gas) Method: OECD Test Guideline 414 Result: negative
Reproductive toxicity - Assessment	: Weight of evidence does not support classification for repro-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

assessment

ductive toxicity

### Isobutane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

### STOT - single exposure

Not classified based on available information.

#### Components:

##### 1,1,1,2-Tetrafluoroethane:

Exposure routes : inhalation (gas)  
Assessment : No significant health effects observed in animals at concentrations of 20000 ppmV/4h or less

### Isobutane:

Assessment : May cause drowsiness or dizziness.

### STOT - repeated exposure

Not classified based on available information.

#### Components:

##### 1,1,1,2-Tetrafluoroethane:

Exposure routes : inhalation (gas)  
Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

### Repeated dose toxicity

#### Components:

##### 1,1,1,2-Tetrafluoroethane:

Species : Rat, male and female  
NOAEL : 50000 ppm  
LOAEL : >50000 ppm  
Application Route : inhalation (gas)  
Exposure time : 2 yr  
Method : OECD Test Guideline 453

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

---

### Isobutane:

Species	:	Rat
NOAEL	:	>= 9000 ppm
Application Route	:	inhalation (gas)
Exposure time	:	6 Weeks
Method	:	OECD Test Guideline 422

### Aspiration toxicity

Not classified based on available information.

### Components:

#### 1,1,1,2-Tetrafluoroethane:

No aspiration toxicity classification

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
------------	---	---

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### 1,1,1,2-Tetrafluoroethane:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 450 mg/l Exposure time: 96 h Method: Regulation (EC) No. 440/2008, Annex, C.1
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 980 mg/l Exposure time: 48 h Method: Regulation (EC) No. 440/2008, Annex, C.2
Toxicity to algae/aquatic plants	:	ErC50 (green algae): > 100 mg/l Exposure time: 96 h Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

---

### 12.2 Persistence and degradability

#### Components:

##### **1,1,1,2-Tetrafluoroethane:**

Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 301D

##### **Isobutane:**

Biodegradability : Result: Readily biodegradable.  
Remarks: Based on data from similar materials

### 12.3 Bioaccumulative potential

#### Components:

##### **1,1,1,2-Tetrafluoroethane:**

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1.06

##### **Isobutane:**

Partition coefficient: n-octanol/water : log Pow: 2.8

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

### 12.7 Other adverse effects

#### Global warming potential

#### Regulation (EU) No 2024/573 on fluorinated greenhouse gases

##### Product:

100-year global warming potential: 2,095

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

- |                        |   |
|------------------------|---|
| Product                | : Dispose of in accordance with local regulations.<br>According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.<br>Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. |
| Contaminated packaging | : Empty containers should be taken to an approved waste handling site for recycling or disposal.<br>Empty pressure vessels should be returned to the supplier.<br>If not otherwise specified: Dispose of as unused product.   |

## SECTION 14: Transport information

### 14.1 UN number or ID number

- |      |           |
|------|-----------|
| ADN  | : UN 1078 |
| ADR  | : UN 1078 |
| RID  | : UN 1078 |
| IMDG | : UN 1078 |
| IATA | : UN 1078 |

### 14.2 UN proper shipping name

- |      |   |
|------|---|
| ADN  | : REFRIGERANT GAS, N.O.S.<br>(1,1,1,2-Tetrafluoroethane, Octafluoropropane) |
| ADR  | : REFRIGERANT GAS, N.O.S.<br>(1,1,1,2-Tetrafluoroethane, Octafluoropropane) |
| RID  | : REFRIGERANT GAS, N.O.S.<br>(1,1,1,2-Tetrafluoroethane, Octafluoropropane) |
| IMDG | : REFRIGERANT GAS, N.O.S.<br>(1,1,1,2-Tetrafluoroethane, Octafluoropropane) |
| IATA | : Refrigerant gas, n.o.s.<br>(1,1,1,2-Tetrafluoroethane, Octafluoropropane) |

### 14.3 Transport hazard class(es)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version 7.4	Revision Date: 05.03.2025	SDS Number: 1324708-00048	Date of last issue: 07.01.2025 Date of first issue: 27.02.2017
----------------	------------------------------	------------------------------	---

	Class	Subsidiary risks
<b>ADN</b>	: 2	2.2
<b>ADR</b>	: 2	2.2
<b>RID</b>	: 2	2.2, (13)
<b>IMDG</b>	: 2.2	
<b>IATA</b>	: 2.2	

### 14.4 Packing group

#### ADN

Packing group : Not assigned by regulation  
Classification Code : 2A  
Hazard Identification Number : 20  
Labels : 2.2

#### ADR

Packing group : Not assigned by regulation  
Classification Code : 2A  
Hazard Identification Number : 20  
Labels : 2.2  
Tunnel restriction code : (C/E)

#### RID

Packing group : Not assigned by regulation  
Classification Code : 2A  
Hazard Identification Number : 20  
Labels : 2.2 ((13))

#### IMDG

Packing group : Not assigned by regulation  
Labels : 2.2  
EmS Code : F-C, S-V

#### IATA (Cargo)

Packing instruction (cargo aircraft) : 200  
Packing group : Not assigned by regulation  
Labels : Non-flammable, non-toxic Gas

#### IATA (Passenger)

Packing instruction (passenger aircraft) : 200  
Packing group : Not assigned by regulation  
Labels : Non-flammable, non-toxic Gas

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

Not applicable

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

Other information : Freon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.  
Chemours™ and the Chemours Logo are trademarks of The Chemours Company.  
Before use read Chemours safety information.  
For further information contact the local Chemours office or nominated distributors.

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

### Full text of H-Statements

H220 : Extremely flammable gas.  
H280 : Contains gas under pressure; may explode if heated.  
H336 : May cause drowsiness or dizziness.

### Full text of other abbreviations

Flam. Gas : Flammable gases  
Press. Gas : Gases under pressure  
STOT SE : Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Freon™ MO49 (R-413A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 07.01.2025
7.4	05.03.2025	1324708-00048	Date of first issue: 27.02.2017

---

Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Press. Gas Liquefied gas H280

### Classification procedure:

Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

MT / EN