

# SAFETY DATA SHEET



## Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2024
5.4	10.02.2025	2072683-00019	Date of first issue: 11.10.2017

---

### Section 1: Identification

Product name : Capstone™ FS-93

SDS-Identcode : 130000141339

#### Manufacturer or supplier's details

Company : The Chemours Malaysia Sdn. Bhd. (for use in New Zealand)

Address : Suite 20-01 & 20-02B, Level 20, The Pinnacle, Persiaran Lagoon, Bandar Sunway, Subang Jaya  
Selangor Darul Ehsan 47500 Malaysia

Telephone : +60 3 5021 0178

Emergency telephone number : NZ Poisons Information Centre: 0800 764766 ; NZ Transport  
Emergency: +64 9 801 0034

Telefax : +60 3 2178 4719

#### Recommended use of the chemical and restrictions on use

Recommended use : Coatings  
Surfactant

Restrictions on use : Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

---

### Section 2: Hazard identification

#### GHS Classification

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Serious eye damage/eye irritation : Category 2

Specific target organ toxicity - single exposure (Inhalation) : Category 1 (Lungs, larynx)

Aspiration hazard : Category 1

# SAFETY DATA SHEET



## Capstone™ FS-93

Version  
5.4

Revision Date:  
10.02.2025

SDS Number:  
2072683-00019

Date of last issue: 23.07.2024  
Date of first issue: 11.10.2017

### GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H370 Causes damage to organs (Lungs, larynx) if inhaled.

Precautionary statements

#### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe mist or vapours.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.

#### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

#### Disposal:

P501 Dispose of contents/ container to an approved waste

# SAFETY DATA SHEET



## Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2024
5.4	10.02.2025	2072683-00019	Date of first issue: 11.10.2017

disposal plant.

### Other hazards which do not result in classification

Inhalation of decomposition products in high concentration may cause shortness of breath (lung oedema).

Vapours may form explosive mixture with air.

### Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Propan-2-ol	67-63-0	$\geq 10$ -< 20
Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts	Not Assigned	$\geq 10$ -< 20

### Section 4: First-aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
If not breathing, give artificial respiration.  
If breathing is difficult, give oxygen.  
Get medical attention.
- In case of skin contact : Remove contaminated clothing and shoes.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Inhalation may provoke the following symptoms:  
Central nervous system depression  
respiratory tract irritation  
Cough  
sneezing  
runny nose  
sore throat  
Shortness of breath  
Eye contact may provoke the following symptoms  
Pain

# SAFETY DATA SHEET



## Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2024
5.4	10.02.2025	2072683-00019	Date of first issue: 11.10.2017

---

tearing  
Swelling of tissue  
Redness  
Impairment of vision  
May be fatal if swallowed and enters airways.  
Causes serious eye irritation.  
Harmful if inhaled.  
Causes damage to organs if inhaled.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

---

### Section 5: Fire-fighting measures

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides  
Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Hazchem Code : 3Y

# SAFETY DATA SHEET



## Capstone™ FS-93

Version 5.4	Revision Date: 10.02.2025	SDS Number: 2072683-00019	Date of last issue: 23.07.2024 Date of first issue: 11.10.2017
----------------	------------------------------	------------------------------	---

---

---

### Section 6: Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### Section 7: Handling and storage

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not breathe mist or vapours.  
Do not swallow.  
Do not get in eyes.  
Avoid prolonged or repeated contact with skin.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

# SAFETY DATA SHEET



## Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2024
5.4	10.02.2025	2072683-00019	Date of first issue: 11.10.2017

assessment

Non-sparking tools should be used.

Keep container tightly closed.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharges.

Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.
- Conditions for safe storage : Keep in properly labelled containers.  
Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable gases  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Poisonous gases  
Explosives

### Section 8: Exposure controls/personal protection

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propan-2-ol	67-63-0	WES-TWA	400 ppm 983 mg/m3	NZ OEL
		WES-STEL	500 ppm 1,230 mg/m3	NZ OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

## SAFETY DATA SHEET



## Capstone™ FS-93

Version  
5.4Revision Date:  
10.02.2025SDS Number:  
2072683-00019Date of last issue: 23.07.2024  
Date of first issue: 11.10.2017

## Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
hydrofluoric acid	7664-39-3	WES-Ceiling	3 ppm 2.6 mg/m <sup>3</sup> (Fluorine)	NZ OEL
Further information: Exposure can also be estimated by biological monitoring				
		TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
Carbonyl difluoride	353-50-4	WES-STEEL	5 ppm 13 mg/m <sup>3</sup>	NZ OEL
		WES-TWA	2 ppm 5.4 mg/m <sup>3</sup>	NZ OEL
		TWA	2 ppm	ACGIH
		STEEL	5 ppm	ACGIH
Carbon dioxide	124-38-9	WES-TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NZ OEL
		WES-STEEL	30,000 ppm 54,000 mg/m <sup>3</sup>	NZ OEL
		TWA	5,000 ppm	ACGIH
		STEEL	30,000 ppm	ACGIH
Carbon monoxide	630-08-0	WES-TWA	20 ppm	NZ OEL
Further information: Ototoxin, Exposure can also be estimated by biological monitoring				
		WES-Ceiling	200 ppm	NZ OEL
Further information: Ototoxin, Exposure can also be estimated by biological monitoring				
		WES-STEEL	100 ppm	NZ OEL
Further information: Ototoxin, Exposure can also be estimated by biological monitoring				
		TWA	25 ppm	ACGIH

## Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust

# SAFETY DATA SHEET



## Capstone™ FS-93

Version 5.4	Revision Date: 10.02.2025	SDS Number: 2072683-00019	Date of last issue: 23.07.2024 Date of first issue: 11.10.2017
----------------	------------------------------	------------------------------	---

---

ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

### Personal protective equipment

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Combined particulates, acidic gas/vapour and organic vapour type
- Hand protection
- Material : Chemical-resistant gloves
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:  
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

---

### Section 9: Physical and chemical properties

- Appearance : liquid
- Colour : clear, colourless, yellow
- Odour : alcohol-like



# SAFETY DATA SHEET



## Capstone™ FS-93

Version 5.4	Revision Date: 10.02.2025	SDS Number: 2072683-00019	Date of last issue: 23.07.2024 Date of first issue: 11.10.2017
----------------	------------------------------	------------------------------	---

---

Odour Threshold	:	No data available
pH	:	7 - 7.5
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	83 °C
Flash point	:	34 °C Method: Pensky-Martens closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	1.18 g/cm <sup>3</sup>
Solubility(ies) Water solubility	:	soluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	> 200 °C
Viscosity Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics		

# SAFETY DATA SHEET



## Capstone™ FS-93

Version 5.4	Revision Date: 10.02.2025	SDS Number: 2072683-00019	Date of last issue: 23.07.2024 Date of first issue: 11.10.2017
----------------	------------------------------	------------------------------	---

---

Particle size : Not applicable

---

### Section 10: Stability and reactivity

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Flammable liquid and vapour.  
Vapours may form explosive mixture with air.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

#### Hazardous decomposition products

Thermal decomposition : hydrofluoric acid  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide

---

### Section 11: Toxicological information

Exposure routes : Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Harmful if inhaled.

#### Product:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 425  
Remarks: Based on data from similar materials

Acute inhalation toxicity : Acute toxicity estimate (Rat): 1.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement  
Remarks: Based on data from similar materials

#### Components:

##### Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

# SAFETY DATA SHEET



## Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2024
5.4	10.02.2025	2072683-00019	Date of first issue: 11.10.2017

---

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l  
Exposure time: 6 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

### Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 425  
Remarks: Based on data from similar materials

Acute inhalation toxicity : Acute toxicity estimate (Rat): 0.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement  
Remarks: Based on data from similar materials

### Skin corrosion/irritation

Not classified based on available information.

### Components:

#### Propan-2-ol:

Species : Rabbit  
Result : No skin irritation

### Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Components:

#### Propan-2-ol:

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

### Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

# SAFETY DATA SHEET



## Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2024
5.4	10.02.2025	2072683-00019	Date of first issue: 11.10.2017

---

Remarks : Based on data from similar materials

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

##### Propan-2-ol:

Test Type	: Buehler Test
Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

#### Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Test Type	: Local lymph node assay (LLNA)
Exposure routes	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative
Remarks	: Based on data from similar materials

### Chronic toxicity

#### Germ cell mutagenicity

Not classified based on available information.

#### Components:

##### Propan-2-ol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
	Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative

#### Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Germ cell mutagenicity -	: Weight of evidence does not support classification as a germ
--------------------------	--

# SAFETY DATA SHEET



## Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2024
5.4	10.02.2025	2072683-00019	Date of first issue: 11.10.2017

---

Assessment cell mutagen., Based on data from similar materials

### Carcinogenicity

Not classified based on available information.

### Components:

#### Propan-2-ol:

Species	: Rat
Application Route	: inhalation (vapour)
Exposure time	: 104 weeks
Method	: OECD Test Guideline 451
Result	: negative

### Reproductive toxicity

Not classified based on available information.

### Components:

#### Propan-2-ol:

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative
----------------------	---

Effects on foetal development	: Test Type: Embryo-foetal development Species: Rat Application Route: Ingestion Result: negative
-------------------------------	--

### Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Reproductive toxicity - Assessment	: Weight of evidence does not support classification for reproductive toxicity, Based on data from similar materials
------------------------------------	--

### STOT - single exposure

Causes damage to organs (Lungs, larynx) if inhaled.

### Product:

Exposure routes	: inhalation (dust/mist/fume)
Target Organs	: Lungs, larynx
Assessment	: Shown to produce significant health effects in animals at concentrations of 1.0 mg/l/4h or less.
Remarks	: Based on data from similar materials

### Components:

#### Propan-2-ol:

Assessment	: May cause drowsiness or dizziness.
------------	--------------------------------------

# SAFETY DATA SHEET



## Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2024
5.4	10.02.2025	2072683-00019	Date of first issue: 11.10.2017

---

### Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Exposure routes	: inhalation (dust/mist/fume)
Target Organs	: Lungs, larynx
Assessment	: Shown to produce significant health effects in animals at concentrations of 1.0 mg/l/4h or less.
Remarks	: Based on data from similar materials

### STOT - repeated exposure

Not classified based on available information.

### Repeated dose toxicity

#### Components:

##### Propan-2-ol:

Species	: Rat
NOAEL	: 12.5 mg/l
Application Route	: inhalation (vapour)
Exposure time	: 104 Weeks

### Aspiration toxicity

May be fatal if swallowed and enters airways.

#### Components:

##### Propan-2-ol:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

## Section 12: Ecological information

### Ecotoxicity

#### Product:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 526 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 526 mg/l Exposure time: 48 h Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (green algae)): > 526 mg/l Exposure time: 72 h Remarks: Based on data from similar materials  NOEC (Pseudokirchneriella subcapitata (green algae)): 526 mg/l

# SAFETY DATA SHEET



## Capstone™ FS-93

Version 5.4	Revision Date: 10.02.2025	SDS Number: 2072683-00019	Date of last issue: 23.07.2024 Date of first issue: 11.10.2017
----------------	------------------------------	------------------------------	---

---

Exposure time: 72 h  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 50 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### Components:

#### **Propan-2-ol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 24 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 1,050 mg/l  
Exposure time: 16 h

#### **Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 110 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 102 mg/l  
Exposure time: 48 h  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 105 mg/l  
Exposure time: 72 h  
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 105 mg/l  
Exposure time: 72 h  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 6.59 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### **Persistence and degradability**

#### Components:

#### **Propan-2-ol:**

Biodegradability : Result: rapidly degradable

# SAFETY DATA SHEET



## Capstone™ FS-93

Version 5.4	Revision Date: 10.02.2025	SDS Number: 2072683-00019	Date of last issue: 23.07.2024 Date of first issue: 11.10.2017
----------------	------------------------------	------------------------------	---

---

BOD/COD : BOD: 1,19 (BOD5)  
COD: 2,23  
BOD/COD: 53 %

### Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Biodegradability : Result: Not readily biodegradable.  
Remarks: Based on data from similar materials

### Bioaccumulative potential

#### Components:

##### Propan-2-ol:

Partition coefficient: n-octanol/water : log Pow: 0.05

##### Mobility in soil

No data available

##### Other adverse effects

No data available

---

## Section 13: Disposal considerations

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

---

## Section 14: Transport information

### International Regulations

#### UNRTDG

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Propan-2-ol)  
Class : 3  
Packing group : III



# SAFETY DATA SHEET



## Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2024
5.4	10.02.2025	2072683-00019	Date of first issue: 11.10.2017

---

Labels : 3  
Environmentally hazardous : no

### IATA-DGR

UN/ID No. : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(Propan-2-ol)  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

### IMDG-Code

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Propan-2-ol)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### NZS 5433

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Propan-2-ol)  
Class : 3  
Packing group : III  
Labels : 3  
Hazchem Code : 3Y  
Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## Section 15: Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### HSNO Approval Number

HSR002495 Additives Process Chemicals and Raw Materials Flammable Group Standard

# SAFETY DATA SHEET



## Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2024
5.4	10.02.2025	2072683-00019	Date of first issue: 11.10.2017

---

### Tolerable Exposure Limits (TEL)

Not applicable

### Environmental Exposure Limits (EEL)

Not applicable

### HSW Controls

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

---

## Section 16: Other information

Revision Date : 10.02.2025

Other information : Capstone™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.  
Chemours™ and the Chemours Logo are trademarks of The Chemours Company.  
Before use read Chemours safety information.  
For further information contact the local Chemours office or nominated distributors.

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
NZ OEL : New Zealand. Workplace Exposure Standards for Atmospheric Contaminants

ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
ACGIH / C : Ceiling limit  
NZ OEL / WES-TWA : Workplace Exposure Standard - Time Weighted average  
NZ OEL / WES-STEEL : Workplace Exposure Standard - Short-Term Exposure Limit  
NZ OEL / WES-Ceiling : Workplace Exposure Standard - Ceiling

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized Sys-

# SAFETY DATA SHEET



## Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 23.07.2024
5.4	10.02.2025	2072683-00019	Date of first issue: 11.10.2017

---

tem; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

NZ / EN