

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 08.01.2024
3.1	29.05.2024	2122163-00018	Date of first issue: 01.11.2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Capstone™ FS-50 Fluorosurfactant

SDS-Identcode : 130000042667

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)

Telephone : 55 5125 4907 in D.F. and metropolitan area - 800 737 5623
inside the Republic.

Emergency telephone : (ANIQ - SETIQ) 55 5559 1588 in CDMX and metropolitan
area; 800 002 1400 inside the Republic.

E-mail address : sds-support@chemours.com

Recommended use of the chemical and restrictions on use

Recommended use : Fluoroaddivitive

Restrictions on use : For industrial use only.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.

Precautionary Statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 08.01.2024
3.1	29.05.2024	2122163-00018	Date of first issue: 01.11.2017

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Inhalation of decomposition products in high concentration may cause shortness of breath (lung edema).

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Ethanol	64-17-5	≥ 30 -< 50

SECTION 4. FIRST AID MEASURES

- | | |
|---|---|
| If inhaled | : If inhaled, remove to fresh air.
Get medical attention if symptoms occur. |
| In case of skin contact | : Remove contaminated clothing and shoes. |
| In case of eye contact | : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists. |
| If swallowed | : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : Dizziness
Blurred vision
Headache
Irritation
Nausea
Pain
Lachrymation
Vomiting
Eye contact may provoke the following symptoms
tearing
Swelling of tissue
Redness
Impairment of vision |
| Protection of first-aiders | : No special precautions are necessary for first aid responders. |

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 08.01.2024
3.1	29.05.2024	2122163-00018	Date of first issue: 01.11.2017

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 08.01.2024
3.1	29.05.2024	2122163-00018	Date of first issue: 01.11.2017

Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- | | | |
|-----------------------------|---|---|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment. |
| Advice on safe handling | : | Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products. |
| Hygiene measures | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use. |
| Conditions for safe storage | : | Keep in properly labeled containers.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition. |
| Materials to avoid | : | Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Flammable solids |

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version 3.1 Revision Date: 29.05.2024 SDS Number: 2122163-00018 Date of last issue: 08.01.2024
Date of first issue: 01.11.2017

Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases
Very acutely toxic substances and mixtures

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	VLE-CT	1,000 ppm	NOM-010-STPS-2014
		STEL	1,000 ppm	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	VLE-PPT	0.5 ppm (Fluorine)	NOM-010-STPS-2014
		VLE-P	2 ppm (Fluorine)	NOM-010-STPS-2014
		TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
Carbonyl difluoride	353-50-4	VLE-PPT	2 ppm	NOM-010-STPS-2014
		VLE-CT	5 ppm	NOM-010-STPS-2014
		TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
Carbon dioxide	124-38-9	VLE-PPT	5,000 ppm	NOM-010-STPS-2014
		VLE-CT	30,000 ppm	NOM-010-STPS-2014
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
Carbon monoxide	630-08-0	VLE-PPT	25 ppm	NOM-010-STPS-2014
		TWA	25 ppm	ACGIH

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 08.01.2024
3.1	29.05.2024	2122163-00018	Date of first issue: 01.11.2017

Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates, acidic gas/vapor and organic vapor type

Hand protection

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : clear, amber

Odor : alcohol-like

Odor Threshold : No data available

pH : 5 - 7

Melting point/freezing point : No data available

Initial boiling point and boiling range : 82 °C

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 08.01.2024
3.1	29.05.2024	2122163-00018	Date of first issue: 01.11.2017

Flash point	:	25 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	53 hPa (20 °C)
Relative vapor density	:	No data available
Relative density	:	1
Solubility(ies) Water solubility	:	completely soluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	> 100 °C
Decomposition temperature	:	> 200 °C
Viscosity Viscosity, kinematic	:	9.7 mm²/s (20 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 08.01.2024
3.1	29.05.2024	2122163-00018	Date of first issue: 01.11.2017

temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride
Carbonyl difluoride
Carbon dioxide
Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Ethanol:

Acute oral toxicity : LD50 (Rat): 10,470 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male): 116.9 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 15,800 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Ethanol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Ethanol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 08.01.2024
3.1	29.05.2024	2122163-00018	Date of first issue: 01.11.2017

Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Ethanol:

Test Type	: Mouse ear swelling test (MEST)
Routes of exposure	: Skin contact
Species	: Mouse
Result	: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Ethanol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
-----------------------	---

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Ingestion Result: negative
----------------------	--

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

Ethanol:

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Mouse Application Route: Ingestion Result: negative
----------------------	---

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 08.01.2024
3.1	29.05.2024	2122163-00018	Date of first issue: 01.11.2017

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Ethanol:

Species	: Rat
NOAEL	: 1,730 mg/kg
LOAEL	: 3,200 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Ethanol:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 14,200 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Ceriodaphnia dubia (water flea)): 5,012 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	: ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Exposure time: 72 h EC10 (Chlorella vulgaris (Fresh water algae)): 11.5 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC (Oryzias latipes (Japanese medaka)): >= 79 mg/l Exposure time: 100 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 9.6 mg/l Exposure time: 9 d
Toxicity to microorganisms	: EC50 (Protozoa): 5,800 mg/l Exposure time: 4 h

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 08.01.2024
3.1	29.05.2024	2122163-00018	Date of first issue: 01.11.2017

Persistence and degradability

Components:

Ethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 84 %
Exposure time: 20 d

Bioaccumulative potential

Components:

Ethanol:

Partition coefficient: n- : log Pow: -0.35
octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1170
Proper shipping name : ETHANOL SOLUTION
Class : 3
Packing group : III
Labels : 3
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 1170
Proper shipping name : Ethanol solution

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 08.01.2024
3.1	29.05.2024	2122163-00018	Date of first issue: 01.11.2017

Class	: 3
Packing group	: III
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 366
Packing instruction (passenger aircraft)	: 355

IMDG-Code

UN number	: UN 1170
Proper shipping name	: ETHANOL SOLUTION (Carboxymethyldimethyl-3-[[[(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide])

Class	: 3
Packing group	: III
Labels	: 3
EmS Code	: F-E, S-D
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

NOM-002-SCT

UN number	: UN 1170
Proper shipping name	: ETHANOL SOLUTION
Class	: 3
Packing group	: III
Labels	: 3

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Federal Law for the control of chemical precursors, essential chemical products and machinery for producing capsules, tablets and pills.	: Butanone
--	------------

SECTION 16. OTHER INFORMATION

Revision Date	: 29.05.2024
Date format	: dd.mm.yyyy

Capstone™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 08.01.2024
3.1	29.05.2024	2122163-00018	Date of first issue: 01.11.2017

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NOM-010-STPS-2014	:	Mexico. Norm NOM-010-STPS-2014 on Chemicals Polluting the Work Environment - Identification, Assessment and Control - Appendix 1 Occupational Exposure Limits
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NOM-010-STPS-2014 / VLE-	:	Time weighted average limit value
PPT	:	
NOM-010-STPS-2014 / VLE-	:	Short term exposure limit value
CT	:	
NOM-010-STPS-2014 / VLE-	:	Ceiling value
P	:	

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
--	---	---

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 08.01.2024
3.1	29.05.2024	2122163-00018	Date of first issue: 01.11.2017

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

MX / Z8