

## 1. Identification

<b>Product identifier</b>	<b>BEHR® PREMIUM Exterior Elastomeric Masonry, Stucco &amp; Brick Paint - White</b>		
<b>Other means of identification</b>			
<b>Product number</b>	068		
<b>Recommended use</b>	Architectural Coating		
<b>Recommended restrictions</b>	None known.		
<b>Manufacturer/Importer/Supplier/Distributor information</b>			
<b>Supplier</b>	Behr Process Canada, Ltd. 2750 Centre Avenue N.E. Calgary, AB T2A 2L3		
<b>Emergency telephone</b>	(US)+1 760 476 3962 (US)+1 866 519 4752		
<b>Access code</b>	335213		

## 2. Hazard identification

Physical hazards	Not classified.		
Health hazards	Carcinogenicity	Category 2	
Label elements			



<b>Signal word</b>	Warning		
<b>Hazard statement</b>	Suspected of causing cancer.		
<b>Precautionary statement</b>			
<b>Prevention</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.		
<b>Response</b>	IF exposed or concerned: Get medical advice/attention.		
<b>Storage</b>	Store locked up.		
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.		
<b>Other hazards</b>	None known.		
<b>Supplemental information</b>	None.		

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Titanium dioxide		13463-67-7	10 - 30
Cristobalite		14464-46-1	1 - 5
Diuron		330-54-1	0.1 - 1
Flux Calcined Diatomaceous Earth (DE)		68855-54-9	0.1 - 1
Quartz (crystalline silica)		14808-60-7	0.1 - 1

<b>Composition comments</b>	<p>All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.</p> <p>The exact concentrations of the above listed chemicals are being withheld as a trade secret.</p>
<b>4. First-aid measures</b>	
<b>Inhalation</b>	Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Wash off with soap and water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. Get medical attention if symptoms occur.
<b>Most important symptoms/effects, acute and delayed</b>	Direct contact with eyes may cause temporary irritation.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
<b>5. Fire-fighting measures</b>	
<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.
<b>6. Accidental release measures</b>	
<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	<p>This product is miscible in water.</p> <p>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.</p> <p>Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p> <p>Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.</p>
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.
<b>7. Handling and storage</b>	
<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
<b>Conditions for safe storage, including any incompatibilities</b>	Store locked up. Store in tightly closed container. Store away from incompatible materials (see section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Diuron (CAS 330-54-1)	TWA	10 mg/m3	
Quartz (crystalline silica) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable particles.
		0.025 mg/m3	Respirable.
Diuron (CAS 330-54-1)	TWA	10 mg/m3	
Quartz (crystalline silica) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

#### Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Diuron (CAS 330-54-1)	TWA	10 mg/m3	
Quartz (crystalline silica) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.

#### Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Diuron (CAS 330-54-1)	TWA	10 mg/m3	
Quartz (crystalline silica) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

#### Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable fraction.
Diuron (CAS 330-54-1)	TWA	10 mg/m3	
Quartz (crystalline silica) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

#### Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.

**Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)**

Components	Type	Value	Form
Diuron (CAS 330-54-1)	TWA	10 mg/m3	
Quartz (crystalline silica) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Total dust.

**Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)**

Components	Type	Value	Form
Cristobalite (CAS 14464-46-1)	15 minute	10 mg/m3	Inhalable fraction.
	8 hour	0.05 mg/m3	Respirable fraction.
Diuron (CAS 330-54-1)	15 minute	20 mg/m3	
	8 hour	10 mg/m3	
Quartz (crystalline silica) (CAS 14808-60-7)	8 hour	0.05 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	15 minute	20 mg/m3	
	8 hour	10 mg/m3	

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Appropriate engineering controls**

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Wear appropriate chemical resistant gloves.

**Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance****Physical state**

Liquid.

**Form**

Liquid.

**Colour**

White.

**Odour**

Slight.

**Odour threshold**

Not available.

**pH**

7 - 10

**Melting point/freezing point**

Not available.

**Initial boiling point and boiling range**

> 37.2 °C (> 99 °F)

**Flash point**

Not available.

**Evaporation rate**

Not available.

**Flammability (solid, gas)**

Not applicable.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)** Not available.

**Flammability limit - upper (%)** Not available.

**Vapour pressure** Not available.

**Vapour density** Not available.

**Relative density** 1.35

**Solubility(ies)**

**Solubility (water)** Soluble.

**Partition coefficient (n-octanol/water)** Not available.

**Auto-ignition temperature** Not available.

**Decomposition temperature** Not available.

**Viscosity** 50 - 140 KU (25 °C)

**Other information**

**Density** 11.26 lbs/gal

**Explosive properties** Not explosive.

**Oxidising properties** Not oxidising.

**VOC** 12 g/l (including water) (Material)  
24 g/l (excluding water) (Coating)

**10. Stability and reactivity**

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

**Possibility of hazardous reactions** No dangerous reaction known under conditions of normal use.

**Conditions to avoid** Contact with incompatible materials.

**Incompatible materials** Fluorine.

**Hazardous decomposition products** No hazardous decomposition products are known.

**11. Toxicological information****Information on likely routes of exposure**

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact** Prolonged skin contact may cause temporary irritation.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics** Direct contact with eyes may cause temporary irritation.

**Information on toxicological effects****Acute toxicity**

Components	Species	Test Results
Quartz (crystalline silica) (CAS 14808-60-7)		
<b><u>Chronic</u></b>		
<b>Inhalation</b>		
LOEC	Human	0.0563 mg/m3
Titanium dioxide (CAS 13463-67-7)		
<b><u>Acute</u></b>		
<b>Inhalation</b>		
LC50	Rat	3.43 mg/l, 4 Hours

Components	Species	Test Results
Oral LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitisation		
Canada - Alberta OELs: Irritant		
Cristobalite (CAS 14464-46-1)		Irritant
Diuron (CAS 330-54-1)		Irritant
Titanium dioxide (CAS 13463-67-7)		Irritant
Respiratory sensitisation	Not a respiratory sensitiser.	
Skin sensitisation	This product is not expected to cause skin sensitisation.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
ACGIH Carcinogens		
Cristobalite (CAS 14464-46-1)		A2 Suspected human carcinogen.
Diuron (CAS 330-54-1)		A4 Not classifiable as a human carcinogen.
Quartz (crystalline silica) (CAS 14808-60-7)		A2 Suspected human carcinogen.
Titanium dioxide (CAS 13463-67-7)		A4 Not classifiable as a human carcinogen.
Canada - Alberta OELs: Carcinogen category		
Cristobalite (CAS 14464-46-1)		Suspected human carcinogen.
Quartz (crystalline silica) (CAS 14808-60-7)		Suspected human carcinogen.
Canada - Manitoba OELs: carcinogenicity		
Cristobalite (CAS 14464-46-1)		Suspected human carcinogen.
Diuron (CAS 330-54-1)		Not classifiable as a human carcinogen.
Quartz (crystalline silica) (CAS 14808-60-7)		Suspected human carcinogen.
Titanium dioxide (CAS 13463-67-7)		Not classifiable as a human carcinogen.
Canada - Quebec OELs: Carcinogen category		
Cristobalite (CAS 14464-46-1)		Detected carcinogenic effect in animals.
Quartz (crystalline silica) (CAS 14808-60-7)		Suspected carcinogenic effect in humans.
IARC Monographs. Overall Evaluation of Carcinogenicity		
Cristobalite (CAS 14464-46-1)		1 Carcinogenic to humans.
Quartz (crystalline silica) (CAS 14808-60-7)		1 Carcinogenic to humans.
Titanium dioxide (CAS 13463-67-7)		2B Possibly carcinogenic to humans.
US. National Toxicology Program (NTP) Report on Carcinogens		
Cristobalite (CAS 14464-46-1)		Known To Be Human Carcinogen.
		Reasonably Anticipated to be a Human Carcinogen.
Quartz (crystalline silica) (CAS 14808-60-7)		Known To Be Human Carcinogen.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful.	
12. Ecological information		
Ecotoxicity	Harmful to aquatic life with long lasting effects.	
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.	
Bioaccumulative potential	No data available.	
Mobility in soil	No data available.	
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.	

### 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

<b>TDG</b>	Not regulated as dangerous goods.
<b>IATA</b>	Not regulated as dangerous goods.
<b>IMDG</b>	Not regulated as dangerous goods.
<b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not applicable.

### 15. Regulatory information

<b>Canadian regulations</b>	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.
<b>Controlled Drugs and Substances Act</b>	Not regulated.
<b>Export Control List (CEPA 1999, Schedule 3)</b>	Not listed.
<b>Greenhouse Gases</b>	Not listed.
<b>Precursor Control Regulations</b>	Not regulated.
<b>International regulations</b>	
<b>Stockholm Convention</b>	Not applicable.
<b>Rotterdam Convention</b>	Not applicable.
<b>Kyoto Protocol</b>	Not applicable.
<b>Montreal Protocol</b>	Not applicable.
<b>Basel Convention</b>	Not applicable.

### 16. Other information

<b>Issue date</b>	16-January-2020
<b>Revision date</b>	-
<b>Version No.</b>	01

**List of abbreviations**

IATA: International Air Transport Association.  
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.  
IMDG Code: International Maritime Dangerous Goods Code.  
LC50: Lethal Concentration, 50%.  
LD50: Lethal Dose, 50%.  
LOEC: Lowest observable effect concentration.  
MARPOL: International Convention for the Prevention of Pollution from Ships.  
TDG: Transportation of Dangerous Goods.  
TWA: Time Weighted Average Value.

**References**

HSDB® - Hazardous Substances Data Bank  
IARC Monographs. Overall Evaluation of Carcinogenicity

**Disclaimer**

Behr Process Corp cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.