

## SAFETY DATA SHEET

### SECTION 1 : IDENTIFICATION

Product Name: **BEHR Chalk Decorative Wax - Clear**  
Product Code: 7140  
SDS Manufacturer Number: 7140  
Manufacturer Name: BEHR Process Corporation  
Address: 1801 E. St. Andrew Place  
Santa Ana, CA 92705  
(714) 545-7101  
(800) 854-0133 ext. 2  
General Phone Number:  
Customer Service Phone Number:  
Emergency Phone Number: For emergencies in the US & Canada, call Verisk 3E: 866-519-4752  
Access Code: 335213  
SDS Creation Date: October 04, 2018  
SDS Revision Date: October 04, 2018

### SECTION 2 : HAZARD(S) IDENTIFICATION

GHS Pictograms:



Signal Word:

Danger

GHS Class:

Flammable Solids, Category 2  
Aspiration Toxicity, Category 1

Hazard Statements:

Flammable solid.  
Heating may cause a fire.

Precautionary Statements:

Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone.  
In case of fire: Use dry chemical, carbon dioxide to extinguish small fires. Use water for large fires.  
Wear protective clothing, gloves, eye, and face protection.  
Do not breathe vapors.  
Do not eat, drink or smoke when using this product.  
Wash hands thoroughly after handling.  
Take off contaminated clothing and wash it before reuse.  
Keep container tightly closed.  
Store locked up in a cool, well-ventilated place.  
Dispose of unused contents, container, and other contaminated wastes in accordance with local, state, federal, and provincial regulations.  
**If in eyes:** Contaminated work clothing should not be allowed out of the workplace.  
**If on skin or hair:** Wash with plenty of soap and water. If skin irritation or rash occurs, get medical attention.  
**If inhaled:** Leave the area if you experience headaches, drowsiness or dizziness to obtain fresh air and keep at rest in a position comfortable for breathing. If difficulty continues, get medical attention immediately.  
**If swallowed:** Do not induce vomiting and get medical attention immediately.

Emergency Overview:

DANGER. Flammable. Harmful if swallowed. Harmful if inhaled. Inhalation of vapors may cause drowsiness and dizziness. Irritant.

Route of Exposure:

Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Eye:

Direct contact may cause irritation.

Skin:

Causes skin irritation.

Inhalation:

Harmful if inhaled. Inhalation of vapors may cause drowsiness and dizziness. Prolonged or excessive inhalation may cause respiratory tract irritation.

Ingestion:

Harmful if swallowed. Ingestion can cause nausea, vomiting, diarrhea and gastrointestinal irritation. Aspiration of petroleum distillates into the lungs can cause severe chemical pneumonitis that can be fatal.

Chronic Health Effects:

Prolonged or repeated contact can result in defatting and drying of the skin, which may result in skin irritation and dermatitis (rash).  
Repeated or prolonged inhalation may cause toxic effects.

Signs/Symptoms:

Overexposure can cause headaches, dizziness, nausea, and vomiting.

Target Organs:

Eyes. Skin. Respiratory system. Digestive system. Central nervous system. Kidney.

Aggravation of Pre-Existing Conditions:

May aggravate pre-existing allergy, eczema, or skin conditions.

### SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

Naphtha (petroleum), hydrotreated heavy 64742-48-9 60 - 100 by weight

#### SECTION 4 : FIRST AID MEASURES

<b>Eye Contact:</b>	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing. Get medical attention, if irritation or symptoms of overexposure persists.
<b>Skin Contact:</b>	Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
<b>Inhalation:</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
<b>Ingestion:</b>	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
<b>Other First Aid:</b>	Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

#### SECTION 5 : FIRE FIGHTING MEASURES

<b>Flash Point:</b>	122 °F (50 °C)
<b>Flash Point Method:</b>	ASTM D-56
<b>Auto Ignition Temperature:</b>	No Data
<b>Lower Flammable/Explosive Limit:</b>	No Data
<b>Upper Flammable/Explosive Limit:</b>	No Data
<b>Fire Fighting Instructions:</b>	Flammable. Cool fire-exposed containers using water spray.
<b>Extinguishing Media:</b>	Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.
<b>Unsuitable Media:</b>	Water jet.
<b>Protective Equipment:</b>	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
<b>Unusual Fire Hazards:</b>	Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back.
<b>NFPA Ratings:</b>	
NFPA Health:	1
NFPA Flammability:	3
NFPA Reactivity:	1

#### SECTION 6 : ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions:</b>	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use proper personal protective equipment as listed in Section 8.
<b>Environmental Precautions:</b>	Avoid runoff into storm sewers, ditches, and waterways.
<b>Methods for containment:</b>	Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by covering, diking or other means. Provide ventilation. Eliminate all ignition sources including those beyond the immediate spill area if safe to do so.
<b>Methods for cleanup:</b>	Clean up spills immediately observing precautions in the protective equipment section. Collect spill with a non-sparking tool. Place into a suitable container for disposal. Take precautionary measures against static discharges. After removal, flush spill area with soap and water to remove trace residue.

#### SECTION 7 : HANDLING and STORAGE

<b>Handling:</b>	Handle with care. Avoid contact with eyes, skin, or clothing. Extinguish all smoking or other ignition sources. Use only in accordance with directions.
<b>Storage:</b>	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use.
<b>Special Handling Procedures:</b>	Do not reuse containers without proper cleaning or reconditioning.
<b>Hygiene Practices:</b>	Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

#### SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

<b>Engineering Controls:</b>	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
<b>Eye/Face Protection:</b>	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
<b>Skin Protection Description:</b>	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.
<b>Respiratory Protection:</b>	Consult a safety professional/industrial hygienist for guidance.
<b>Other Protective:</b>	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.
<b>PPE Pictograms:</b>	

**EXPOSURE GUIDELINES**

**Naphtha (petroleum), hydrotreated heavy :**

<b>Guideline ACGIH:</b>	TWA: 2 mg/m3 fume
<b>Guideline OSHA:</b>	TWA: 2 mg/m3 fume (vacated)
<b>Guideline NIOSH:</b>	TWA: 2 mg/m3 fume

**SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES**

<b>Physical State:</b>	Paste.
<b>Color:</b>	Pale yellow.
<b>Odor:</b>	Slight.
<b>Odor Threshold:</b>	No Data
<b>Boiling Point:</b>	No Data
<b>Melting Point:</b>	No Data
<b>Density:</b>	6.75 lb/gl
<b>Specific Gravity:</b>	0.8
<b>Solubility:</b>	Insoluble.
<b>Vapor Density:</b>	No Data
<b>Vapor Pressure:</b>	No Data
<b>Evaporation Rate:</b>	0.2 (BuAc = 1)
<b>pH:</b>	Not applicable.
<b>Coefficient of Water/Oil Distribution:</b>	None.
<b>Flammability:</b>	No Data
<b>Flash Point:</b>	122 °F (50 °C)
<b>Flash Point Method:</b>	ASTM D-56
<b>Auto Ignition Temperature:</b>	No Data

**SECTION 10 : STABILITY and REACTIVITY**

<b>Chemical Stability:</b>	Stable under normal temperatures and pressures.
<b>Hazardous Polymerization:</b>	Not reported.
<b>Conditions to Avoid:</b>	Keep away from heat, sparks and open flames.
<b>Incompatible Materials:</b>	No Data

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**Naphtha (petroleum), hydrotreated heavy :**

<b>Skin:</b>	L50: > 3600 mg/kg ( Rabbit )
<b>Ingestion:</b>	LD50: > 5000 mg/kg ( Rat )

**SECTION 12 : ECOLOGICAL INFORMATION**

Environmental Fate: No environmental information found for this product.

**Naphtha (petroleum), hydrotreated heavy :**

Ecotoxicity: Toxicity to Fish: 96h LC50: = 2200 mg/L (Pimephales promelas)  
Daphnia Magna: 96h LC50: = 2.6 mg/L

**SECTION 13 : DISPOSAL CONSIDERATIONS**

**Waste Disposal:** This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

**SECTION 14 : TRANSPORT INFORMATION**

**DOT Shipping Name:** Flammable Solid, Organic, N.O.S.  
**DOT UN Number:** UN1325  
**DOT Hazard Class:** 4.1  
**DOT Packing Group:** III

**IATA Shipping Name:** FLAMMABLE SOLID, ORGANIC, N.O.S.  
**IATA UN Number:** UN1325  
**IATA Hazard Class:** 4.1  
**IATA Packing Group:** III

**IMDG UN Number :** UN1325  
**IMDG Shipping Name :** FLAMMABLE SOLID, ORGANIC, N.O.S.  
**IMDG Hazard Class :** 4.1  
**IMDG Packing Group :** III

**SECTION 15 : REGULATORY INFORMATION**

**Section 313:** EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.

**Naphtha (petroleum), hydrotreated heavy :**

**TSCA Inventory Status:** Listed  
**Canada DSL:** Listed

**SECTION 16 : ADDITIONAL INFORMATION**

**HMIS Ratings:**

**HMIS Health Hazard:** 2  
**HMIS Fire Hazard:** 2  
**HMIS Reactivity:** 0  
**HMIS Personal Protection:** B

**SDS Creation Date:** October 04, 2018  
**SDS Revision Date :** October 04, 2018