

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

SECTION 1. IDENTIFICATION

Product name : Ti-Pure™ TS-6200 Titanium Dioxide Pigment

SDS-Identcode : 130000018855

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Pigment

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version 7.0 Revision Date: 10/26/2023 SDS Number: 1579560-00013 Date of last issue: 04/11/2023
Date of first issue: 04/28/2017

Response:

P308 + P313 IF exposed or concerned: Get medical attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Dust contact with the eyes can lead to mechanical irritation.
Contact with dust can cause mechanical irritation or drying of the skin.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Titanium dioxide	No data available	13463-67-7	$\geq 80 - \leq 100$ *
Silicon dioxide, amorphous	Silica	7631-86-9	$\geq 1 - < 5$ *
Aluminium hydroxide	No data available	21645-51-2	$\geq 1 - < 5$ *
Trimethylolpropane	No data available	77-99-6	$\geq 0.1 - < 1$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : If in eyes, rinse well with water.
Get medical attention if irritation develops and persists.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	: irritant effects Suspected of damaging fertility. Suspected of damaging the unborn child. Contact with dust can cause mechanical irritation or drying of the skin. Dust contact with the eyes can lead to mechanical irritation.
Protection of first-aiders	: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
Notes to physician	: Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Not applicable Will not burn
Unsuitable extinguishing media	: Not applicable Will not burn
Specific hazards during fire fighting	: Exposure to combustion products may be a hazard to health.
Hazardous combustion products	: Metal oxides
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
Environmental precautions	: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version 7.0 Revision Date: 10/26/2023 SDS Number: 1579560-00013 Date of last issue: 04/11/2023
Date of first issue: 04/28/2017

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not breathe dust.
Do not swallow.
Avoid contact with eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Minimize dust generation and accumulation.
Keep container closed when not in use.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Titanium dioxide	13463-67-7	TWA	10 mg/m ³	CA AB OEL
		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m ³	CA BC OEL
		TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA (Respi-	2.5 mg/m ³	ACGIH

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version 7.0 Revision Date: 10/26/2023 SDS Number: 1579560-00013 Date of last issue: 04/11/2023
Date of first issue: 04/28/2017

		able particulate matter)	(Titanium dioxide)	
Silicon dioxide, amorphous	7631-86-9	TWAEV (respirable dust)	6 mg/m ³	CA QC OEL
Aluminium hydroxide	21645-51-2	TWA (Respirable)	1 mg/m ³ (Aluminum)	CA BC OEL
		TWAEV (respirable dust)	5 mg/m ³	CA QC OEL
		TWA (Respirable particulate matter)	1 mg/m ³ (Aluminum)	ACGIH

Engineering measures : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Particulates type

Hand protection

Material : Chemical-resistant gloves

Remarks : For prolonged or repeated contact use protective gloves. Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment: Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the wor-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

king place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	powder
Color	:	white
Odor	:	odorless
Odor Threshold	:	No data available
pH	:	4
Melting point/freezing point	:	1,843 °C
Initial boiling point and boiling range	:	3,000 °C
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Will not burn
		Not expected to form explosive dust-air mixtures.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	3.4 - 4.3
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

Decomposition temperature : The substance or mixture is not classified self-reactive.

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : None known.

Conditions to avoid : None known.

Incompatible materials : None.

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation

Skin contact

Ingestion

Eye contact

Acute toxicity

Not classified based on available information.

Components:

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 425

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

Acute dermal toxicity : Acute toxicity estimate (Rat): > 2,000 mg/kg
Method: Expert judgment
Assessment: The substance or mixture has no acute dermal toxicity

Silicon dioxide, amorphous:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Aluminium hydroxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 5.09 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Trimethylolpropane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 0.85 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Titanium dioxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Silicon dioxide, amorphous:

Species : Rabbit

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

Method	: OECD Test Guideline 404
Result	: No skin irritation

Aluminium hydroxide:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Trimethylolpropane:

Species	: Rabbit
Result	: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Titanium dioxide:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Silicon dioxide, amorphous:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Aluminium hydroxide:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Trimethylolpropane:

Species	: Rabbit
Result	: No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Titanium dioxide:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

Method	: OECD Test Guideline 406
Result	: negative

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative

Routes of exposure	: Inhalation
Species	: Mouse
Result	: negative

Routes of exposure	: Inhalation
Species	: Humans
Result	: negative

Aluminium hydroxide:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Trimethylolpropane:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Titanium dioxide:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
	Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
	Test Type: comet assay Method: OPPTS 870.5140 Result: positive

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

Genotoxicity in vivo	: Test Type: In vivo mammalian alkaline comet assay Species: Rat Application Route: intratracheal Method: OECD Test Guideline 489 Result: negative Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Ingestion Method: OECD Test Guideline 474 Result: negative Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 475 Result: negative Test Type: Transgenic rodent germ cell gene mutation assay Species: Mouse Application Route: Intravenous injection Method: OECD Test Guideline 488 Result: negative
Germ cell mutagenicity - Assessment	: Weight of evidence does not support classification as a germ cell mutagen.

Silicon dioxide, amorphous:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
Genotoxicity in vivo	: Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat Application Route: Ingestion Result: negative
Germ cell mutagenicity - Assessment	: Weight of evidence does not support classification as a germ cell mutagen.

Aluminium hydroxide:

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative Test Type: Chromosome aberration test in vitro Result: positive Remarks: Based on data from similar materials
-----------------------	---

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

Genotoxicity in vivo	:	Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro) Result: equivocal Remarks: Based on data from similar materials
	:	Test Type: in vitro micronucleus test Result: positive Remarks: Based on data from similar materials
	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Ingestion Method: OECD Test Guideline 474 Result: negative

Trimethylolpropane:

Genotoxicity in vitro	:	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
-----------------------	---	--

Carcinogenicity

Not classified based on available information.

Product:

Remarks	:	<p>In lifetime inhalation studies rats were exposed for 2 years to respectively 10, 50 and 250 mg/m³ of respirable TiO₂. Slight lung fibrosis was observed at 50 and 250 mg/m³ levels. Microscopic lung tumours were also observed in 13 percent of the rats exposed to 250 mg/m³, an exposure level that caused lung overloading and impairment of rat lungs clearance mechanisms.</p> <p>In further studies, these tumours were found to occur only under particle overload conditions in a uniquely sensitive species, the rat, and have little or no relevance for humans. The pulmonary inflammatory response to TiO₂ particles exposure was also found to be much more severe in rats than in other rodent species.</p> <p>In February 2006, IARC has re-evaluated Titanium dioxide as pertaining to Group 2B: "possibly carcinogenic to humans", based upon inadequate evidence in humans and sufficient evidence in experimental animals for the carcinogenicity of titanium dioxide. IARC evaluation guidelines consider the generation of tumours, in 2 different studies within the same animal species, to be adequate criteria for an assessment of sufficient evidence.</p> <p>The conclusions of several epidemiology studies on more than 20000 TiO₂ industry workers in Europe and the USA did not suggest a carcinogenic effect of TiO₂ dust on the human lung. Mortality from other chronic diseases, including other respiratory diseases, was also not associated with exposure to TiO₂ dust.</p>
---------	---	--

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

Based upon all available study results, Chemours scientists conclude that titanium dioxide will not cause lung cancer or chronic respiratory diseases in humans at concentrations experienced in the workplace.

Components:

Titanium dioxide:

Species	: Rat
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 2 Years
Result	: negative

Species	: Rat
Application Route	: Ingestion
Exposure time	: 105 weeks
Result	: negative

Species	: Mouse
Application Route	: Ingestion
Exposure time	: 103 weeks
Result	: negative

Application Route	: inhalation (dust/mist/fume)
Exposure time	: 2 Years
Method	: OECD Test Guideline 453
Result	: positive
Remarks	: The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment	: Weight of evidence does not support classification as a carcinogen
------------------------------	--

Silicon dioxide, amorphous:

Species	: Rat
Application Route	: Ingestion
Exposure time	: 103 weeks
Result	: negative

Carcinogenicity - Assessment	: Weight of evidence does not support classification as a carcinogen
------------------------------	--

Aluminium hydroxide:

Species	: Rat
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 86 weeks
Result	: negative
Remarks	: Based on data from similar materials

Reproductive toxicity

Suspected of damaging fertility. Suspected of damaging the unborn child.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

Components:

Titanium dioxide:

- | | |
|------------------------------------|--|
| Effects on fertility | : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 443
Result: negative |
| Effects on fetal development | : Test Type: Prenatal development toxicity study (teratogenicity)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative |
| Reproductive toxicity - Assessment | : Weight of evidence does not support classification for reproductive toxicity |

Silicon dioxide, amorphous:

- | | |
|------------------------------------|---|
| Effects on fetal development | : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative |
| Reproductive toxicity - Assessment | : Weight of evidence does not support classification for reproductive toxicity |

Aluminium hydroxide:

- | | |
|------------------------------|--|
| Effects on fertility | : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials |
| Effects on fetal development | : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative |

Trimethylolpropane:

- | | |
|------------------------------|---|
| Effects on fertility | : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: positive |
| Effects on fetal development | : Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 443
Result: positive |

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments., Some evidence of adverse effects on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

Components:

Titanium dioxide:

Routes of exposure : Skin contact
Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

Routes of exposure : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

Routes of exposure : inhalation (dust/mist/fume)
Assessment : No significant health effects observed in animals at concentrations of 5.0 mg/l/4h or less

STOT-repeated exposure

Not classified based on available information.

Components:

Titanium dioxide:

Routes of exposure : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Routes of exposure : inhalation (dust/mist/fume)
Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Routes of exposure : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

Repeated dose toxicity

Components:

Titanium dioxide:

Species : Rat, male and female
NOAEL : 24,000 mg/kg
LOAEL : > 24,000 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 407
Remarks : No significant adverse effects were reported

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

Species	: Rat, male and female
NOAEL	: 0.01 mg/l
LOAEL	: 0.5 mg/l
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 24 Months
Method	: OECD Test Guideline 453
Remarks	: No significant adverse effects were reported

Species	: Rat, male and female
NOAEL	: 962 mg/kg
LOAEL	: > 962 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days
Method	: OECD Test Guideline 408
Remarks	: No significant adverse effects were reported

Silicon dioxide, amorphous:

Species	: Rat
NOAEL	: 1.3 mg/m ³
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 13 Weeks

Aluminium hydroxide:

Species	: Rat
NOAEL	: > 100 mg/kg
Application Route	: Ingestion
Exposure time	: 364 Days
Method	: OECD Test Guideline 426
Remarks	: Based on data from similar materials

Species	: Rat
NOAEL	: > 0.2 mg/kg
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 12 Months
Remarks	: Based on data from similar materials

Trimethylolpropane:

Species	: Rat
NOAEL	: 67 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

Aspiration toxicity

Not classified based on available information.

Components:

Titanium dioxide:

|| No aspiration toxicity classification

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Titanium dioxide:

Toxicity to fish	: LC50 (Fish): > 1,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 LC50 (Marine species): > 10,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia sp. (Water flea)): > 1,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 EC50 (No species specified): > 1,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l Exposure time: 72 h Method: ISO 10253 NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 3 d Method: OECD Test Guideline 201 NOEC (Skeletonema costatum (marine diatom)): 5,600 mg/l Exposure time: 3 d Method: ISO 10253

Silicon dioxide, amorphous:

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 10,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 24 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EC50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l Exposure time: 72 h

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): 10,000 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Aluminium hydroxide:

Toxicity to fish : LL50 (Salmo trutta (brown trout)): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EL50 (Selenastrum capricornutum (green algae)): > 100 mg/l
Exposure time: 96 h

Trimethylolpropane:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 1,000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 13,000 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 21 d

Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h

Persistence and degradability

Components:

Trimethylolpropane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 6 %
Exposure time: 28 d

Bioaccumulative potential

Components:

Titanium dioxide:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

|| Bioconcentration factor (BCF): 352

Trimethylolpropane:

|| Partition coefficient: n-octanol/water : log Pow: -0.47

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

|| Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.

|| Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

SECTION 16. OTHER INFORMATION

Ti-Pure™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

These products may not be directly added to food, pharmaceuticals, cosmetics, or cigarette papers/filters for tobacco products.

Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

In the manufacture of titanium dioxide, product is packaged at temperatures of approximately 100 to 120°C (212 to 248°F). When pigment is shipped shortly after manufacture, it may stay hot for a very long time depending on ambient temperatures and inventory storage practices. Use caution while handling hot pigment to prevent burns to personnel. Use caution in solvent applications to prevent ignition of solvent.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWA EV	:	Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumu-

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Ti-Pure™ TS-6200 Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 04/11/2023
7.0	10/26/2023	1579560-00013	Date of first issue: 04/28/2017

lative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/26/2023
Date format : mm/dd/yyyy

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8