

SAFETY DATA SHEET



Capstone™ ST-500

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 30.05.2024 |
| 9.0 | 23.09.2024 | 1339672-00052 | Date of first issue: 27.02.2017 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capstone™ ST-500

SDS-Identcode : 130000107333

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Stain and soil repellent

Recommended restrictions on use : For industrial use only.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

1.3 Details of the supplier of the safety data sheet

Company : Chemours (France) S.A.S.
Rue Frederic Kuhlmann
60870 Villers-Saint-Paul France

Telephone : +33 (0) 3 44 74 44 58

E-mail address of person responsible for the SDS : sds-support@chemours.com

1.4 Emergency telephone number

+(44)-870-8200418 (CHEMTREC - Recommended)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

|| Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

|| No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

Additional Labelling

|| EUH210 Safety data sheet available on request.

SAFETY DATA SHEET



Capstone™ ST-500

Version 9.0 Revision Date: 23.09.2024 SDS Number: 1339672-00052 Date of last issue: 30.05.2024
Date of first issue: 27.02.2017

|| EUH208 Contains 1,2-Benzisothiazol-3(2H)-one. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Inhalation of decomposition products in high concentration may cause shortness of breath (lung oedema).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|------------------------------|---|---|--------------------------|
| 1,2-Benzisothiazol-3(2H)-one | 2634-33-5 220-120-9 613-088-00-6 | Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 | ≥ 0.025 - < 0.036 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

|| Protection of first-aiders : No special precautions are necessary for first aid responders.

|| If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

|| In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.

|| In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

SAFETY DATA SHEET



Capstone™ ST-500

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 30.05.2024 |
| 9.0 | 23.09.2024 | 1339672-00052 | Date of first issue: 27.02.2017 |

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:
Lung oedema
Shortness of breath

Eye contact may provoke the following symptoms
tearing
Redness
Discomfort

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates
Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SAFETY DATA SHEET



Capstone™ ST-500

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 30.05.2024 |
| 9.0 | 23.09.2024 | 1339672-00052 | Date of first issue: 27.02.2017 |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami-

SAFETY DATA SHEET



Capstone™ ST-500

Version 9.0 Revision Date: 23.09.2024 SDS Number: 1339672-00052 Date of last issue: 30.05.2024
Date of first issue: 27.02.2017

|| nated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Gases

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

Occupational exposure limits of decomposition products

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|---------------------|--|-------------------------------|--------------------------|-------------|
| hydrofluoric acid | 7664-39-3 | TWA | 1.8 ppm 1.5 mg/m3 | 2000/39/EC |
| | Further information: Indicative | | | |
| | | STEL | 3 ppm 2.5 mg/m3 | 2000/39/EC |
| | Further information: Indicative | | | |
| Carbonyl difluoride | 353-50-4 | TWA | 2.5 mg/m3 (Fluorine) | 2000/39/EC |
| | Further information: Indicative | | | |
| Carbon dioxide | 124-38-9 | TWA | 5,000 ppm 9,000 mg/m3 | 2006/15/EC |
| | Further information: Indicative | | | |
| Carbon monoxide | 630-08-0 | STEL | 100 ppm 117 mg/m3 | 2017/164/EU |
| | Further information: Indicative | | | |
| | | TWA | 20 ppm 23 mg/m3 | 2017/164/EU |
| | Further information: Indicative | | | |
| | | TWA | 20 ppm 23 mg/m3 | 2004/37/EC |
| | Further information: Carcinogens or mutagens | | | |
| | | STEL | 100 ppm 117 mg/m3 | 2004/37/EC |
| | Further information: Carcinogens or mutagens | | | |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

SAFETY DATA SHEET



Capstone™ ST-500

Version 9.0 Revision Date: 23.09.2024 SDS Number: 1339672-00052 Date of last issue: 30.05.2024
Date of first issue: 27.02.2017

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|------------------------------|-----------|-----------------|----------------------------|--------------------|
| 1,2-Benzisothiazol-3(2H)-one | Workers | Inhalation | Long-term systemic effects | 6.81 mg/m3 |
| | Workers | Skin contact | Long-term systemic effects | 0.966 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 1.2 mg/m3 |
| | Consumers | Skin contact | Long-term systemic effects | 0.345 mg/kg bw/day |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

| Substance name | Environmental Compartment | Value |
|------------------------------|---------------------------|---------------------------------|
| 1,2-Benzisothiazol-3(2H)-one | Fresh water | 11 µg/l |
| | Intermittent use/release | 0.403 µg/l |
| | Marine water | 1.1 µg/l |
| | Intermittent use/release | 0.0403 µg/l |
| | Sewage treatment plant | 1.03 mg/l |
| | Fresh water sediment | 0.0499 mg/kg dry weight (d.w.) |
| | Marine sediment | 0.00499 mg/kg dry weight (d.w.) |
| | Soil | 3 mg/kg dry weight (d.w.) |

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety glasses

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Skin and body protection : Skin should be washed after contact.

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and acidic gas/vapour type (E-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid, Aqueous solution

Colour : clear, opaque, yellow

SAFETY DATA SHEET



Capstone™ ST-500

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 30.05.2024 |
| 9.0 | 23.09.2024 | 1339672-00052 | Date of first issue: 27.02.2017 |

| | | |
|--|---|--|
| Odour | : | No data available |
| Odour Threshold | : | No data available |
| pH | : | 9 - 11 |
| Melting point/freezing point | : | 0 °C |
| Initial boiling point and boiling range | : | 100 °C (1,013 hPa) |
| Flash point | : | does not flash |
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | Not applicable |
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Vapour pressure | : | No data available |
| Relative vapour density | : | No data available |
| Density | : | 1.1 g/cm ³ |
| Solubility(ies) | : | |
| Water solubility | : | dispersible |
| Partition coefficient: n-octanol/water | : | Not applicable |
| Auto-ignition temperature | : | No data available |
| Decomposition temperature | : | > 200 °C |
| Viscosity | : | |
| Viscosity, kinematic | : | No data available |
| Explosive properties | : | Not explosive |
| Oxidizing properties | : | The substance or mixture is not classified as oxidizing. |

9.2 Other information

| | | |
|------------------------|---|-------------------|
| Flammability (liquids) | : | No data available |
| Particle size | : | Not applicable |

SAFETY DATA SHEET



Capstone™ ST-500

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 30.05.2024 |
| 9.0 | 23.09.2024 | 1339672-00052 | Date of first issue: 27.02.2017 |

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.
Hazardous decomposition products will be formed at elevated temperatures.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

Thermal decomposition : hydrofluoric acid
Carbonyl difluoride
Carbon dioxide
Carbon monoxide

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

|| Not classified based on available information.

Product:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate (Rat): > 5.8 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Assessment: The substance or mixture has no acute inhalation toxicity

|| No observed adverse effect concentration (Rat): >970 mg/m3
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

SAFETY DATA SHEET



Capstone™ ST-500

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 30.05.2024 |
| 9.0 | 23.09.2024 | 1339672-00052 | Date of first issue: 27.02.2017 |

Components:

1,2-Benzisothiazol-3(2H)-one:

| | | |
|---------------------------|---|---|
| Acute oral toxicity | : | LD50 (Rat, male): 450 mg/kg Method: OECD Test Guideline 401 |
| Acute inhalation toxicity | : | LC50 (Rat, male): 0.21 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 |
| Acute dermal toxicity | : | LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity |

Skin corrosion/irritation

|| Not classified based on available information.

Product:

| | | |
|---------|---|--------------------|
| Species | : | Rabbit |
| Result | : | No skin irritation |

Components:

1,2-Benzisothiazol-3(2H)-one:

|| Result : Skin irritation

Serious eye damage/eye irritation

|| Not classified based on available information.

Product:

| | | |
|---------|---|-------------------|
| Species | : | Rabbit |
| Result | : | No eye irritation |

Components:

1,2-Benzisothiazol-3(2H)-one:

| | | |
|---------|---|---------------------------------|
| Species | : | Rabbit |
| Result | : | Irreversible effects on the eye |

Respiratory or skin sensitisation

Skin sensitisation

|| Not classified based on available information.

Respiratory sensitisation

|| Not classified based on available information.

Components:

1,2-Benzisothiazol-3(2H)-one:

SAFETY DATA SHEET



Capstone™ ST-500

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 30.05.2024 |
| 9.0 | 23.09.2024 | 1339672-00052 | Date of first issue: 27.02.2017 |

| | |
|-----------------|---|
| Test Type | : Maximisation Test |
| Exposure routes | : Skin contact |
| Species | : Guinea pig |
| Method | : OECD Test Guideline 406 |
| Result | : positive |
| Assessment | : Probability or evidence of high skin sensitisation rate in humans |

Germ cell mutagenicity

Not classified based on available information.

Product:

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Components:

1,2-Benzisothiazol-3(2H)-one:

| | |
|-----------------------|--|
| Genotoxicity in vitro | : Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: positive |
| Genotoxicity in vivo | : Test Type: Unscheduled DNA synthesis (UDS) test with mammalian liver cells in vivo Species: Rat Application Route: Ingestion Method: OECD Test Guideline 486 Result: negative |

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

1,2-Benzisothiazol-3(2H)-one:

| | |
|----------------------|--|
| Effects on fertility | : Test Type: Fertility/early embryonic development Species: Rat Application Route: Ingestion Method: OPPTS 870.3800 Result: negative |
|----------------------|--|

SAFETY DATA SHEET



Capstone™ ST-500

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 30.05.2024 |
| 9.0 | 23.09.2024 | 1339672-00052 | Date of first issue: 27.02.2017 |

STOT - single exposure

|| Not classified based on available information.

STOT - repeated exposure

|| Not classified based on available information.

Components:

1,2-Benzisothiazol-3(2H)-one:

|| Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

1,2-Benzisothiazol-3(2H)-one:

|| Species : Dog
|| NOAEL : 5 mg/kg
|| LOAEL : 20 mg/kg
|| Application Route : Ingestion
|| Exposure time : 90 Days
|| Method : Directive 67/548/EEC, Annex, B.27

Aspiration toxicity

|| Not classified based on available information.

Experience with human exposure

Product:

Inhalation : Target Organs: Respiratory system
Symptoms: Shortness of breath

Eye contact : Symptoms: Irritation, Lachrymation, Discomfort, Redness

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 120 mg/l
Exposure time: 48 h

Components:

1,2-Benzisothiazol-3(2H)-one:

|| Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.74 mg/l
Exposure time: 96 h
|| Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.24 mg/l
Exposure time: 48 h
|| Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)):

SAFETY DATA SHEET



Capstone™ ST-500

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 30.05.2024 |
| 9.0 | 23.09.2024 | 1339672-00052 | Date of first issue: 27.02.2017 |

| | |
|--|--|
| plants | 0.1087 mg/l Exposure time: 24 h |
| | EC10 (Pseudokirchneriella subcapitata (green algae)): 0.0268 mg/l Exposure time: 24 h |
| M-Factor (Acute aquatic toxicity) | : 1 |
| Toxicity to microorganisms | : NOEC : 10.3 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 |
| Toxicity to fish (Chronic toxicity) | : NOEC: 0.28 mg/l Exposure time: 33 d Species: Pimephales promelas (fathead minnow) Method: OECD Test Guideline 210 |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : NOEC: 0.91 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211 |
| M-Factor (Chronic aquatic toxicity) | : 1 |

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

1,2-Benzisothiazol-3(2H)-one:

| | |
|--|--|
| Bioaccumulation | : Species: Lepomis macrochirus (Bluegill sunfish) Bioconcentration factor (BCF): 6.62 |
| Partition coefficient: n-octanol/water | : log Pow: 0.7 |

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

| | |
|------------|--|
| Assessment | : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. |
|------------|--|

SAFETY DATA SHEET



Capstone™ ST-500

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 30.05.2024 |
| 9.0 | 23.09.2024 | 1339672-00052 | Date of first issue: 27.02.2017 |

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

SAFETY DATA SHEET



Capstone™ ST-500

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 30.05.2024 |
| 9.0 | 23.09.2024 | 1339672-00052 | Date of first issue: 27.02.2017 |

IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Capstone™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.
Chemours™ and the Chemours Logo are trademarks of The Chemours Company.
Before use read Chemours safety information.
For further information contact the local Chemours office or nominated distributors.

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

| | |
|------|---|
| H302 | : Harmful if swallowed. |
| H315 | : Causes skin irritation. |
| H317 | : May cause an allergic skin reaction. |
| H318 | : Causes serious eye damage. |
| H330 | : Fatal if inhaled. |
| H400 | : Very toxic to aquatic life. |
| H410 | : Very toxic to aquatic life with long lasting effects. |

Full text of other abbreviations

SAFETY DATA SHEET



Capstone™ ST-500

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 30.05.2024 |
| 9.0 | 23.09.2024 | 1339672-00052 | Date of first issue: 27.02.2017 |

| | |
|--------------------|---|
| Acute Tox. | : Acute toxicity |
| Aquatic Acute | : Short-term (acute) aquatic hazard |
| Aquatic Chronic | : Long-term (chronic) aquatic hazard |
| Eye Dam. | : Serious eye damage |
| Skin Irrit. | : Skin irritation |
| Skin Sens. | : Skin sensitisation |
| 2000/39/EC | : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values |
| 2004/37/EC | : Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work |
| 2006/15/EC | : Europe. Indicative occupational exposure limit values |
| 2017/164/EU | : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values |
| 2000/39/EC / TWA | : Limit Value - eight hours |
| 2000/39/EC / STEL | : Short term exposure limit |
| 2004/37/EC / STEL | : Short term exposure limit |
| 2004/37/EC / TWA | : Long term exposure limit |
| 2006/15/EC / TWA | : Limit Value - eight hours |
| 2017/164/EU / STEL | : Short term exposure limit |
| 2017/164/EU / TWA | : Limit Value - eight hours |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

SAFETY DATA SHEET



Capstone™ ST-500

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 30.05.2024 |
| 9.0 | 23.09.2024 | 1339672-00052 | Date of first issue: 27.02.2017 |

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

IL / EN