

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 29.05.2024 |
| 10.4 | 25.11.2024 | 1336775-00049 | Date of first issue: 27.02.2017 |

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier

Product name : Capstone™ FS-63 Fluorosurfactant

SDS-Identcode : 130000051604

Chemical name :

CAS-No. : Not Assigned

Product code :

Recommended use of the chemical and restrictions on use

Recommended use : Surfactant

Restrictions on use : For industrial use only.
Do not use this product in consumer spray applications except in water-based coatings where the maximum concentration of active ingredient does not exceed 0.1 wt percent.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

Manufacturer or supplier's details

Company : The Chemours Malaysia Sdn. Bhd.

Address : Suite 20-01 & 20-02B, Level 20, The Pinnacle, Persiaran Lagoon, Bandar Sunway, Subang Jaya
Selangor Darul Ehsan 47500 Malaysia

Telephone : +60 3 5021 0178

Emergency telephone number : 1-800-815-308

Telefax : +60 3 2178 4719

SECTION 2: Hazards identification

Classification of the hazardous chemical

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 1

Serious eye damage/eye irri- : Category 2

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

| | | | |
|-----------------|------------------------------|------------------------------|---|
| Version 10.4 | Revision Date: 25.11.2024 | SDS Number: 1336775-00049 | Date of last issue: 29.05.2024 Date of first issue: 27.02.2017 |
|-----------------|------------------------------|------------------------------|---|

tation

Specific target organ toxicity - : Category 3
single exposure

Specific target organ toxicity - : Category 2
repeated exposure

Hazardous to the aquatic : Category 1
environment - chronic hazard

Label elements

Hazard pictograms



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P391 Collect spillage.

Storage:

P405 Store locked up.

Capstone™ FS-63 Fluorosurfactant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 29.05.2024 |
| 10.4 | 25.11.2024 | 1336775-00049 | Date of first issue: 27.02.2017 |

Other hazards which do not result in classification

Inhalation of decomposition products in high concentration may cause shortness of breath (lung oedema).

Vapours may form explosive mixture with air.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|--|--------------|-----------------------|
| Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts | Not Assigned | ≥ 30 -< 60 |
| Propan-2-ol | 67-63-0 | ≥ 20 -< 30 |

SECTION 4: First aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention if symptoms occur.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Inhalation may provoke the following symptoms:
Respiratory disorder
Shortness of breath
Lung oedema
Cough
Irritation
Eye contact may provoke the following symptoms
Lachrymation
Redness
Discomfort
Causes serious eye irritation.
Fatal if inhaled.

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 29.05.2024 |
| 10.4 | 25.11.2024 | 1336775-00049 | Date of first issue: 27.02.2017 |

May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Physicochemical hazards arising from the chemical

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates
Carbon oxides

Special protective equipment and precautions for fire-fighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Hazchem Code : •3Y

Capstone™ FS-63 Fluorosurfactant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 29.05.2024 |
| 10.4 | 25.11.2024 | 1336775-00049 | Date of first issue: 27.02.2017 |

SECTION 6: Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Only trained personnel should re-enter the area.
Remove all sources of ignition.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7: Handling and storage**Handling****Precautions for safe handling**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not breathe mist or vapours.
Do not swallow.
Do not get in eyes.
Avoid prolonged or repeated contact with skin.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 10.4 Revision Date: 25.11.2024 SDS Number: 1336775-00049 Date of last issue: 29.05.2024
Date of first issue: 27.02.2017

assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

Storage

Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Keep in properly labelled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable gases
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Poisonous gases
Explosives

SECTION 8: Exposure controls and personal protection

Control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-------------|---------|----------------------------------|--|--------|
| Propan-2-ol | 67-63-0 | TWA | 400 ppm 983 mg/m ³ | MY PEL |
| | | TWA | 200 ppm | ACGIH |
| | | STEL | 400 ppm | ACGIH |

Occupational exposure limits of decomposition products

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|-------------------|-----------|----------------------------------|--|--------|
| hydrofluoric acid | 7664-39-3 | CEIL | 3 ppm 2.3 mg/m ³ (Fluorine) | MY PEL |
| | | TWA | 0.5 ppm | ACGIH |

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 10.4 Revision Date: 25.11.2024 SDS Number: 1336775-00049 Date of last issue: 29.05.2024
 Date of first issue: 27.02.2017

| | | | | |
|---------------------|----------|------|--------------------------------------|--------|
| | | | (Fluorine) | |
| | | C | 2 ppm (Fluorine) | ACGIH |
| Carbonyl difluoride | 353-50-4 | TWA | 2 ppm 5.4 mg/m ³ | MY PEL |
| | | TWA | 2 ppm | ACGIH |
| | | STEL | 5 ppm | ACGIH |
| Carbon dioxide | 124-38-9 | TWA | 5,000 ppm 9,000 mg/m ³ | MY PEL |
| | | TWA | 5,000 ppm | ACGIH |
| | | STEL | 30,000 ppm | ACGIH |
| Carbon monoxide | 630-08-0 | TWA | 25 ppm 29 mg/m ³ | MY PEL |
| | | TWA | 25 ppm | ACGIH |

Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Sam-pling time | Permissible concentra-tion | Basis |
|-------------|---------|--------------------|---------------------|----------------------------------|----------------------------|-----------|
| Propan-2-ol | 67-63-0 | Acetone | Urine | End of shift at end of work-week | 40 mg/l | ACGIH BEI |

Appropriate engineering controls : Processing may form hazardous compounds (see section 10).
 Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.
 Use explosion-proof electrical, ventilating and lighting equipment.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection : Wear the following personal protective equipment:
 Safety goggles

Skin protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
 Wear the following personal protective equipment:
 If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
 Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hand protection
 Material : butyl-rubber
 Break through time : 480 min
 Glove thickness : 0.89 mm

Remarks : Choose gloves to protect hands against chemicals depending

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

| | | | |
|-----------------|------------------------------|------------------------------|---|
| Version 10.4 | Revision Date: 25.11.2024 | SDS Number: 1336775-00049 | Date of last issue: 29.05.2024 Date of first issue: 27.02.2017 |
|-----------------|------------------------------|------------------------------|---|

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Combined particulates, acidic gas/vapour and organic vapour type
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9: Physical and chemical properties

- Appearance : liquid
- Colour : clear, colourless, yellow
- Odour : alcohol-like
- Odour Threshold : No data available
- pH : 7 - 8.5
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available
- Flash point : 26 °C
Method: Pensky-Martens closed cup
- Evaporation rate : No data available
- Flammability (solid, gas) : Not applicable
- Flammability (liquids) : Ignitable (see flash point)
- Upper explosion limit / Upper flammability limit : No data available

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 29.05.2024 |
| 10.4 | 25.11.2024 | 1336775-00049 | Date of first issue: 27.02.2017 |

| | | |
|--|---|--|
| Lower explosion limit / Lower flammability limit | : | No data available |
| Vapour pressure | : | 13.79 hPa (20 °C) Solvent |
| Relative vapour density | : | No data available |
| Density | : | 1.1 g/cm ³ |
| Solubility(ies) Water solubility | : | soluble |
| Partition coefficient: n-octanol/water | : | log Pow: 0.35 (for a component of this mixture) |
| Auto-ignition temperature | : | No data available |
| Decomposition temperature | : | > 200 °C |
| Viscosity Viscosity, kinematic | : | No data available |
| Explosive properties | : | Not explosive |
| Oxidizing properties | : | The substance or mixture is not classified as oxidizing. |
| Particle characteristics Particle size | : | Not applicable |

SECTION 10: Stability and reactivity

| | | |
|------------------------------------|---|--|
| Reactivity | : | Not classified as a reactivity hazard. |
| Chemical stability | : | Stable under normal conditions. |
| Possibility of hazardous reactions | : | Flammable liquid and vapour. Vapours may form explosive mixture with air. Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures. |
| Conditions to avoid | : | Heat, flames and sparks. |
| Incompatible materials | : | Oxidizing agents |

Hazardous decomposition products

| | | |
|-----------------------|---|---|
| Thermal decomposition | : | hydrofluoric acid Carbonyl difluoride Carbon dioxide Carbon monoxide |
|-----------------------|---|---|

Capstone™ FS-63 Fluorosurfactant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 29.05.2024 |
| 10.4 | 25.11.2024 | 1336775-00049 | Date of first issue: 27.02.2017 |

SECTION 11: Toxicological information

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Fatal if inhaled.

Product:

| | |
|---------------------------|--|
| Acute oral toxicity | : LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials |
| Acute inhalation toxicity | : Acute toxicity estimate (Rat): 0.005 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Remarks: Based on data from similar materials |
| Acute dermal toxicity | : LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials |

Components:**Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:**

| | |
|---------------------------|---|
| Acute oral toxicity | : LD50 (Rat): > 1,000 mg/kg Method: OECD Test Guideline 425 Assessment: The substance or mixture has no acute oral toxicity |
| Acute inhalation toxicity | : Approximate Lethal Concentration (Rat): 0.047 mg/l Exposure time: 4 h Test atmosphere: dust/mist |
| Acute dermal toxicity | : LD50 (Rat): > 1,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity |

Propan-2-ol:

| | |
|---------------------------|--|
| Acute oral toxicity | : LD50 (Rat): > 5,000 mg/kg |
| Acute inhalation toxicity | : LC50 (Rat): > 25 mg/l Exposure time: 6 h Test atmosphere: vapour |
| Acute dermal toxicity | : LD50 (Rabbit): > 5,000 mg/kg |

Skin corrosion/irritation

Not classified based on available information.

Capstone™ FS-63 Fluorosurfactant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 29.05.2024 |
| 10.4 | 25.11.2024 | 1336775-00049 | Date of first issue: 27.02.2017 |

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

| | | |
|---------|---|-------------------------|
| Species | : | Rabbit |
| Method | : | OECD Test Guideline 404 |
| Result | : | No skin irritation |

Propan-2-ol:

| | | |
|---------|---|--------------------|
| Species | : | Rabbit |
| Result | : | No skin irritation |

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

| | | |
|---------|---|-------------------------|
| Species | : | Rabbit |
| Result | : | No eye irritation |
| Method | : | OECD Test Guideline 405 |

Propan-2-ol:

| | | |
|---------|---|--|
| Species | : | Rabbit |
| Result | : | Irritation to eyes, reversing within 21 days |

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

| | | |
|-----------------|---|-------------------------------|
| Test Type | : | Local lymph node assay (LLNA) |
| Exposure routes | : | Skin contact |
| Species | : | Mouse |
| Method | : | OECD Test Guideline 429 |
| Result | : | negative |

Propan-2-ol:

| | | |
|-----------------|---|-------------------------|
| Test Type | : | Buehler Test |
| Exposure routes | : | Skin contact |
| Species | : | Guinea pig |
| Method | : | OECD Test Guideline 406 |
| Result | : | negative |

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 29.05.2024 |
| 10.4 | 25.11.2024 | 1336775-00049 | Date of first issue: 27.02.2017 |

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Propan-2-ol:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 104 weeks
Method : OECD Test Guideline 451
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 29.05.2024 |
| 10.4 | 25.11.2024 | 1336775-00049 | Date of first issue: 27.02.2017 |

Method: OECD Test Guideline 415
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Propan-2-ol:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Exposure routes : Ingestion
Target Organs : Liver
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

Repeated dose toxicity

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Species : Rat, male and female

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 29.05.2024 |
| 10.4 | 25.11.2024 | 1336775-00049 | Date of first issue: 27.02.2017 |

LOAEL : 3.6 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408
Remarks : Based on data from similar materials

Species : Rat, male
NOAEL : 100 mg/kg
LOAEL : 1,000 mg/kg
Application Route : Skin contact
Exposure time : 28 Days
Method : OECD Test Guideline 410
Remarks : Based on data from similar materials

Propan-2-ol:

Species : Rat
NOAEL : 12.5 mg/l
Application Route : inhalation (vapour)
Exposure time : 104 Weeks

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

Ecotoxicity

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 36.4 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 3.24 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 22.44 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 22.44 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 29.05.2024 |
| 10.4 | 25.11.2024 | 1336775-00049 | Date of first issue: 27.02.2017 |

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 0.88 mg/l
Exposure time: 90 d
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.0093 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

M-Factor (Chronic aquatic toxicity) : 10

Propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 24 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 1,050 mg/l
Exposure time: 16 h

Persistence and degradability

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301D
Remarks: Based on data from similar materials

Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1,19 (BOD5)
COD: 2,23
BOD/COD: 53 %

Bioaccumulative potential

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 4
Remarks: Based on data from similar materials

Propan-2-ol:

Partition coefficient: n- : log Pow: 0.05

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 29.05.2024 |
| 10.4 | 25.11.2024 | 1336775-00049 | Date of first issue: 27.02.2017 |

octanol/water

Mobility in soil

No data available

Other adverse effects

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Results of PBT and vPvB assessment : PBT substance

Additional ecological information : Information given is based on data on the components and the ecotoxicology of similar products.

SECTION 13: Disposal information

Disposal methods

Waste from residues : Disposal of waste to be in accordance with the Environmental Quality (Scheduled Wastes) Regulations and other guidelines issuance by DOE and/or local authorities.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

International Regulations

UNRTDG

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Propan-2-ol)
Class : 3
Packing group : III
Labels : 3
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1993
Proper shipping name : Flammable liquid, n.o.s.
(Propan-2-ol)
Class : 3
Packing group : III
Labels : Flammable Liquids

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 29.05.2024 |
| 10.4 | 25.11.2024 | 1336775-00049 | Date of first issue: 27.02.2017 |

Packing instruction (cargo aircraft) : 366

Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Propan-2-ol, Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts)

Class : 3

Packing group : III

Labels : 3

EmS Code : F-E, S-E

Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Hazchem Code : •3Y

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

SECTION 16: Other information

Revision Date : 25.11.2024

Other information : Capstone™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.
Chemours™ and the Chemours Logo are trademarks of The Chemours Company.
Before use read Chemours safety information.
For further information contact the local Chemours office or nominated distributors.

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 29.05.2024 |
| 10.4 | 25.11.2024 | 1336775-00049 | Date of first issue: 27.02.2017 |

Full text of other abbreviations

| | | |
|---------------|---|---|
| ACGIH | : | USA. ACGIH Threshold Limit Values (TLV) |
| ACGIH BEI | : | ACGIH - Biological Exposure Indices (BEI) |
| MY PEL | : | Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000. |
| ACGIH / TWA | : | 8-hour, time-weighted average |
| ACGIH / STEL | : | Short-term exposure limit |
| ACGIH / C | : | Ceiling limit |
| MY PEL / TWA | : | Eight-hour time-weighted average airborne concentration |
| MY PEL / CEIL | : | Ceiling limit airborne concentration |

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

MY / EN

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 29.05.2024 |
| 10.4 | 25.11.2024 | 1336775-00049 | Date of first issue: 27.02.2017 |
