

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

Version 4.10 Revision Date: 01/22/2025 SDS Number: 1575699-00017 Date of last issue: 10/17/2024
Date of first issue: 04/26/2017

SECTION 1. IDENTIFICATION

Product name : Ti-Pure™ R-900 Titanium Dioxide Pigment

SDS-Identcode : 130000030873

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Coloring agent
Pigment

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|---------------------|------------|-----------------------|
| Titanium dioxide | 13463-67-7 | $\geq 90 - \leq 100$ |
| Aluminium hydroxide | 21645-51-2 | $\geq 1 - < 5$ |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

| | | | |
|-----------------|------------------------------|------------------------------|-------------------------------------------------------------------|
| Version 4.10 | Revision Date: 01/22/2025 | SDS Number: 1575699-00017 | Date of last issue: 10/17/2024 Date of first issue: 04/26/2017 |
|-----------------|------------------------------|------------------------------|-------------------------------------------------------------------|

| | |
|-------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| If inhaled | : If inhaled, remove to fresh air. Get medical attention if symptoms occur. |
| In case of skin contact | : Wash with water and soap as a precaution. Get medical attention if symptoms occur. |
| In case of eye contact | : Flush eyes with water as a precaution. Get medical attention if irritation develops and persists. |
| If swallowed | : If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : irritant effects |
| Protection of first-aiders | : No special precautions are necessary for first aid responders. |
| Notes to physician | : Treat symptomatically and supportively. |

SECTION 5. FIRE-FIGHTING MEASURES

| | |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media | : Not applicable Will not burn |
| Unsuitable extinguishing media | : Not applicable Will not burn |
| Specific hazards during fire fighting | : Exposure to combustion products may be a hazard to health. |
| Hazardous combustion products | : Metal oxides |
| Specific extinguishing methods | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area. |
| Special protective equipment for fire-fighters | : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

Version 4.10 Revision Date: 01/22/2025 SDS Number: 1575699-00017 Date of last issue: 10/17/2024
Date of first issue: 04/26/2017

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---------------------|------------|-------------------------------------|------------------------------------------------|----------|
| Titanium dioxide | 13463-67-7 | TWA (Respirable particulate matter) | 2.5 mg/m ³ (Titanium dioxide) | ACGIH |
| | | TWA (total dust) | 15 mg/m ³ | OSHA Z-1 |
| Aluminium hydroxide | 21645-51-2 | TWA (Res- | 1 mg/m ³ | ACGIH |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

| | | | |
|-----------------|------------------------------|------------------------------|-------------------------------------------------------------------|
| Version 4.10 | Revision Date: 01/22/2025 | SDS Number: 1575699-00017 | Date of last issue: 10/17/2024 Date of first issue: 04/26/2017 |
|-----------------|------------------------------|------------------------------|-------------------------------------------------------------------|

| | | | | |
|--|--|---------------------------------------|------------|--|
| | | pirable par- ticulate mat- ter) | (Aluminum) | |
|--|--|---------------------------------------|------------|--|

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : solid

Color : white

Odor : odorless

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : 3,349 °F / 1,843 °C

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

| | | | |
|-----------------|------------------------------|------------------------------|-------------------------------------------------------------------|
| Version 4.10 | Revision Date: 01/22/2025 | SDS Number: 1575699-00017 | Date of last issue: 10/17/2024 Date of first issue: 04/26/2017 |
|-----------------|------------------------------|------------------------------|-------------------------------------------------------------------|

| | |
|--------------------------------------------------|-------------------------------------------------------------|
| Initial boiling point and boiling range | : 5,432 °F / 3,000 °C |
| Flash point | : Not applicable |
| Evaporation rate | : Not applicable |
| Flammability (solid, gas) | : Will not burn |
| | Not expected to form explosive dust-air mixtures. |
| Upper explosion limit / Upper flammability limit | : No data available |
| Lower explosion limit / Lower flammability limit | : No data available |
| Vapor pressure | : Not applicable |
| Relative vapor density | : Not applicable |
| Relative density | : 3.4 - 4.3 |
| Density | : 4.050 g/cm ³ |
| Solubility(ies) Water solubility | : insoluble |
| Partition coefficient: n-octanol/water | : Not applicable |
| Autoignition temperature | : No data available |
| Decomposition temperature | : The substance or mixture is not classified self-reactive. |
| Viscosity Viscosity, kinematic | : Not applicable |
| Explosive properties | : Not explosive |
| Oxidizing properties | : The substance or mixture is not classified as oxidizing. |
| Particle characteristics Particle size | : No data available |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------|------------------------------------------|
| Reactivity | : Not classified as a reactivity hazard. |
|------------|------------------------------------------|

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/17/2024 |
| 4.10 | 01/22/2025 | 1575699-00017 | Date of first issue: 04/26/2017 |

| | | |
|------------------------------------|---|------------------------------------------------|
| Chemical stability | : | Stable under normal conditions. |
| Possibility of hazardous reactions | : | None known. |
| Conditions to avoid | : | None known. |
| Incompatible materials | : | None. |
| Hazardous decomposition products | : | No hazardous decomposition products are known. |

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Titanium dioxide:

| | | |
|---------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Acute oral toxicity | : | LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 425 |
| Acute inhalation toxicity | : | LC50 (Rat): > 6.82 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity |
| Acute dermal toxicity | : | Acute toxicity estimate (Rat): > 2,000 mg/kg Method: Expert judgment Assessment: The substance or mixture has no acute dermal toxicity |

Aluminium hydroxide:

| | | |
|---------------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Acute oral toxicity | : | LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 423 Assessment: The substance or mixture has no acute oral toxicity |
| Acute inhalation toxicity | : | LC50 (Rat): > 5.09 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/17/2024 |
| 4.10 | 01/22/2025 | 1575699-00017 | Date of first issue: 04/26/2017 |

Skin corrosion/irritation

Not classified based on available information.

Components:

Titanium dioxide:

| | | |
|---------|---|-------------------------|
| Species | : | Rabbit |
| Method | : | OECD Test Guideline 404 |
| Result | : | No skin irritation |

Aluminium hydroxide:

| | | |
|---------|---|-------------------------|
| Species | : | Rabbit |
| Method | : | OECD Test Guideline 404 |
| Result | : | No skin irritation |

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Titanium dioxide:

| | | |
|---------|---|-------------------------|
| Species | : | Rabbit |
| Result | : | No eye irritation |
| Method | : | OECD Test Guideline 405 |

Aluminium hydroxide:

| | | |
|---------|---|-------------------------|
| Species | : | Rabbit |
| Result | : | No eye irritation |
| Method | : | OECD Test Guideline 405 |

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Titanium dioxide:

| | | |
|--------------------|---|-------------------------|
| Test Type | : | Buehler Test |
| Routes of exposure | : | Skin contact |
| Species | : | Guinea pig |
| Method | : | OECD Test Guideline 406 |
| Result | : | negative |

| | | |
|--------------------|---|-------------------------------|
| Test Type | : | Local lymph node assay (LLNA) |
| Routes of exposure | : | Skin contact |
| Species | : | Mouse |
| Method | : | OECD Test Guideline 429 |
| Result | : | negative |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/17/2024 |
| 4.10 | 01/22/2025 | 1575699-00017 | Date of first issue: 04/26/2017 |

Routes of exposure : Inhalation
Species : Mouse
Result : negative

Routes of exposure : Inhalation
Species : Humans
Result : negative

Aluminium hydroxide:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: comet assay
Method: OPPTS 870.5140
Result: positive

Genotoxicity in vivo : Test Type: In vivo mammalian alkaline comet assay
Species: Rat
Application Route: intratracheal
Method: OECD Test Guideline 489
Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/17/2024 |
| 4.10 | 01/22/2025 | 1575699-00017 | Date of first issue: 04/26/2017 |

Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 475
Result: negative

Test Type: Transgenic rodent germ cell gene mutation assay
Species: Mouse
Application Route: Intravenous injection
Method: OECD Test Guideline 488
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Aluminium hydroxide:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: positive
Remarks: Based on data from similar materials

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: equivocal
Remarks: Based on data from similar materials

Test Type: in vitro micronucleus test
Result: positive
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Not classified based on available information.

Product:

Remarks : In lifetime inhalation studies rats were exposed for 2 years to respectively 10, 50 and 250 mg/m³ of respirable TiO₂. Slight lung fibrosis was observed at 50 and 250 mg/m³ levels. Microscopic lung tumours were also observed in 13 percent of the rats exposed to 250 mg/m³, an exposure level that caused lung overloading and impairment of rat lungs clearance mechanisms.
In further studies, these tumours were found to occur only under particle overload conditions in a uniquely sensitive species, the rat, and have little or no relevance for humans. The

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/17/2024 |
| 4.10 | 01/22/2025 | 1575699-00017 | Date of first issue: 04/26/2017 |

pulmonary inflammatory response to TiO₂ particles exposure was also found to be much more severe in rats than in other rodent species.

In February 2006, IARC has re-evaluated Titanium dioxide as pertaining to Group 2B: "possibly carcinogenic to humans", based upon inadequate evidence in humans and sufficient evidence in experimental animals for the carcinogenicity of titanium dioxide. IARC evaluation guidelines consider the generation of tumours, in 2 different studies within the same animal species, to be adequate criteria for an assessment of sufficient evidence.

The conclusions of several epidemiology studies on more than 20000 TiO₂ industry workers in Europe and the USA did not suggest a carcinogenic effect of TiO₂ dust on the human lung. Mortality from other chronic diseases, including other respiratory diseases, was also not associated with exposure to TiO₂ dust.

Based upon all available study results, Chemours scientists conclude that titanium dioxide will not cause lung cancer or chronic respiratory diseases in humans at concentrations experienced in the workplace.

Components:

Titanium dioxide:

| | |
|-------------------|-------------------------------|
| Species | : Rat |
| Application Route | : inhalation (dust/mist/fume) |
| Exposure time | : 2 Years |
| Result | : negative |

| | |
|-------------------|-------------|
| Species | : Rat |
| Application Route | : Ingestion |
| Exposure time | : 105 weeks |
| Result | : negative |

| | |
|-------------------|-------------|
| Species | : Mouse |
| Application Route | : Ingestion |
| Exposure time | : 103 weeks |
| Result | : negative |

| | |
|------------------------------|----------------------------------------------------------------------|
| Carcinogenicity - Assessment | : Weight of evidence does not support classification as a carcinogen |
|------------------------------|----------------------------------------------------------------------|

Aluminium hydroxide:

| | |
|-------------------|----------------------------------------|
| Species | : Rat |
| Application Route | : inhalation (dust/mist/fume) |
| Exposure time | : 86 weeks |
| Result | : negative |
| Remarks | : Based on data from similar materials |

| | | |
|------|-------------------------------------------|------------|
| IARC | Group 2B: Possibly carcinogenic to humans | |
| | Titanium dioxide | 13463-67-7 |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/17/2024 |
| 4.10 | 01/22/2025 | 1575699-00017 | Date of first issue: 04/26/2017 |

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Titanium dioxide:

| | | |
|------------------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Effects on fertility | : | Test Type: One-generation reproduction toxicity study Species: Rat Application Route: Ingestion Method: OECD Test Guideline 443 Result: negative |
| Effects on fetal development | : | Test Type: Prenatal development toxicity study (teratogenicity) Species: Rat Application Route: Ingestion Method: OECD Test Guideline 414 Result: negative |
| Reproductive toxicity - Assessment | : | Weight of evidence does not support classification for reproductive toxicity |

Aluminium hydroxide:

| | | |
|------------------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Effects on fertility | : | Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative Remarks: Based on data from similar materials |
| Effects on fetal development | : | Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Result: negative |

STOT-single exposure

Not classified based on available information.

Components:

Titanium dioxide:

| | | |
|--------------------|---|----------------------------------------------------------------------------------------------|
| Routes of exposure | : | Skin contact |
| Assessment | : | No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less |
| Routes of exposure | : | Ingestion |
| Assessment | : | No significant health effects observed in animals at concentra- |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/17/2024 |
| 4.10 | 01/22/2025 | 1575699-00017 | Date of first issue: 04/26/2017 |

tions of 2000 mg/kg bw or less

| | | |
|--------------------|---|--------------------------------------------------------------------------------------------|
| Routes of exposure | : | inhalation (dust/mist/fume) |
| Assessment | : | No significant health effects observed in animals at concentrations of 5.0 mg/l/4h or less |

STOT-repeated exposure

Not classified based on available information.

Components:

Titanium dioxide:

| | | |
|--------------------|---|----------------------------------------------------------------------------------------------|
| Routes of exposure | : | Ingestion |
| Assessment | : | No significant health effects observed in animals at concentrations of 100 mg/kg bw or less. |

| | | |
|--------------------|---|-----------------------------------------------------------------------------------------------|
| Routes of exposure | : | inhalation (dust/mist/fume) |
| Assessment | : | No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less. |

| | | |
|--------------------|---|----------------------------------------------------------------------------------------------|
| Routes of exposure | : | Ingestion |
| Assessment | : | No significant health effects observed in animals at concentrations of 200 mg/kg bw or less. |

Repeated dose toxicity

Components:

Titanium dioxide:

| | | |
|-------------------|---|----------------------------------------------|
| Species | : | Rat, male and female |
| NOAEL | : | 24,000 mg/kg |
| LOAEL | : | > 24,000 mg/kg |
| Application Route | : | Ingestion |
| Exposure time | : | 28 Days |
| Method | : | OECD Test Guideline 407 |
| Remarks | : | No significant adverse effects were reported |

| | | |
|-------------------|---|----------------------------------------------|
| Species | : | Rat, male and female |
| NOAEL | : | 0.01 mg/l |
| LOAEL | : | 0.5 mg/l |
| Application Route | : | inhalation (dust/mist/fume) |
| Exposure time | : | 24 Months |
| Method | : | OECD Test Guideline 453 |
| Remarks | : | No significant adverse effects were reported |

| | | |
|-------------------|---|----------------------------------------------|
| Species | : | Rat, male and female |
| NOAEL | : | 962 mg/kg |
| LOAEL | : | > 962 mg/kg |
| Application Route | : | Ingestion |
| Exposure time | : | 90 Days |
| Method | : | OECD Test Guideline 408 |
| Remarks | : | No significant adverse effects were reported |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/17/2024 |
| 4.10 | 01/22/2025 | 1575699-00017 | Date of first issue: 04/26/2017 |

Aluminium hydroxide:

| | | |
|-------------------|---|--------------------------------------|
| Species | : | Rat |
| NOAEL | : | > 100 mg/kg |
| Application Route | : | Ingestion |
| Exposure time | : | 364 Days |
| Method | : | OECD Test Guideline 426 |
| Remarks | : | Based on data from similar materials |

| | | |
|-------------------|---|--------------------------------------|
| Species | : | Rat |
| NOAEL | : | > 0.2 mg/kg |
| Application Route | : | inhalation (dust/mist/fume) |
| Exposure time | : | 12 Months |
| Remarks | : | Based on data from similar materials |

Aspiration toxicity

Not classified based on available information.

Components:

Titanium dioxide:

No aspiration toxicity classification

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Titanium dioxide:

| | | |
|-----------------------------------------------------|---|-----------------------------------------------------------------------------------------------------------------------------|
| Toxicity to fish | : | LC50 (Fish): > 1,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 |
| | | LC50 (Marine species): > 10,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia sp. (Water flea)): > 1,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 |
| | | EC50 (No species specified): > 1,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 |
| Toxicity to algae/aquatic plants | : | ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 |
| | | EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l Exposure time: 72 h |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/17/2024 |
| 4.10 | 01/22/2025 | 1575699-00017 | Date of first issue: 04/26/2017 |

Method: ISO 10253

NOEC (*Pseudokirchneriella subcapitata* (green algae)): > 100 mg/l

Exposure time: 3 d

Method: OECD Test Guideline 201

NOEC (*Skeletonema costatum* (marine diatom)): 5,600 mg/l

Exposure time: 3 d

Method: ISO 10253

Aluminium hydroxide:

Toxicity to fish : LL50 (*Salmo trutta* (brown trout)): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EL50 (*Daphnia magna* (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EL50 (*Selenastrum capricornutum* (green algae)): > 100 mg/l
plants Exposure time: 96 h

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Titanium dioxide:

Bioaccumulation : Species: *Oncorhynchus mykiss* (rainbow trout)
Bioconcentration factor (BCF): 352

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste
handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/17/2024 |
| 4.10 | 01/22/2025 | 1575699-00017 | Date of first issue: 04/26/2017 |

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

| | |
|---------------------|------------|
| Titanium dioxide | 13463-67-7 |
| Aluminium hydroxide | 21645-51-2 |
| Aluminum oxide | 1344-28-1 |

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Permissible Exposure Limits for Chemical Contaminants

| | |
|------------------|------------|
| Titanium dioxide | 13463-67-7 |
|------------------|------------|

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard




Ti-Pure™ R-900 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/17/2024 |
| 4.10 | 01/22/2025 | 1575699-00017 | Date of first issue: 04/26/2017 |

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

| | | |
|-----------------|---|---|
| HEALTH | / | 0 |
| FLAMMABILITY | | 0 |
| PHYSICAL HAZARD | | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Ti-Pure™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

These products may not be directly added to food, pharmaceuticals, cosmetics, or cigarette papers/filters for tobacco products.

Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

In the manufacture of titanium dioxide, product is packaged at temperatures of approximately 100 to 120°C (212 to 248°F). When pigment is shipped shortly after manufacture, it may stay hot for a very long time depending on ambient temperatures and inventory storage practices. Use caution while handling hot pigment to prevent burns to personnel. Use caution in solvent applications to prevent ignition of solvent.

Full text of other abbreviations

| | | |
|----------------|---|----------------------------------------------------------------------------------|
| ACGIH | : | USA. ACGIH Threshold Limit Values (TLV) |
| OSHA Z-1 | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| ACGIH / TWA | : | 8-hour, time-weighted average |
| OSHA Z-1 / TWA | : | 8-hour time weighted average |

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Ti-Pure™ R-900 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 10/17/2024 |
| 4.10 | 01/22/2025 | 1575699-00017 | Date of first issue: 04/26/2017 |

German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 01/22/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8