

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

SECTION 1. IDENTIFICATION

Product name : Capstone™ FS-93

SDS-Identcode : 130000141339

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Coatings
Surfactant

Restrictions on use : Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Eye irritation : Category 2A

Specific target organ toxicity : Category 1 (Lungs, larynx)
- single exposure (Inhalation)

Specific target organ toxicity : Category 3
- single exposure

GHS label elements

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H226 Flammable liquid and vapor.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H370 Causes damage to organs (Lungs, larynx) if inhaled.

Precautionary Statements

:

Prevention:

P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.
P233 Keep container tightly closed.
P241 Use explosion-proof electrical, ventilating and lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, eye protection and face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P307 + P311 IF exposed: Call a doctor.
P337 + P313 If eye irritation persists: Get medical attention.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Inhalation of decomposition products in high concentration may cause shortness of breath (lung edema).
Vapors may form explosive mixture with air.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version 10.5 Revision Date: 10/17/2024 SDS Number: 1351611-00051 Date of last issue: 07/23/2024
Date of first issue: 02/27/2017

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Propan-2-ol	67-63-0	$\geq 10 - < 20$
Partially fluorinated alcohol, reaction products with phosphorus oxide (P ₂ O ₅) amine salts	Not Assigned	$\geq 10 - < 20$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention.
- In case of skin contact : Remove contaminated clothing and shoes.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Inhalation may provoke the following symptoms:
Central nervous system depression
respiratory tract irritation
Cough
sneezing
runny nose
sore throat
Shortness of breath
Eye contact may provoke the following symptoms
Pain
tearing
Swelling of tissue
Redness
Impairment of vision
Causes serious eye irritation.
Harmful if inhaled.
May cause drowsiness or dizziness.
Causes damage to organs if inhaled.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Do not breathe mist or vapors.
Do not swallow.
Do not get in eyes.
Avoid prolonged or repeated contact with skin.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version 10.5 Revision Date: 10/17/2024 SDS Number: 1351611-00051 Date of last issue: 07/23/2024
Date of first issue: 02/27/2017

Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases
Very acutely toxic substances and mixtures

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		ST	500 ppm 1,225 mg/m ³	NIOSH REL
		TWA	400 ppm 980 mg/m ³	NIOSH REL
		TWA	400 ppm 980 mg/m ³	OSHA Z-1

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		C	6 ppm 5 mg/m ³	NIOSH REL
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version 10.5 Revision Date: 10/17/2024 SDS Number: 1351611-00051 Date of last issue: 07/23/2024
Date of first issue: 02/27/2017

		TWA	2 ppm 5 mg/m ³	NIOSH REL
		ST	5 ppm 15 mg/m ³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m ³	NIOSH REL
		ST	30,000 ppm 54,000 mg/m ³	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m ³	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m ³	NIOSH REL
		C	200 ppm 229 mg/m ³	NIOSH REL
		TWA	50 ppm 55 mg/m ³	OSHA Z-1

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : clear, colorless, yellow

Odor : alcohol-like

Odor Threshold : No data available

pH : 7 - 7.5

Melting point/freezing point : No data available

Initial boiling point and boiling range : 181 °F / 83 °C

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

Flash point	:	93 °F / 34 °C
		Method: Pensky-Martens closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	1.18 g/cm ³
Solubility(ies)	:	
Water solubility	:	soluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	> 392 °F / > 200 °C
Viscosity	:	
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics	:	
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Flammable liquid and vapor. Vapors may form explosive mixture with air.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

Can react with strong oxidizing agents.
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride
Carbonyl difluoride
Carbon dioxide
Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 425
Remarks: Based on data from similar materials

Acute inhalation toxicity : Acute toxicity estimate (Rat): 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgment
Remarks: Based on data from similar materials

Components:

Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l
Exposure time: 6 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5) amine salts:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 425
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

Acute inhalation toxicity : Acute toxicity estimate (Rat): 0.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgment
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Propan-2-ol:

Species : Rabbit
Result : No skin irritation

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5) amine salts:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Propan-2-ol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5) amine salts:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Propan-2-ol:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

Result : negative

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5) amine salts:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative
Remarks	: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Propan-2-ol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
-----------------------	--

	Test Type: In vitro mammalian cell gene mutation test Result: negative
--	---

Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative
----------------------	--

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5) amine salts:

Germ cell mutagenicity - Assessment	: Weight of evidence does not support classification as a germ cell mutagen., Based on data from similar materials
-------------------------------------	--

Carcinogenicity

Not classified based on available information.

Components:

Propan-2-ol:

Species	: Rat
Application Route	: inhalation (vapor)
Exposure time	: 104 weeks
Method	: OECD Test Guideline 451
Result	: negative

IARC	No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
------	--

OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
------	--

NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
-----	--

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

Reproductive toxicity

Not classified based on available information.

Components:

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5) amine salts:

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity, Based on data from similar materials

STOT-single exposure

May cause drowsiness or dizziness.

Causes damage to organs (Lungs, larynx) if inhaled.

Product:

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Lungs, larynx
Assessment : Shown to produce significant health effects in animals at concentrations of 1.0 mg/l/4h or less.
Remarks : Based on data from similar materials

Components:

Propan-2-ol:

Assessment : May cause drowsiness or dizziness.

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5) amine salts:

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Lungs, larynx
Assessment : Shown to produce significant health effects in animals at concentrations of 1.0 mg/l/4h or less.
Remarks : Based on data from similar materials

STOT-repeated exposure

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

Repeated dose toxicity

Components:

Propan-2-ol:

Species	:	Rat
NOAEL	:	12.5 mg/l
Application Route	:	inhalation (vapor)
Exposure time	:	104 Weeks

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 526 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 526 mg/l Exposure time: 48 h Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): > 526 mg/l Exposure time: 72 h Remarks: Based on data from similar materials NOEC (Pseudokirchneriella subcapitata (green algae)): 526 mg/l Exposure time: 72 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 50 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials

Components:

Propan-2-ol:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h
Toxicity to microorganisms	:	EC50 (Pseudomonas putida): > 1,050 mg/l Exposure time: 16 h

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5) amine salts:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 110 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 102 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 105 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 105 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 6.59 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Persistence and degradability

Components:

Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1,19 (BOD5)
COD: 2,23
BOD/COD: 53 %

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5) amine salts:

Biodegradability : Result: Not readily biodegradable.
Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

Propan-2-ol:

Partition coefficient: n-octanol/water : log Pow: 0.05

Mobility in soil

No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- | | | |
|------------------------|---|--|
| Waste from residues | : | Dispose of in accordance with local regulations.
Do not dispose of waste into sewer. |
| Contaminated packaging | : | Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product. |

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

- | | | |
|---------------------------|---|---|
| UN number | : | UN 1993 |
| Proper shipping name | : | FLAMMABLE LIQUID, N.O.S.
(Propan-2-ol) |
| Class | : | 3 |
| Packing group | : | III |
| Labels | : | 3 |
| Environmentally hazardous | : | no |

IATA-DGR

- | | | |
|--|---|---|
| UN/ID No. | : | UN 1993 |
| Proper shipping name | : | Flammable liquid, n.o.s.
(Propan-2-ol) |
| Class | : | 3 |
| Packing group | : | III |
| Labels | : | Flammable Liquids |
| Packing instruction (cargo aircraft) | : | 366 |
| Packing instruction (passenger aircraft) | : | 355 |

IMDG-Code

- | | | |
|----------------------|---|---|
| UN number | : | UN 1993 |
| Proper shipping name | : | FLAMMABLE LIQUID, N.O.S.
(Propan-2-ol) |
| Class | : | 3 |
| Packing group | : | III |
| Labels | : | 3 |
| EmS Code | : | F-E, <u>S-E</u> |
| Marine pollutant | : | no |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number	:	UN 1993
Proper shipping name	:	Flammable liquids, n.o.s. (Propan-2-ol)
Class	:	3
Packing group	:	III
Labels	:	FLAMMABLE LIQUID
ERG Code	:	128
Marine pollutant	:	no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	Flammable (gases, aerosols, liquids, or solids)
		Acute toxicity (any route of exposure)
		Specific target organ toxicity (single or repeated exposure)
		Serious eye damage or eye irritation

SARA 313	:	The following components are subject to reporting levels established by SARA Title III, Section 313:
-----------------	---	--

Propan-2-ol	67-63-0	>= 10 - < 20 %
-------------	---------	----------------

US State Regulations

Pennsylvania Right To Know

Water	7732-18-5
Propan-2-ol	67-63-0
Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5) amine salts	Not Assigned

California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more in-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

formation go to www.P65Warnings.ca.gov. Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.

California List of Hazardous Substances

Propan-2-ol	67-63-0
-------------	---------

California Permissible Exposure Limits for Chemical Contaminants

Propan-2-ol	67-63-0
-------------	---------

Additional regulatory information

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5) amine salts

The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product.

See 40 CFR § 721.10855

This material contains one or more substances which are subject to a TSCA Section 5 Consent Order or Significant New Use Rule (SNUR).


This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D:

P-12-0450

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	4
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Capstone™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-
---	---	---

according to the OSHA Hazard Communication Standard



Version	Revision Date:	SDS Number:	Date of last issue: 07/23/2024
10.5	10/17/2024	1351611-00051	Date of first issue: 02/27/2017

Data Sheet [cy, http://echa.europa.eu/](http://echa.europa.eu/)

Revision Date : 10/17/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8