

# Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR  
Date of issue: 11/01/2017 Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Trade name : Jumbo Feltip Paint Marker: White, Yellow, Black, Red

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Marker

#### 1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc.  
1201 Pratt Boulevard  
Elk Grove Village, IL. 60007-5746  
Phone: (847) 956-7600  
Fax: (847) 956-9885  
E-mail: customer\_service@laco.com



#### 1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable liquids, Category 3	H226
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Carcinogenicity, Category 2	H351
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity — Repeated exposure, Category 2	H373

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Warning

Hazard statements (GHS) :

H226 - Flammable liquid and vapour.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H332 - Harmful if inhaled.  
H335 - May cause respiratory irritation.  
H351 - Suspected of causing cancer (Inhalation).  
H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS) :

P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe vapours.  
P264 - Wash hands thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves.

# Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P308+P313 - If exposed or concerned: Get medical advice/attention.  
 P314 - Get medical advice/attention if you feel unwell.  
 P332+P313 - If skin irritation occurs: Get medical advice/attention.  
 P337+P313 - If eye irritation persists: Get medical advice/attention.  
 P362+P364 - Take off contaminated clothing and wash it before reuse.  
 P370+P378 - In case of fire: Use carbon dioxide (CO<sub>2</sub>), Dry chemical, Water fog, foam to extinguish.  
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235 - Store in a well-ventilated place. Keep cool.  
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS classification
Hydrocarbon resin	(CAS-No.) 68131-77-1	51: Black 26: Red, White, Yellow	Comb. Dust
Xylene	(CAS-No.) 1330-20-7	49: White 42: Yellow 33: Red and Black	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Titanium dioxide	(CAS-No.) 13463-67-7	24: White 17: Red and Yellow	Carc. 2, H351 (as dust)
Colorant		23: Red 14: Yellow	Not classified
Carbon black	(CAS-No.) 1333-86-4	15	Carc. 2, H351 (as dust)
Ethylbenzene	(CAS-No.) 100-41-4	1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:dust,mist), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304

Hazard classification of this material is based on the worst possible case  
 Full text of hazard classes and H-statements : see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.  
 First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.  
 First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.  
 First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation.  
 Symptoms/effects after skin contact : Irritation.  
 Symptoms/effects after eye contact : Eye irritation.

# Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.  
Explosion hazard : Flammable vapours heavier than air/can accumulate.  
Reactivity : No dangerous reactions known.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : No open flames, no sparks, and no smoking. Do not breathe vapours. Avoid contact with skin, eyes and clothing.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Do not get in eyes, on skin, or on clothing. Wear Nitrile rubber gloves, natural rubber gloves. Gloves must be replaced after each use and whenever signs of wear or perforation appear.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.  
Incompatible products : Strong oxidizers.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Ethylbenzene (100-41-4)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	434 mg/m <sup>3</sup>
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	543 mg/m <sup>3</sup>
ACGIH	ACGIH STEL (ppm)	125 ppm

# Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

<b>Ethylbenzene (100-41-4)</b>		
ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Canada (Quebec)	VECD (mg/m <sup>3</sup> )	543 mg/m <sup>3</sup>
Canada (Quebec)	VECD (ppm)	125 ppm
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	434 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (ppm)	100 ppm
<b>Titanium dioxide (13463-67-7)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
ACGIH	Remark (ACGIH)	LRT irr; A4 (Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histologic type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiologic studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Canada (Quebec)	Notations and remarks	(la poussière totale), (note1)
<b>Hydrocarbon resin (68131-77-1)</b>		
Not applicable		
<b>Colorant</b>		
Not applicable		
<b>Xylene (1330-20-7)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	434 mg/m <sup>3</sup>
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	651 mg/m <sup>3</sup>
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Canada (Quebec)	VECD (mg/m <sup>3</sup> )	651 mg/m <sup>3</sup>
Canada (Quebec)	VECD (ppm)	150 ppm
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	434 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (ppm)	100 ppm
<b>Carbon black (1333-86-4)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
ACGIH	Remark (ACGIH)	Bronchitis
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Fibres de carbone et de graphite; Poussière totale) 5 mg/m <sup>3</sup> (Fibres de carbone et de graphite; Poussière respirable) 3.5 mg/m <sup>3</sup>

### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

# Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Hand protection	: Protective gloves. (PVC, neoprene, nitrile rubber). Gloves must be replaced after each use and whenever signs of wear or perforation appear.
Eye protection	: Eye protection should only be necessary where liquid could be splashed or sprayed.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: No respiratory protection needed under normal use conditions.
Environmental exposure controls	: Avoid release to the environment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Solid marker containing liquid colored paint.
Colour	: Various
Odour	: aromatic
Odour threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 139 - 141 °C
Flash point	: 30 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: > 1
Relative density	: > 1
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 50 cSt
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

Strong oxidizers.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

**Likely routes of exposure** : Inhalation; Dermal  
**Acute toxicity** : Inhalation:dust,mist: Harmful if inhaled.

Jumbo Feltip Paint Marker: White, Yellow, Black, Red	
ATE US (dust,mist)	3 mg/l/4h

Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	17.8 ml/kg
LC50 inhalation rat (ppm)	< 1500 ppm
ATE (oral)	3500 mg/kg bodyweight
ATE (dust,mist)	1.5 mg/l/4h

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 6.82 mg/l/4h

Xylene (1330-20-7)	
LD50 oral rat	4300 mg/kg
LC50 inhalation rat (ppm)	6247 ppm/4h
ATE (oral)	4300 mg/kg bodyweight
ATE (gases)	6247 ppmv/4h
ATE (vapours)	47635 mg/l/4h
ATE (dust,mist)	1.5 mg/l/4h

Carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg
LC50 inhalation rat (mg/l)	> 4.6 mg/m <sup>3</sup> 4 h

**Skin corrosion/irritation** : Causes skin irritation.  
**Serious eye damage/irritation** : Causes serious eye irritation.  
**Respiratory or skin sensitisation** : Not classified  
**Germ cell mutagenicity** : Not classified  
**Carcinogenicity** : Suspected of causing cancer (Inhalation).

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans

Titanium dioxide (13463-67-7)	
NOAEL (chronic, oral, animal/male, 2 years)	5 mg/kg bodyweight rat
Additional information	Carcinogen Inhalation of dust
IARC group	2B - Possibly carcinogenic to humans, as dust

Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans, Inhalation of dust

**Reproductive toxicity** : Not classified  
**Specific target organ toxicity (single exposure)** : May cause respiratory irritation.  
**Specific target organ toxicity (repeated exposure)** : May cause damage to organs (hearing organs) through prolonged or repeated exposure.  
**Aspiration hazard** : Not classified  
**Symptoms/effects after inhalation** : May cause respiratory irritation.  
**Symptoms/effects after skin contact** : Irritation.  
**Symptoms/effects after eye contact** : Eye irritation.

### SECTION 12: Ecological information

**12.1. Toxicity**  
**Ecology - general** : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

# Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Ethylbenzene (100-41-4)	
LC50 fish 1	5.1 mg/l
EC50 other aquatic organisms 1	7.7 mg/l
NOEC (acute)	3.3 mg/l

### 12.2. Persistence and degradability

Ethylbenzene (100-41-4)	
Persistence and degradability	Not established.

Carbon black (1333-86-4)	
Persistence and degradability	Not readily biodegradable.

### 12.3. Bioaccumulative potential

Ethylbenzene (100-41-4)	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

Jumbo Feltip Paint Marker: White, Yellow, Black, Red	
Mobility in soil	Not established

### 12.5. Other adverse effects

No additional information

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapours may accumulate in the container.

## SECTION 14: Transport information

In accordance with US-DOT 49-CFR and the HMR / TDG / ADR / IMDG / ICAO / IATA

In accordance with DOT

Transport document description : UN1263 Paint, 3, III  
UN-No. (DOT) : UN1263  
Proper Shipping Name (DOT) : Paint  
Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Packing group (DOT) : III - Minor Danger  
Hazard labels (DOT) : 3 - Flammable liquid



### Transportation of Dangerous Goods

Transport document description : UN1263 Paint, 3, III  
UN-No. (TDG) : UN1263  
Proper Shipping Name (Transportation of Dangerous Goods) : Paint  
TDG Primary Hazard Classes : 3 - Class 3 - Flammable Liquids  
Packing group : III - Minor Danger

### Transport by sea

UN-No. (IMDG) : 1263  
Proper Shipping Name (IMDG) : PAINT

# Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5 L

### Air transport

UN-No. (IATA)	: 1263
Proper Shipping Name (IATA)	: PAINT
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

<b>Ethylbenzene (100-41-4)</b>	
Subject to reporting requirements of United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory	
CERCLA RQ	1000 lb
<b>Titanium dioxide (13463-67-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Hydrocarbon resin (68131-77-1)</b>	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).
<b>Xylene (1330-20-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
<b>Carbon black (1333-86-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### CANADA

<b>Ethylbenzene (100-41-4)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
<b>Titanium dioxide (13463-67-7)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
<b>Hydrocarbon resin (68131-77-1)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
<b>Xylene (1330-20-7)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
<b>Carbon black (1333-86-4)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	

### 15.3. US State regulations

<b>Jumbo Feltip Paint Marker: White, Yellow, Black, Red</b>				
State or local regulations		The carbon black in this product is bound and is not respirable. California Prop. 65 warnings are not required.		
<b>Ethylbenzene (100-41-4)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	54



# Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Titanium dioxide (13463-67-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

Carbon black (1333-86-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

Ethylbenzene (100-41-4)				
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Maine - Air Pollutants - Hazardous Air Pollutants U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Washington - Permissible Exposure Limits - TWAs				

Titanium dioxide (13463-67-7)				
U.S. - Minnesota - Hazardous Substance List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York - Right to Know List of Hazardous Substances U.S. - Washington - Permissible Exposure Limits - TWAs U.S. - Washington - Permissible Exposure Limits - STELs				

Carbon black (1333-86-4)				
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - New Jersey - Right to Know Hazardous Substance List				

### SECTION 16: Other information

Data sources : ACGIH (American Conference of Government Industrial Hygienists).  
 Chemical Inspection & Regulation Service; accessed at: [http://www.cirs-reach.com/Inventory/Global\\_Chemical\\_Inventories.html](http://www.cirs-reach.com/Inventory/Global_Chemical_Inventories.html).  
 Component Supplier SDSs.  
 European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.  
 European Chemicals Agency (ECHA) Registered Substances list.  
 Internal Company test data.  
 Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.  
 National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.  
 OSHA 29CFR 1910.1200 Hazard Communication Standard.  
 TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Full text of H-phrases:

H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin.
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

# Jumbo Feltip Paint Marker: White, Yellow, Black, Red

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

---

# Jumbo Feltip Paint Marker: White, Yellow, Black, Red


## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

### Abbreviations and acronyms:

ACGIH (American Conference of Government Industrial Hygienists)
ATE: Acute Toxicity Estimate
CAS (Chemical Abstracts Service) number
CLP: Classification, Labelling, Packaging.
EC50: Environmental Concentration associated with a response by 50% of the test population.
GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
LD50: Lethal Dose for 50% of the test population
LC50: Median lethal concentration
STEL: Short Term Exposure Limits
TSCA: Toxic Substances Control Act
TWA: Time Weighted Average

- NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
- NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



**SDS Prepared by:** The Redstone Group, LLC  
6077 Frantz Rd.  
Suite 206  
Dublin, OH USA 43017  
T 614-923-7472  
[www.redstonegrp.com](http://www.redstonegrp.com)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*