

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Starblast™ XL

Version 15.0 Revision Date: 05/07/2025 SDS Number: 1331991-00054 Date of last issue: 10/16/2024
Date of first issue: 02/27/2017

SECTION 1. IDENTIFICATION

Product name : Starblast™ XL

SDS-Identcode : 130000030940

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Abrasive blasting
Sand blasting

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

|| Not a hazardous substance or mixture.

Other hazards

None known.

GHS label elements

|| No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Staurolite#	12182-56-8*	>= 80 - <= 100	TSC
Rutile (TiO ₂)	1317-80-2*	>= 0.1 - <= 1	TSC

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Starblast™ XL

Version 15.0	Revision Date: 05/07/2025	SDS Number: 1331991-00054	Date of last issue: 10/16/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Quartz	14808-60-7*	>= 0.1 - <= 1	TSC
--------	-------------	---------------	-----

Voluntarily-disclosed substance

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	: Wash with water and soap as a precaution. Get medical attention if symptoms occur.
In case of eye contact	: Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	: irritant effects
Protection of first-aiders	: No special precautions are necessary for first aid responders.
Notes to physician	: Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Not applicable Will not burn
Unsuitable extinguishing media	: Not applicable Will not burn
Specific hazards during fire fighting	: Exposure to combustion products may be a hazard to health.
Hazardous combustion products	: No hazardous combustion products are known
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Starblast™ XL

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2024
15.0	05/07/2025	1331991-00054	Date of first issue: 02/27/2017

Special protective equipment : Wear self-contained breathing apparatus for firefighting if necessary.
for fire-fighters Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment

Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
------------	---------	----------------------------------	--	-------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Starblast™ XL

Version 15.0 Revision Date: 05/07/2025 SDS Number: 1331991-00054 Date of last issue: 10/16/2024
Date of first issue: 02/27/2017

Rutile (TiO ₂)	1317-80-2	TWA (Respirable particulate matter)	2.5 mg/m ³ (Titanium dioxide)	ACGIH
Quartz	14808-60-7	TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL

This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Quartz

Engineering measures : If using this product as an abrasive blast agent in confined areas, airborne dust levels should be controlled by physical enclosure of the abrasive blasting operation. The enclosure should be exhaust ventilated.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection
Material : Protective gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Starblast™ XL

Version 15.0	Revision Date: 05/07/2025	SDS Number: 1331991-00054	Date of last issue: 10/16/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : solid, dry, free flowing granules

Color : red brown

Odor : odorless

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : 2,498 °F / 1,370 °C

Initial boiling point and boiling range : No data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Will not burn
Not expected to form explosive dust-air mixtures.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 3.7

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Starblast™ XL

Version 15.0	Revision Date: 05/07/2025	SDS Number: 1331991-00054	Date of last issue: 10/16/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Solubility(ies) Water solubility	: insoluble
Partition coefficient: n-octanol/water	: Not applicable
Autoignition temperature	: No data available
Decomposition temperature	: The substance or mixture is not classified self-reactive.
Viscosity Viscosity, kinematic	: Not applicable
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: None known.
Conditions to avoid	: None known.
Incompatible materials	: None.
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Staurolite:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
---------------------	-----------------------------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Starblast™ XL

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2024
15.0	05/07/2025	1331991-00054	Date of first issue: 02/27/2017

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Rutile (TiO₂):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 425
Remarks: Based on data from similar materials

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Rutile (TiO₂):

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Information given is based on data obtained from similar substances.

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Rutile (TiO₂):

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Rutile (TiO₂):

Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Starblast™ XL

Version 15.0	Revision Date: 05/07/2025	SDS Number: 1331991-00054	Date of last issue: 10/16/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

||Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Rutile (TiO₂):

||Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Not classified based on available information.

Components:

Rutile (TiO₂):

||Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

Quartz:

||Species : Humans
||Application Route : inhalation (dust/mist/fume)
||Result : positive
||Remarks : This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

||Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

||IARC Group 2B: Possibly carcinogenic to humans
Rutile (TiO₂) 1317-80-2

||OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

||NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Rutile (TiO₂):

||Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

STOT-single exposure

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Starblast™ XL

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2024
15.0	05/07/2025	1331991-00054	Date of first issue: 02/27/2017

STOT-repeated exposure

Not classified based on available information.

Components:

Rutile (TiO₂):

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Quartz:

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Lungs
Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Rutile (TiO₂):

Species : Rat
NOAEL : 24,000 mg/kg
LOAEL : > 24,000 mg/kg
Application Route : Ingestion
Exposure time : 28 d
Remarks : No significant adverse effects were reported
Based on data from similar materials

Quartz:

Species : Humans
LOAEL : 0.053 mg/m³
Application Route : inhalation (dust/mist/fume)
Remarks : This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Rutile (TiO₂):

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Starblast™ XL

Version 15.0	Revision Date: 05/07/2025	SDS Number: 1331991-00054	Date of last issue: 10/16/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

	Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	: ErC50 (algae): > 10,000 mg/l Exposure time: 72 h Remarks: Based on data from similar materials
	NOEC (algae): 5,600 mg/l Exposure time: 72 h Remarks: Based on data from similar materials

Quartz:

Ecotoxicology Assessment

Acute aquatic toxicity	: No toxicity at the limit of solubility.
Chronic aquatic toxicity	: No toxicity at the limit of solubility.

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Rutile (TiO₂):

Bioaccumulation	: Remarks: Bioaccumulation is unlikely. Based on data from similar materials
-----------------	---

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	: Dispose of in accordance with local regulations. Do not dispose of waste into sewer.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Starblast™ XL

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2024
15.0	05/07/2025	1331991-00054	Date of first issue: 02/27/2017

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Staurolite	12182-56-8
Tourmaline	1317-93-7
Leucosene	12173-81-8

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Regulated Carcinogens

Quartz	14808-60-7
--------	------------

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Starblast™ XL


Version
15.0

Revision Date:
05/07/2025

SDS Number:
1331991-00054

Date of last issue: 10/16/2024
Date of first issue: 02/27/2017

NFPA 704:



HMIS® IV:

HEALTH	/	0
FLAMMABILITY		0
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Starblast™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

This product contains Naturally Occurring Radioactive Materials (NORMs) at levels below U.S. Nuclear Regulatory Commission licensing requirements at 10 CFR 40. Many local jurisdictions are developing new regulations for the disposal of waste containing Naturally Occurring Radioactive Materials (NORM) or Technologically Enhanced Naturally Occurring Radioactive Materials (TENORM) above background levels. Consult and comply with current regulations.

The main radiological hazard from the product is internal exposure from small amounts of alpha particles given off by inhaled dust. Industrial hygiene practices aimed at control of airborne dust can lessen the potential for exposure. Overexposure by inhalation to inhaled dusts containing radioactive uranium, thorium, and radium may cause lung cancer. Low level gamma radiation in proximity to bulk or bagged stockpiles of these products may present a lesser, external exposure that can be managed by limiting close proximity for long time periods to large volumes of material. With respect to dust exposure, evaluation and calculation based upon dosimetry (ICRP 68) yield the following guidance to ensure that inhalation intake is less than a 100 mrem/yr public dose reference point for radionuclides.

For a total dust with aerodynamic diameter of 1 µm, the calculated reference dust level is 17.4 mg/m³. For a total dust with aerodynamic diameter of 5 µm, the calculated reference dust level is 27.0 mg/m³. For a total dust with aerodynamic diameter of 10 µm, the calculated reference dust level is 39.8 mg/m³.

The calculations noted above are based upon 8 hr/day TWAs. It should be noted that for these products, the actual particle physical diameter is approximately 1/2 the effective aerodynamic diameter. For these products, as shipped, with essentially no particles as small as calculated above, the highest total dust level can provide a conservative limit. However, if during handling or use the particles are broken down to finer particle sizes, lower levels of total dust would apply.

These reference calculations for radionuclides may or may not provide the most conservative recommendation vs. other trace contaminants as compared to specific country dust contaminant li-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Starblast™ XL

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2024
15.0	05/07/2025	1331991-00054	Date of first issue: 02/27/2017

mit calculations. It is recommended that the user compare and calculate or measure for specific contaminants vs. reference limits, especially if particles are broken down, to determine the most appropriate standard for protection.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

according to the OSHA Hazard Communication Standard



Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2024
15.0	05/07/2025	1331991-00054	Date of first issue: 02/27/2017

Data Sheet [cy, http://echa.europa.eu/](http://echa.europa.eu/)

Revision Date : 05/07/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8