

SAFETY DATA SHEET

U.S. HazCom GHS Format



Date Issued : 11/21/2019

SDS No : 250503

Drivers Choice Carpet Cleaner**1. PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: Drivers Choice Carpet Cleaner
GENERAL USE: Cleaning Agent
PRODUCT DESCRIPTION: Cleaner
PRODUCT CODE: 250503
PRODUCT FORMULATION NAME: Aerosol Carpet Cleaner
GENERIC NAME: Carpet Cleaner

MANUFACTURER

SMB International, LLC
 121 Highway 36
 STE 180
 West Long Branch, NJ 07764
Emergency Contact: Responder-Manny Ehrlich
Emergency Phone: 973-809-6700
Customer Service: 330-773-7669
E-Mail: msds@smbinternational.com

24 HR. EMERGENCY TELEPHONE NUMBERS

Poison Control Center (Medical) : (800) 222-1222
CANUTEC (Canadian Transportation) : (613) 996-6666
CHEMTREC (US Transportation) : (800) 262-8200

2. HAZARDS IDENTIFICATION**GHS CLASSIFICATIONS****Health:**

Acute Toxicity (Inhalation), Category 4
 Acute Toxicity (Oral), Category 4
 Acute Toxicity (Dermal), Category 4
 Skin Irritation, Category 3
 Serious Eye Damage, Category 2A

Physical:

Flammable Aerosols, Category 2

GHS LABEL

Flame

Exclamation
mark**SIGNAL WORD:** DANGER**HAZARD STATEMENTS**

H223: Flammable aerosol.
 H280: Contains gas under pressure; may explode if heated.
 H315 + H320: Causes skin and eye irritation.

PRECAUTIONARY STATEMENTS

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P235+P410: Keep cool. Protect from sunlight.
 P251: Do not pierce or burn, even after use.
 P264: Wash ... thoroughly after handling.
 P271: Use only outdoors or in a well-ventilated area.

Response:

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P301+P312: IF SWALLOWED: Call a POISON CENTER/ doctor/...if you feel unwell.
 P304+P341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P302+P352: IF ON SKIN: Wash with plenty of water/...
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313: If eye irritation persists: Get medical advice/attention.
 P314: Get medical advice/attention if you feel unwell.

Storage:

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P102: Keep out of reach of children.

Disposal:

P501: Dispose of contents: All disposal practices must be in accordance with local, state, national and international regulations.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: Caution! Irritant! May irritate eyes. Refer to Section 4 and 11 for health hazard identification.

POTENTIAL HEALTH EFFECTS

EYES: Causes eye irritation on direct contact.

SKIN: May cause skin irritation upon prolonged contact.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Propane/butane	< 5 - 10	68476-86-8
2- Butoxyethanol	< 2 - 5	111-76-2
Ethanol, 2-(2-butoxyethoxy)-	< 1 - 3	112-34-5
Linear Primary Alcohol Ethoxylate	< 0 - 3	68439-46-3
Sodium Metasilicate Pentahydrate	< 0 - 2	10213-79-3

4. FIRST AID MEASURES

EYES: Adverse effect not expected from this product. In case of eye irritation rinse with plenty of water. If irritation persists consult a physician,

SKIN: Immediately remove all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. If irritation develops or persists seek medical attention. Wash contaminated clothing before re-use.

INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

INHALATION: Ensure that this material is not discharged into the human breathing zone

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: May be irritating.

SKIN: Contact may cause skin irritation.

NOTES TO PHYSICIAN: Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Aerosol

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Hazardous decomposition products: Carbon Oxides and Formaldehyde.

EXPLOSION HAZARDS: Aerosol containers, when exposed to heat from fire, may build pressure and explode. Vapors may accumulate in a confined space and create a flammable atmosphere.

FIRE FIGHTING PROCEDURES: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Water spray may be used to keep fire exposed containers cool.

FIRE FIGHTING EQUIPMENT: Respiratory and eye protection are required for fire fighting personnel. Full protective equipment (Bunker Gear) and self contained breathing apparatus (SCBA) should be used for all indoor fires and any significant outdoor fires. For small outdoor fires, which may easily be extinguished with a portable fire extinguisher, use of a SCBA may not be required.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon and formaldehyde.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

LARGE SPILL: Always employ the proper personal protective equipment. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas through the use of berms. Collect liquid with explosion proof pumps if possible. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Fluorocarbon alcohol resistant foams may be applied to spill to diminish vapor and fire hazard.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Take precautions to avoid release to the environment. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.

LAND SPILL: Construct temporary dikes of dirt, sand, or any appropriate readily available noncombustible (sawdust) material to prevent spreading of the material.

AIR SPILL: If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop the leak, and to flush spills away from exposures.

GENERAL PROCEDURES: Absorb with diatomaceous earth or equivalent inert material. Shovel up and dispose of at an appropriate waste disposal facility according to current applicable laws and regulations, and product characteristics at time of disposal.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: No special handling procedures are required. Wash thoroughly after handling. . Use with adequate ventilation. Avoid breathing spray or mist.

HANDLING: Handle and use in a manner consistent with good industrial/manufacturing techniques and practices. Open and handle with care.

STORAGE: Aerosol Storage Level: 3

Store in a well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container tightly closed. The floor of the storage room must be impermeable, non-oxidizing and with contention dikes to retain the product in case of leakage. Store in adequate storage tanks placed in containment basin to retain product in case of leakage.

STORAGE TEMPERATURE: Store in closed original container. Protect from direct sun light. Do not expose to temperatures exceeding 50 C/122 F.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
EXPOSURE LIMITS				
Chemical Name	Type		ppm	mg/m ³
Propane/butane	OSHA PEL	TWA	1800	
2- Butoxyethanol	OSHA PEL	TWA	50(S)	240(S)
		STEL	NL	NL
	ACGIH TLV	TWA	25(S)	121(S)
		STEL	NL	NL
	Supplier OEL	TWA	NL	NL
		STEL	NL	NL

ENGINEERING CONTROLS: If vapors, or mists are generated, provide local exhaust ventilation to prevent airborne exposure. All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94)

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear chemical splash goggles and face shield when eye and face contact is possible due to pressure in container.

SKIN: To prevent any contact, wear impervious protective clothing such as neoprene or butyl rubber gloves, apron, boots or whole bodysuit, as appropriate.

RESPIRATORY: No special precautions are necessary under normal operating conditions.

If the exposure limit is exceeded and engineering controls are not feasible, a half-face organic vapor respirator may be worn for up to ten times the exposure limit or maximum use concentration specified by the respirator supplier or regulatory agency. A full-face organic vapor respirator may be employed for use in atmospheres that contain up to 50 times the exposure limit. For emergencies or instances where the exposure levels are not known a positive- pressure, full-face piece, air supplied respirator should be employed.

PROTECTIVE CLOTHING: Long sleeved clothing should always be considered when handling chemical substances.

WORK HYGIENIC PRACTICES: Good personal hygiene practices should always be followed. Keep away from food, drink and animal feeding stuffs. When using, do not eat, drink or smoke. Hands and any other exposed area should be washed thoroughly with soap and water after contact. Regular laundering of contaminated clothing is essential to reduce indirect skin contact.

OTHER USE PRECAUTIONS: Keep away from sources of ignition.

COMMENTS: **KEEP OUT OF THE REACH OF CHILDREN.**

9. PHYSICAL AND CHEMICAL PROPERTIES

Chemical Name	Flash Point (°C)
Propane/butane	-104 Estimated
Linear Primary Alcohol Ethoxylate	334

PHYSICAL STATE: Aerosolized Liquid

ODOR: Characteristic

APPEARANCE: Clear Liquid

COLOR: Colorless to Yellow

PHYSICAL STATE COMMENTS: Aerosol

pH: NA = Not Applicable

FLASH POINT AND METHOD: -104.400°C (-156°F) to 0°C (0°F) TAG CC

AUTOIGNITION TEMPERATURE: 0°C (0°F) to 0°C (0°F)

VAPOR PRESSURE: 0

VAPOR DENSITY: 0

BOILING POINT: ~ -204.400°C (-336°F) to -42.200°C (-44°F)

SOLUBILITY IN WATER: Completely soluble.

SPECIFIC GRAVITY: ~ 0.900 to 0.96 (Water = 1.00)

(VOC): ~ 9 to 9.900 % by wt.

10. STABILITY AND REACTIVITY

REACTIVITY: Not Available

HAZARDOUS POLYMERIZATION: Material will not polymerize.

STABILITY: This product is stable under storage at normal ambient temperatures.

CONDITIONS TO AVOID: Avoid all possible sources of ignition (spark or flame).

POSSIBILITY OF HAZARDOUS REACTIONS: None Expected.

HAZARDOUS DECOMPOSITION PRODUCTS: Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

INCOMPATIBLE MATERIALS: Avoid Strong Oxidizing Agents

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀
Linear Primary Alcohol Ethoxylate	1400 to 2700	> 4000

SERIOUS EYE DAMAGE/IRRITATION: May be irritating to eyes and skin.

CARCINOGENICITY

IARC: Not Listed by IARC

NTP: Not Listed by NTP

OSHA: Not Listed by OSHA

STOT-REPEATED EXPOSURE: Severe defatting of the skin.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Do not allow to enter into surface water or drains.

ECOTOXICOLOGICAL INFORMATION: Avoid exposing to the environment, no specific aquatic data available.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal must comply with federal, state, and local disposal or discharge laws.

FOR LARGE SPILLS: Dispose of waste at an appropriate waste disposal facility according to current applicable laws and regulations.

PRODUCT DISPOSAL: Collect in appropriate containers. Dispose of waste at an appropriate waste disposal facility in accordance with current applicable laws and regulation, and product characteristics at time of disposal.

EMPTY CONTAINER: Empty container retains product residue and can be hazardous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks, static electricity, or other sources of ignition. Dispose of packaging or containers in accordance with local, regional, national and international regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Limited Quantity

VESSEL (IMO/IMDG)

SHIPPING NAME: AEROSOLS, flammable

TECHNICAL NAME: Aerosols, Limited Quantity

UN/NA NUMBER: 1950

PRIMARY HAZARD CLASS/DIVISION: 2.1

LIMITED QUANTITY: Yes

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS	TSCA SECTION
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	12b,
Linear Primary Alcohol Ethoxylate	68439-46-3	

CLEAN AIR ACT

Chemical Name	Wt.%	CAS
Propane/butane	< 5 - 10	68476-86-8

CALIFORNIA PROPOSITION 65: This product does not contain listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

16. OTHER INFORMATION

REASON FOR ISSUE: NEW PRODUCT


APPROVED BY: Scott Margulis **TITLE:** President

PREPARED BY: S Margulis **Date Prepared:** 11/21/2019

HMIS RATING

HEALTH	<input type="checkbox"/>	1
FLAMMABILITY		2
PHYSICAL HAZARD		0
PERSONAL PROTECTION		B

NFPA CODES



MANUFACTURER SUPPLEMENTAL NOTES: All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Manufacturer shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the Manufacturer to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

MANUFACTURER DISCLAIMER: Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of use of the product are therefore assumed by the user. Nothing is intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users.