

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

Section 1: Identification

Product identifier : Capstone™ FS-93

SDS-Identcode : 130000141339

Recommended use of the chemical and restrictions on use

Recommended use : Coatings
Surfactant

Restrictions on use : Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

Manufacturer or supplier's details

Company : The Chemours Company Singapore PTE. LTD.

Address : 1 HarbourFront Place, #16-01 HarbourFront Tower One
Singapore 098633

Telephone : 65-6715-8688

Emergency telephone number : 1800 315 8134

Telefax : 65-6715-8697

Section 2: Hazard identification

Classification of the substance or mixture

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Serious eye damage/eye irritation : Category 2

Specific target organ toxicity - single exposure (Inhalation) : Category 1 (Lungs, larynx)

GHS Label elements, including precautionary statements

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

Hazard pictograms



Signal word

: Danger

Hazard statements

: H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H370 Causes damage to organs (Lungs, larynx) if inhaled.

Precautionary statements

: **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

Other hazards which do not result in classification

Inhalation of decomposition products in high concentration may cause shortness of breath (lung oedema).

Vapours may form explosive mixture with air.

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Propan-2-ol	67-63-0	≥ 10 -< 20
Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts	Not Assigned	≥ 10 -< 20

Section 4: First-aid measures

Description of necessary first-aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention.

In case of skin contact : Remove contaminated clothing and shoes.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed

Risks : Inhalation may provoke the following symptoms:
Central nervous system depression
respiratory tract irritation
Cough
sneezing
runny nose
sore throat
Shortness of breath
Eye contact may provoke the following symptoms

SAFETY DATA SHEET



Capstone™ FS-93

Version 2.1	Revision Date: 23.07.2024	SDS Number: 6525499-00010	Date of last issue: 25.03.2024 Date of first issue: 02.10.2020
----------------	------------------------------	------------------------------	---

Pain
tearing
Swelling of tissue
Redness
Impairment of vision
Causes serious eye irritation.
Harmful if inhaled.
Causes damage to organs if inhaled.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

Section 5: Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates

Special protective actions for fire-fighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

so.
Evacuate area.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

Section 7: Handling and storage

Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Do not breathe mist or vapours.
Do not swallow.

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

Do not get in eyes.
Avoid prolonged or repeated contact with skin.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Keep in properly labelled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable gases
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Poisonous gases
Explosives

Section 8: Exposure controls/personal protection

Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of	Control parameters / Permissible	Basis
------------	---------	------------------------	----------------------------------	-------

SAFETY DATA SHEET



Capstone™ FS-93

Version
2.1Revision Date:
23.07.2024SDS Number:
6525499-00010Date of last issue: 25.03.2024
Date of first issue: 02.10.2020

		exposure)	concentration	
Propan-2-ol	67-63-0	PEL (long term)	400 ppm 983 mg/m ³	SG OEL
		PEL (short term)	500 ppm 1,230 mg/m ³	SG OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
hydrofluoric acid	7664-39-3	PEL (short term)	3 ppm 2.6 mg/m ³	SG OEL
		TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
Carbonyl difluoride	353-50-4	PEL (short term)	5 ppm 13 mg/m ³	SG OEL
		PEL (long term)	2 ppm 5.4 mg/m ³	SG OEL
		TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
Carbon dioxide	124-38-9	PEL (short term)	30,000 ppm 54,000 mg/m ³	SG OEL
		PEL (long term)	5,000 ppm 9,000 mg/m ³	SG OEL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
Carbon monoxide	630-08-0	PEL (long term)	25 ppm 29 mg/m ³	SG OEL
		TWA	25 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

Appropriate engineering control measures

: Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

Individual protection measures, such as personal protective equipment (PPE)

- | | |
|------------------------|---|
| Eye/face protection | : Wear the following personal protective equipment:
Safety goggles |
| Skin protection | : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc). |
| Respiratory protection | : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection. |
| Filter type | : Combined particulates, acidic gas/vapour and organic vapour type |
| Hand protection | |
| Material | : Chemical-resistant gloves |
| Remarks | : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday. |

Section 9: Physical and chemical properties

- | | |
|-----------------|-----------------------------|
| Appearance | : liquid |
| Colour | : clear, colourless, yellow |
| Odour | : alcohol-like |
| Odour Threshold | : No data available |
| pH | : 7 - 7.5 |

SAFETY DATA SHEET



Capstone™ FS-93

Version 2.1	Revision Date: 23.07.2024	SDS Number: 6525499-00010	Date of last issue: 25.03.2024 Date of first issue: 02.10.2020
----------------	------------------------------	------------------------------	---

Melting point/freezing point : No data available

Initial boiling point and boiling range : 83 °C

Flash point : 34 °C
Method: Pensky-Martens closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : 1.18 g/cm³

Solubility(ies)
Water solubility : soluble

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : > 200 °C

Viscosity
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics
Particle size : Not applicable

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

Section 10: Stability and reactivity

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Flammable liquid and vapour. Vapours may form explosive mixture with air. Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents

Hazardous decomposition products

Thermal decomposition	: hydrofluoric acid Carbonyl difluoride Carbon dioxide Carbon monoxide
-----------------------	---

Section 11: Toxicological information

Information on likely routes of exposure	: Inhalation Skin contact Ingestion Eye contact
--	--

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 425 Remarks: Based on data from similar materials
Acute inhalation toxicity	: Acute toxicity estimate (Rat): 1.5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Remarks: Based on data from similar materials

Components:

Propan-2-ol:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 25 mg/l Exposure time: 6 h

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 425
Remarks: Based on data from similar materials

Acute inhalation toxicity : Acute toxicity estimate (Rat): 0.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Propan-2-ol:

Species : Rabbit
Result : No skin irritation

Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Propan-2-ol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Propan-2-ol:

Test Type	: Buehler Test
Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Test Type	: Local lymph node assay (LLNA)
Exposure routes	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative
Remarks	: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Propan-2-ol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
	Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative

Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Germ cell mutagenicity - Assessment	: Weight of evidence does not support classification as a germ cell mutagen., Based on data from similar materials
-------------------------------------	--

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

Carcinogenicity

Not classified based on available information.

Components:

Propan-2-ol:

Species	: Rat
Application Route	: inhalation (vapour)
Exposure time	: 104 weeks
Method	: OECD Test Guideline 451
Result	: negative

Reproductive toxicity

Not classified based on available information.

Components:

Propan-2-ol:

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative
Effects on foetal development	: Test Type: Embryo-foetal development Species: Rat Application Route: Ingestion Result: negative

Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Reproductive toxicity - Assessment	: Weight of evidence does not support classification for reproductive toxicity, Based on data from similar materials
------------------------------------	--

STOT - single exposure

Causes damage to organs (Lungs, larynx) if inhaled.

Product:

Exposure routes	: inhalation (dust/mist/fume)
Target Organs	: Lungs, larynx
Assessment	: Shown to produce significant health effects in animals at concentrations of 1.0 mg/l/4h or less.
Remarks	: Based on data from similar materials

Components:

Propan-2-ol:

Assessment	: May cause drowsiness or dizziness.
------------	--------------------------------------

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Exposure routes	: inhalation (dust/mist/fume)
Target Organs	: Lungs, larynx
Assessment	: Shown to produce significant health effects in animals at concentrations of 1.0 mg/l/4h or less.
Remarks	: Based on data from similar materials

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Propan-2-ol:

Species	: Rat
NOAEL	: 12.5 mg/l
Application Route	: inhalation (vapour)
Exposure time	: 104 Weeks

Aspiration toxicity

Not classified based on available information.

Section 12: Ecological information

Toxicity

Product:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 526 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 526 mg/l Exposure time: 48 h Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (green algae)): > 526 mg/l Exposure time: 72 h Remarks: Based on data from similar materials NOEC (Pseudokirchneriella subcapitata (green algae)): 526 mg/l Exposure time: 72 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 50 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

Components:

Propan-2-ol:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h
Toxicity to microorganisms	:	EC50 (Pseudomonas putida): > 1,050 mg/l Exposure time: 16 h

Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 110 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 102 mg/l Exposure time: 48 h Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): > 105 mg/l Exposure time: 72 h Remarks: Based on data from similar materials
		NOEC (Pseudokirchneriella subcapitata (green algae)): 105 mg/l Exposure time: 72 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 6.59 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials

Persistence and degradability

Components:

Propan-2-ol:

Biodegradability	:	Result: rapidly degradable
BOD/COD	:	BOD: 1,19 (BOD5) COD: 2,23 BOD/COD: 53 %

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

Reaction mass of mixed 3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl phosphate and diphosphate salts:

Biodegradability : Result: Not readily biodegradable.
Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

Propan-2-ol:

Partition coefficient: n-octanol/water : log Pow: 0.05

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

Section 14: Transport information

International Regulations

UNRTDG

UN number : UN 1993
UN proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Propan-2-ol)
Transport hazard class(es) : 3
Packing group : III
Labels : 3
Environmental hazards : no

IATA-DGR

UN/ID No. : UN 1993
UN proper shipping name : Flammable liquid, n.o.s.

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

(Propan-2-ol)

Transport hazard class(es)	: 3
Packing group	: III
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 366
Packing instruction (passenger aircraft)	: 355

IMDG-Code

UN number	: UN 1993
Proper shipping name	: FLAMMABLE LIQUID, N.O.S. (Propan-2-ol)
Transport hazard class(es)	: 3
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
Marine pollutant	: no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Section 15: Regulatory information

Safety, health and environmental regulations specific for the product in question

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management Act and Environmental Protection and Management (Hazardous Substances) Regulations	: Not applicable
---	------------------

Fire Safety (Petroleum and Flammable Materials) Regulations	: Isopropanol
---	---------------

Section 16: Other information

Revision Date	: 23.07.2024
---------------	--------------

Other information	: Capstone™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC. Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or
-------------------	---

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

nominated distributors.

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
SG OEL : Singapore. Workplace Safety and Health (General Provisions) Regulations - First Schedule Permissible Exposure Limits of Toxic Substances.

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
ACGIH / C : Ceiling limit
SG OEL / PEL (long term) : Permissible Exposure Level (PEL) Long Term
SG OEL / PEL (short term) : Permissible Exposure Level (PEL) Short Term

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recom-

SAFETY DATA SHEET



Capstone™ FS-93

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
2.1	23.07.2024	6525499-00010	Date of first issue: 02.10.2020

recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

SG / EN