

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HCFC-22

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 12/11/2023  |
| 5.15    | 03/05/2025     | 1332012-00046 | Date of first issue: 02/27/2017 |

### SECTION 1. IDENTIFICATION

Product name : HCFC-22

SDS-Identcode : 130000030957

Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Canada Company

Address : 151 Bloor Street West - 12th Floor  
Toronto, ON M5S 1S4 Canada

Telephone : 1-844-773-CHEM (2436)

Emergency telephone : 1-866-595-1473 (24 hours)

#### Recommended use of the chemical and restrictions on use

Recommended use : Transported isolated intermediate used under strictly controlled conditions.  
Manufacture of chemical products  
Packaging  
(Re)packing of substances and mixtures

Restrictions on use : For professional and industrial installation and use only.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Gases under pressure : Liquefied gas

Simple Asphyxiant : Category 1

#### GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H280 Contains gas under pressure; may explode if heated.  
May displace oxygen and cause rapid suffocation.

Precautionary Statements : **Storage:**  
P410 + P403 Protect from sunlight. Store in a well-ventilated

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HCFC-22

Version 5.15      Revision Date: 03/05/2025      SDS Number: 1332012-00046      Date of last issue: 12/11/2023  
Date of first issue: 02/27/2017

place.

### Other hazards

Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Substance name : Chlorodifluoromethane

CAS-No. : 75-45-6

Common Name/Synonym : No data available

### Components

| Chemical name         | Common Name/Synonym | CAS-No. | Concentration (% w/w)  |
|-----------------------|---------------------|---------|------------------------|
| Chlorodifluoromethane | No data available   | 75-45-6 | $\geq 99.8 - \leq 100$ |

### SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
If not breathing, give artificial respiration.  
If breathing is difficult, give oxygen.  
Get medical attention immediately.

In case of skin contact : Thaw frosted parts with lukewarm water. Do not rub affected area.  
Get medical attention immediately.

In case of eye contact : Get medical attention immediately.

If swallowed : Ingestion is not considered a potential route of exposure.

Most important symptoms and effects, both acute and delayed : May cause cardiac arrhythmia.  
Other symptoms potentially related to misuse or inhalation abuse are  
Cardiac sensitization  
Anaesthetic effects  
Light-headedness  
Dizziness  
confusion

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HCFC-22

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 12/11/2023  |
| 5.15    | 03/05/2025     | 1332012-00046 | Date of first issue: 02/27/2017 |

Lack of coordination  
Drowsiness  
Unconsciousness  
May displace oxygen and cause rapid suffocation.  
Gas reduces oxygen available for breathing.  
Contact with liquid or refrigerated gas can cause cold burns and frostbite.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Not applicable  
Will not burn

Unsuitable extinguishing media : Not applicable  
Will not burn

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fight fire remotely due to the risk of explosion.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Avoid skin contact with leaking liquid (danger of frostbite).  
Ventilate the area.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HCFC-22

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 12/11/2023  |
| 5.15    | 03/05/2025     | 1332012-00046 | Date of first issue: 02/27/2017 |

---

- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.
- Methods and materials for containment and cleaning up : Ventilate the area.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

- Technical measures : Use equipment rated for cylinder pressure. Use a backflow preventative device in piping. Close valve after each use and when empty.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Avoid breathing gas.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Wear cold insulating gloves/ face shield/ eye protection.  
Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point.  
Prevent backflow into the gas tank.  
Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.  
Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems.  
Close valve after each use and when empty. Do NOT change or force fit connections.  
Prevent the intrusion of water into the gas tank.  
Never attempt to lift cylinder by its cap.  
Do not drag, slide or roll cylinders.  
Use a suitable hand truck for cylinder movement.  
Keep away from heat and sources of ignition.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Cylinders should be stored upright and firmly secured to prevent falling or being knocked over.  
Separate full containers from empty containers.  
Do not store near combustible materials.  
Avoid area where salt or other corrosive materials are present.  
Keep in properly labeled containers.  
Keep in a cool, well-ventilated place.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HCFC-22

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 12/11/2023  |
| 5.15    | 03/05/2025     | 1332012-00046 | Date of first issue: 02/27/2017 |

Keep away from direct sunlight.  
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable liquids  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Very acutely toxic substances and mixtures  
Acutely toxic substances and mixtures  
Substances and mixtures with chronic toxicity

Recommended storage temperature : < 52 °C

Storage period : > 10 y

Further information on storage stability : The product has an indefinite shelf life when stored properly.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

| Components            | CAS-No. | Value type<br>(Form of exposure) | Control parameters / Permissible concentration | Basis     |
|-----------------------|---------|----------------------------------|--|-----------|
| Chlorodifluoromethane | 75-45-6 | TWA                              | 1,000 ppm<br>3,500 mg/m <sup>3</sup>           | CA AB OEL |
|                       |         | TWA                              | 500 ppm  | CA BC OEL |
|                       |         | STEL                             | 1,250 ppm                                      | CA BC OEL |
|                       |         | TWAEV                            | 1,000 ppm<br>3,540 mg/m <sup>3</sup>           | CA QC OEL |
|                       |         | TWA                              | 1,000 ppm                                      | ACGIH     |

**Engineering measures** : Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

### Personal protective equipment

Respiratory protection : Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown.

Hand protection  
Material : Heat resistant gloves

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HCFC-22

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 12/11/2023  |
| 5.15    | 03/05/2025     | 1332012-00046 | Date of first issue: 02/27/2017 |

- |                          |   |
|--------------------------|---|
| Remarks                  | : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often! |
| Eye protection           | : Wear the following personal protective equipment:<br>Chemical resistant goggles must be worn.<br>Face-shield  |
| Skin and body protection | : Skin should be washed after contact.  |
| Protective measures      | : Wear cold insulating gloves/ face shield/ eye protection.   |
| Hygiene measures         | : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.<br>When using do not eat, drink or smoke.<br>Wash contaminated clothing before re-use.  |

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- |   |                           |
|---|---------------------------|
| Appearance                              | : Liquefied gas           |
| Color                                   | : colorless               |
| Odor                                    | : odorless, slight, sweet |
| Odor Threshold                          | : No data available       |
| pH                                      | : No data available       |
| Melting point/freezing point            | : -160 °C                 |
| Initial boiling point and boiling range | : -40.8 °C<br>(1,013 hPa) |
| Flash point                             | : Not applicable          |
| Evaporation rate                        | : > 1<br>(CCL4=1.0)       |
| Flammability (solid, gas)               | : Will not burn           |

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HCFC-22

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 12/11/2023  |
| 5.15    | 03/05/2025     | 1332012-00046 | Date of first issue: 02/27/2017 |

|  |   |   |
|--|---|---|
| Self-ignition                                    | : | The substance or mixture is not classified as pyrophoric. |
| Upper explosion limit / Upper flammability limit | : | Upper flammability limit<br>Method: ASTM E681<br>None.    |
| Lower explosion limit / Lower flammability limit | : | Lower flammability limit<br>Method: ASTM E681<br>None.    |
| Vapor pressure                                   | : | 9,135 hPa (20 °C)   |
| Relative vapor density                           | : | 3   |
| Relative density                                 | : | 1.19 (25 °C)  |
| Density  | : | 1.191 g/cm <sup>3</sup> (25 °C)<br>(as liquid)            |
| Solubility(ies)<br>Water solubility              | : | 2.6 g/l (25 °C)   |
| Partition coefficient: n-octanol/water           | : | log Pow: 1.13 (25 °C)                                     |
| Autoignition temperature                         | : | 632 - 635 °C  |
| Decomposition temperature                        | : | 632 °C  |
| Viscosity<br>Viscosity, dynamic                  | : | 0.22 mPa.s (10 °C)  |
| Viscosity, kinematic                             | : | Not applicable  |
| Explosive properties                             | : | Not explosive   |
| Oxidizing properties                             | : | The substance or mixture is not classified as oxidizing.  |
| Particle characteristics<br>Particle size        | : | Not applicable  |

### SECTION 10. STABILITY AND REACTIVITY

|                                    |   |  |
|------------------------------------|---|--|
| Reactivity                         | : | Not classified as a reactivity hazard.   |
| Chemical stability                 | : | Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions. |
| Possibility of hazardous reactions | : | Can react with strong oxidizing agents.  |
| Conditions to avoid                | : | This substance is not flammable in air at temperatures up to   |

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HCFC-22

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 12/11/2023  |
| 5.15    | 03/05/2025     | 1332012-00046 | Date of first issue: 02/27/2017 |

100 °C (212 °F) at atmospheric pressure. However, mixtures of this substance with high concentrations of air at elevated pressure and/or temperature can become combustible in the presence of an ignition source. This substance can also become combustible in an oxygen enriched environment (oxygen concentrations greater than that in air). Whether a mixture containing this substance and air, or this substance in an oxygen enriched atmosphere become combustible depends on the inter-relationship of 1) the temperature 2) the pressure, and 3) the proportion of oxygen in the mixture. In general, this substance should not be allowed to exist with air above atmospheric pressure or at high temperatures; or in an oxygen enriched environment. For example this substance should NOT be mixed with air under pressure for leak testing or other purposes.  
Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation  
Skin contact  
Eye contact

### Acute toxicity

Not classified based on available information.

### Components:

#### Chlorodifluoromethane:

Acute inhalation toxicity : LC50 (Mouse): > 150000 ppm  
Exposure time: 4 h  
Test atmosphere: gas  
Method: Expert judgment

No observed adverse effect concentration (Dog): 25000 ppm  
Test atmosphere: gas

Lowest observed adverse effect concentration (Dog): 50000 ppm  
Test atmosphere: gas

Cardiac sensitisation threshold limit (Dog): 175,000 mg/m<sup>3</sup>  
Test atmosphere: gas

### Skin corrosion/irritation

Not classified based on available information.



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HCFC-22

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 12/11/2023  |
| 5.15    | 03/05/2025     | 1332012-00046 | Date of first issue: 02/27/2017 |

---

### Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Chlorodifluoromethane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: positive

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

### Carcinogenicity

Not classified based on available information.

### Components:

#### Chlorodifluoromethane:

Species : Mouse  
Application Route : inhalation (gas)  
Exposure time : 581 days  
Result : negative  
Remarks : The mechanism or mode of action is not relevant in humans.

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

### Reproductive toxicity

Not classified based on available information.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HCFC-22

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 12/11/2023  |
| 5.15    | 03/05/2025     | 1332012-00046 | Date of first issue: 02/27/2017 |

---

### Components:

#### **Chlorodifluoromethane:**

|                                    |   |   |
|------------------------------------|---|---|
| Effects on fertility               | : | Species: Mouse<br>Application Route: Inhalation<br>Result: negative   |
| Effects on fetal development       | : | Test Type: Prenatal development toxicity study (teratogenicity)<br>Species: Rat<br>Application Route: Inhalation<br>Method: OECD Test Guideline 414<br>Result: negative |
| Reproductive toxicity - Assessment | : | Weight of evidence does not support classification for reproductive toxicity  |

#### **STOT-single exposure**

May displace oxygen and cause rapid suffocation.

### Components:

#### **Chlorodifluoromethane:**

|                    |   |  |
|--------------------|---|--|
| Routes of exposure | : | inhalation (gas)   |
| Assessment         | : | No significant health effects observed in animals at concentrations of 20000 ppmV/4h or less |

#### **STOT-repeated exposure**

Not classified based on available information.

### Components:

#### **Chlorodifluoromethane:**

|                    |   |   |
|--------------------|---|---|
| Routes of exposure | : | inhalation (gas)  |
| Assessment         | : | No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less. |

#### **Repeated dose toxicity**

### Components:

#### **Chlorodifluoromethane:**

|                   |   |                        |
|-------------------|---|------------------------|
| Species           | : | Mouse, male and female |
| NOAEL             | : | 10000 ppm              |
| LOAEL             | : | 50000 ppm              |
| Application Route | : | inhalation (gas)       |
| Exposure time     | : | 581 d                  |

#### **Aspiration toxicity**

Not classified based on available information.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HCFC-22

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 12/11/2023  |
| 5.15    | 03/05/2025     | 1332012-00046 | Date of first issue: 02/27/2017 |

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Components:

##### **Chlorodifluoromethane:**

|   |   |   |
|---|---|---|
| Toxicity to fish                                    | : | LC50 (Danio rerio (zebra fish)): 777 mg/l<br>Exposure time: 96 h<br>Method: OECD Test Guideline 203             |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 433 mg/l<br>Exposure time: 48 h<br>Method: OECD Test Guideline 202           |
| Toxicity to algae/aquatic plants                    | : | EC50 (algae): 377.6 mg/l<br>Exposure time: 72 h<br>Method: ECOSAR (Ecological Structure Activity Relationships) |

#### Persistence and degradability

##### Components:

##### **Chlorodifluoromethane:**

|                  |   |  |
|------------------|---|--|
| Biodegradability | : | Result: Not readily biodegradable.<br>Method: OECD Test Guideline 301D |
|------------------|---|--|

#### Bioaccumulative potential

##### Components:

##### **Chlorodifluoromethane:**

|  |   |                       |
|--|---|-----------------------|
| Partition coefficient: n-octanol/water | : | log Pow: 1.13 (25 °C) |
|--|---|-----------------------|

#### Mobility in soil

No data available

#### Other adverse effects

##### Components:

##### **Chlorodifluoromethane:**

|                           |   |  |
|---------------------------|---|--|
| Ozone-Depletion Potential | : | 0.055<br>Where a range of ODPs is indicated, the highest value in that range shall be used for the purposes of the Protocol. The ODPs listed as a single value have been determined from calculations based on laboratory measurements. Those listed as a range are based on estimates and are less certain. The range pertains to an isomeric group. The upper value is the estimate of the ODP of the isomer with the highest ODP, and |
|---------------------------|---|--|

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HCFC-22

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 12/11/2023  |
| 5.15    | 03/05/2025     | 1332012-00046 | Date of first issue: 02/27/2017 |

the lower value is the estimate of the ODP of the isomer with the lowest ODP.

Regulation: UNEP - Handbook for the Montreal Protocol on Substances that Deplete the Ozone Layer (Update: 2016-11-23)

Group: Annex C - Group I: HCFCs (consumption and production)

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty pressure vessels should be returned to the supplier.  
If not otherwise specified: Dispose of as unused product.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

UN number : UN 1018  
Proper shipping name : REFRIGERANT GAS R 22  
Class : 2.2  
Packing group : Not assigned by regulation  
Labels : 2.2  
Environmentally hazardous : no

##### IATA-DGR

UN/ID No. : UN 1018  
Proper shipping name : Refrigerant gas R 22  
Class : 2.2  
Packing group : Not assigned by regulation  
Labels : Non-flammable, non-toxic Gas  
Packing instruction (cargo aircraft) : 200  
Packing instruction (passenger aircraft) : 200

##### IMDG-Code

UN number : UN 1018  
Proper shipping name : REFRIGERANT GAS R 22  
  
Class : 2.2  
Packing group : Not assigned by regulation  
Labels : 2.2  
EmS Code : F-C, S-V  
Marine pollutant : no

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HCFC-22

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 12/11/2023  |
| 5.15    | 03/05/2025     | 1332012-00046 | Date of first issue: 02/27/2017 |

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### TDG

UN number : UN 1018  
Proper shipping name : REFRIGERANT GAS R 22

Class : 2.2  
Packing group : Not assigned by regulation  
Labels : 2.2  
ERG Code : 126  
Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### International Regulations

Montreal Protocol : Chlorodifluoromethane

## SECTION 16. OTHER INFORMATION

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.  
Before use read Chemours safety information.  
For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)  
CA BC OEL : Canada. British Columbia OEL  
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants  
ACGIH / TWA : 8-hour, time-weighted average  
CA AB OEL / TWA : 8-hour Occupational exposure limit  
CA BC OEL / TWA : 8-hour time weighted average  
CA BC OEL / STEL : short-term exposure limit  
CA QC OEL / TWAEV : Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule;

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## HCFC-22

|         |                |               |                                 |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number:   | Date of last issue: 12/11/2023  |
| 5.15    | 03/05/2025     | 1332012-00046 | Date of first issue: 02/27/2017 |

ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 03/05/2025  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8