

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/01/08
5.1	2024/05/29	1334688-00048	Date of first issue: 2017/02/27

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Capstone™ FS-50 Fluorosurfactant

SDS-Identcode : 130000042667

Manufacturer or supplier's details

Company : Chemours Vietnam Co., Ltd.

Address : Level 7, Friendship Tower, 31 Le Duan Street, Ben Nghe Ward,
District 1
Ho Chi Minh City Vietnam

Telephone : (84 8) 6288 3964

Emergency telephone number : 1800-577-721

Recommended use of the chemical and restrictions on use

Recommended use : Fluoroadditive

Restrictions on use : For industrial use only.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms :



SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/01/08
5.1	2024/05/29	1334688-00048	Date of first issue: 2017/02/27

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P391 Collect spillage.

Storage:
P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Inhalation of decomposition products in high concentration may cause shortness of breath (lung oedema).
Vapours may form explosive mixture with air.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Ethanol	64-17-5	>= 30 -< 40
Carboxymethyldimethyl-3- [[[(3,3,4,4,5,5,6,6,7,7,8,8,8- tridecafluoroooc- tyl)sulphonyl]amino]propylammonium hydroxide	34455-29-3	>= 25 -< 30

4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version 5.1	Revision Date: 2024/05/29	SDS Number: 1334688-00048	Date of last issue: 2024/01/08 Date of first issue: 2017/02/27
----------------	------------------------------	------------------------------	---

In case of skin contact	: Remove contaminated clothing and shoes.
In case of eye contact	: Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	: Dizziness Blurred vision Headache Irritation Nausea Pain Lachrymation Vomiting Eye contact may provoke the following symptoms tearing Swelling of tissue Redness Impairment of vision
Protection of first-aiders	: No special precautions are necessary for first aid responders.
Notes to physician	: Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Water spray Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire-fighting	: Do not use a solid water stream as it may scatter and spread fire. Flash back possible over considerable distance. Vapours may form explosive mixtures with air. Exposure to combustion products may be a hazard to health.
Hazardous combustion products	: Carbon oxides Hydrogen fluoride carbonyl fluoride potentially toxic fluorinated compounds aerosolized particulates
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version 5.1	Revision Date: 2024/05/29	SDS Number: 1334688-00048	Date of last issue: 2024/01/08 Date of first issue: 2017/02/27
----------------	------------------------------	------------------------------	---

Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue:
5.1	2024/05/29	1334688-00048	2024/01/08
			Date of first issue: 2017/02/27

practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labelled containers.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable gases
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Poisonous gases
Explosives

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1.000 mg/m3	VN OEL
	Further information: Group 1: Carcinogenic to humans			
		STEL	3.000 mg/m3	VN OEL
	Further information: Group 1: Carcinogenic to humans			
		STEL	1.000 ppm	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
hydrofluoric acid	7664-39-3	TWA	0,1 mg/m3	VN OEL
		STEL	0,5 mg/m3	VN OEL
		TWA	0,5 ppm	ACGIH

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version 5.1 Revision Date: 2024/05/29 SDS Number: 1334688-00048 Date of last issue: 2024/01/08
Date of first issue: 2017/02/27

			(Fluorine)	
		C	2 ppm (Fluorine)	ACGIH
Carbonyl difluoride	353-50-4	TWA	5 mg/m3	VN OEL
		STEL	13 mg/m3	VN OEL
		TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
Carbon dioxide	124-38-9	TWA	9.000 mg/m3	VN OEL
		STEL	18.000 mg/m3	VN OEL
		TWA	5.000 ppm	ACGIH
		STEL	30.000 ppm	ACGIH
Carbon monoxide	630-08-0	TWA	20 mg/m3	VN OEL
		STEL	40 mg/m3	VN OEL
		TWA	25 ppm	ACGIH

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates, acidic gas/vapour and organic vapour type

Hand protection

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version 5.1	Revision Date: 2024/05/29	SDS Number: 1334688-00048	Date of last issue: 2024/01/08 Date of first issue: 2017/02/27
----------------	------------------------------	------------------------------	---

atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: clear, amber
Odour	: alcohol-like
Odour Threshold	: No data available
pH	: 5 - 7
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: 82 °C
Flash point	: 25 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: 53 hPa (20 °C)
Relative vapour density	: No data available

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version 5.1	Revision Date: 2024/05/29	SDS Number: 1334688-00048	Date of last issue: 2024/01/08 Date of first issue: 2017/02/27
----------------	------------------------------	------------------------------	---

Relative density	:	1
Solubility(ies) Water solubility	:	completely soluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	> 100 °C
Decomposition temperature	:	> 200 °C
Viscosity Viscosity, kinematic	:	9,7 mm ² /s (20 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	:	Not applicable

10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Flammable liquid and vapour. Vapours may form explosive mixture with air. Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents

Hazardous decomposition products

Thermal decomposition	:	hydrofluoric acid Carbonyl difluoride Carbon dioxide Carbon monoxide
-----------------------	---	---

11. TOXICOLOGICAL INFORMATION

Exposure routes	:	Inhalation Skin contact
-----------------	---	----------------------------

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/01/08
5.1	2024/05/29	1334688-00048	Date of first issue: 2017/02/27

Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Ethanol:

Acute oral toxicity : LD50 (Rat): 10.470 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male): 116,9 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 15.800 mg/kg

Carboxymethyldimethyl-3-[[[3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 425
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Ethanol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Carboxymethyldimethyl-3-[[[3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/01/08
5.1	2024/05/29	1334688-00048	Date of first issue: 2017/02/27

Components:

Ethanol:

Species	: Rabbit
Result	: Irritation to eyes, reversing within 21 days
Method	: OECD Test Guideline 405

Carboxymethyldimethyl-3-[[[(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Ethanol:

Test Type	: Mouse ear swelling test (MEST)
Exposure routes	: Skin contact
Species	: Mouse
Result	: negative

Carboxymethyldimethyl-3-[[[(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide:

Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Ethanol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES)
	Method: OECD Test Guideline 471
	Result: negative

	Test Type: In vitro mammalian cell gene mutation test
	Method: OECD Test Guideline 476
	Result: negative

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/01/08
5.1	2024/05/29	1334688-00048	Date of first issue: 2017/02/27

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Result: negative

Carboxymethyldimethyl-3-[[[(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide:

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

Ethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

Carboxymethyldimethyl-3-[[[(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Ethanol:

Species : Rat
NOAEL : 1.730 mg/kg
LOAEL : 3.200 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/01/08
5.1	2024/05/29	1334688-00048	Date of first issue: 2017/02/27

Carboxymethyldimethyl-3-[[[(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide:

Species	: Rat
NOAEL	: 200 mg/kg
LOAEL	: 1.000 mg/kg
Application Route	: Ingestion
Exposure time	: 28 d

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Ethanol:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 14.200 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Ceriodaphnia dubia (water flea)): 5.012 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	: ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Exposure time: 72 h EC10 (Chlorella vulgaris (Fresh water algae)): 11,5 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC (Oryzias latipes (Japanese medaka)): >= 79 mg/l Exposure time: 100 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 9,6 mg/l Exposure time: 9 d
Toxicity to microorganisms	: EC50 (Protozoa): 5.800 mg/l Exposure time: 4 h

Carboxymethyldimethyl-3-[[[(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide:

Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 144 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (green algae)): 3,26 mg/l

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/01/08
5.1	2024/05/29	1334688-00048	Date of first issue: 2017/02/27

Exposure time: 72 h
Method: OECD Test Guideline 201

Persistence and degradability

Components:

Ethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 84 %
Exposure time: 20 d

Carboxymethyldimethyl-3-[[[(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide:

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301

Bioaccumulative potential

Components:

Ethanol:

Partition coefficient: n-octanol/water : log Pow: -0,35

Carboxymethyldimethyl-3-[[[(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide:

Partition coefficient: n-octanol/water : log Pow: 1

Mobility in soil

No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/01/08
5.1	2024/05/29	1334688-00048	Date of first issue: 2017/02/27

If not otherwise specified: Dispose of as unused product.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number	: UN 1170
Proper shipping name	: ETHANOL SOLUTION
Class	: 3
Packing group	: III
Labels	: 3
Environmentally hazardous	: yes

IATA-DGR

UN/ID No.	: UN 1170
Proper shipping name	: Ethanol solution
Class	: 3
Packing group	: III
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 366
Packing instruction (passenger aircraft)	: 355

IMDG-Code

UN number	: UN 1170
Proper shipping name	: ETHANOL SOLUTION (Carboxymethyldimethyl-3-[[[(3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl)sulphonyl]amino]propylammonium hydroxide])
Class	: 3
Packing group	: III
Labels	: 3
EmS Code	: F-E, S-D
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Law on Chemicals No. 06/2007/QH12

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue:
5.1	2024/05/29	1334688-00048	2024/01/08
			Date of first issue: 2017/02/27

16. OTHER INFORMATION

Revision Date : 2024/05/29

Other information : Capstone™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.
Chemours™ and the Chemours Logo are trademarks of The Chemours Company.
Before use read Chemours safety information.
For further information contact the local Chemours office or nominated distributors.

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
VN OEL : Vietnam. Occupational Exposure Limits

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
ACGIH / C : Ceiling limit
VN OEL / TWA : Time weighted average
VN OEL / STEL : Short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances

SAFETY DATA SHEET



Capstone™ FS-50 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/01/08
5.1	2024/05/29	1334688-00048	Date of first issue: 2017/02/27

es; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

VN / EN