

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

### SECTION 1. IDENTIFICATION

Product name : Nafion™ PFSA 20% Dispersions - D2021CS

SDS-Identcode : 130000034156

Other means of identification : Nafion™ PFSA 20% Dispersions - D2021

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Intermediate

Restrictions on use : For industrial use only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2

Serious eye damage : Category 1

Specific target organ toxicity : Category 3  
- single exposure

#### GHS label elements

Hazard pictograms :



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.  
H318 Causes serious eye damage.  
H336 May cause drowsiness or dizziness.

Precautionary Statements : **Prevention:**  
P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P241 Use explosion-proof electrical, ventilating and lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing mist or vapors.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, eye protection and face protection.

**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER.

**Storage:**  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**  
P501 Dispose of contents and container to an approved waste disposal plant.

### Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.  
Vapors may form explosive mixture with air.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Propan-1-ol	71-23-8	>= 30 - < 50
Ethanol	64-17-5	>= 1 - < 5

Actual concentration is withheld as a trade secret

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

### SECTION 4. FIRST AID MEASURES

- |   |   |
|---|---|
| General advice  | : In the case of accident or if you feel unwell, seek medical advice immediately.<br>When symptoms persist or in all cases of doubt seek medical advice.  |
| If inhaled  | : If inhaled, remove to fresh air.<br>Get medical attention if symptoms occur.  |
| In case of skin contact                                     | : In case of contact, immediately flush skin with plenty of water.<br>Remove contaminated clothing and shoes.<br>Get medical attention if symptoms occur.   |
| In case of eye contact                                      | : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.<br>If easy to do, remove contact lens, if worn.<br>Get medical attention immediately.  |
| If swallowed  | : If swallowed, DO NOT induce vomiting.<br>If vomiting occurs have person lean forward.<br>Call a physician or poison control center immediately.<br>Rinse mouth thoroughly with water.<br>Never give anything by mouth to an unconscious person.   |
| Most important symptoms and effects, both acute and delayed | : Effects of breathing high concentrations of vapor may include:<br>Central nervous system depression<br>Dizziness<br>confusion<br>Lack of coordination<br>Drowsiness<br>Unconsciousness<br>narcosis<br>Repeated exposure may cause skin dryness or cracking.<br>Ingestion may provoke the following symptoms:<br>Vomiting<br>Eye contact may provoke the following symptoms<br>Irritation<br>Pain<br>tearing<br>Swelling of tissue<br>Redness<br>Impairment of vision<br>Lung damage<br>Causes serious eye damage.<br>May cause drowsiness or dizziness. |
| Protection of first-aiders                                  | : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).   |
| Notes to physician  | : Treat symptomatically and supportively.   |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Ventilate the area.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Avoid breathing mist or vapors.  
Do not swallow.  
Do not get in eyes.  
Avoid prolonged or repeated contact with skin.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Non-sparking tools should be used.  
Keep container tightly closed.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.  
  
Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Self-reactive substances and mixtures

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version 7.4      Revision Date: 10/18/2024      SDS Number: 1334141-00048      Date of last issue: 05/30/2024  
Date of first issue: 02/27/2017

Organic peroxides  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases  
Very acutely toxic substances and mixtures

Recommended storage temperature : 32 - 90 °F / 0 - 32 °C

Further information on storage stability : Do not freeze.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propan-1-ol	71-23-8	TWA	100 ppm	ACGIH
		TWA	200 ppm 500 mg/m <sup>3</sup>	NIOSH REL
		ST	250 ppm 625 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm 500 mg/m <sup>3</sup>	OSHA Z-1
Ethanol	64-17-5	STEL	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m <sup>3</sup>	OSHA Z-1

#### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		C	6 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3 ppm 2.5 mg/m <sup>3</sup>	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version 7.4      Revision Date: 10/18/2024      SDS Number: 1334141-00048      Date of last issue: 05/30/2024  
Date of first issue: 02/27/2017

		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		ST	5 ppm 15 mg/m <sup>3</sup>	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NIOSH REL
		ST	30,000 ppm 54,000 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m <sup>3</sup>	NIOSH REL
		C	200 ppm 229 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 55 mg/m <sup>3</sup>	OSHA Z-1

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

### Personal protective equipment

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Hand protection

Material : butyl-rubber  
Glove thickness : 16 - 32 mm

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

- Eye protection : Wear the following personal protective equipment: Chemical resistant goggles must be worn. If splashes are likely to occur, wear: Face-shield
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : clear, colorless, light yellow
- Odor : alcohol-like
- Odor Threshold : No data available
- pH : 2
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available
- Flash point : 64 °F / 18 °C

Method: Pensky-Martens closed cup



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	1.01 - 1.03 g/cm <sup>3</sup>
Solubility(ies) Water solubility	:	dispersible
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	50 - 500 mPa.s (77 °F / 25 °C)
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	:	Not applicable

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Highly flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

### Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

### Acute toxicity

Not classified based on available information.

### Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

### Components:

#### Propan-1-ol:

Acute oral toxicity : LD50 (Rabbit): 2,823 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 33.8 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): 4,032 mg/kg

#### Ethanol:

Acute oral toxicity : LD50 (Rat): 10,470 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male): 116.9 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 15,800 mg/kg

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

---

### Skin corrosion/irritation

Not classified based on available information.

#### Product:

Exposure time	:	1 h
Method	:	In Vitro Membrane Barrier Test Method for Skin Corrosion - CORROSITEX
Result	:	No skin irritation

#### Components:

##### Propan-1-ol:

Species	:	Rabbit
Result	:	No skin irritation

##### Ethanol:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation

### Serious eye damage/eye irritation

Causes serious eye damage.

#### Components:

##### Propan-1-ol:

Species	:	Rabbit
Result	:	Irreversible effects on the eye

##### Ethanol:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Method	:	OECD Test Guideline 405

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

#### Components:

##### Propan-1-ol:

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

---

### Ethanol:

Test Type	: Mouse ear swelling test (MEST)
Routes of exposure	: Skin contact
Species	: Mouse
Result	: negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Propan-1-ol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
	Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative

### Ethanol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
	Test Type: Chromosome aberration test in vitro Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Ingestion Result: negative

### Carcinogenicity

Not classified based on available information.

**IARC** No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No ingredient of this product present at levels greater than or equal to 0.1% is

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

---

identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Not classified based on available information.

#### Components:

##### Ethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Mouse  
Application Route: Ingestion  
Result: negative

### STOT-single exposure

May cause drowsiness or dizziness.

#### Components:

##### Propan-1-ol:

Assessment : May cause drowsiness or dizziness.

### STOT-repeated exposure

Not classified based on available information.

### Repeated dose toxicity

#### Components:

##### Propan-1-ol:

Species : Rat  
NOAEL : > 8 mg/l  
Application Route : inhalation (vapor)  
Method : OECD Test Guideline 413

##### Ethanol:

Species : Rat  
NOAEL : 1,730 mg/kg  
LOAEL : 3,200 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

### Aspiration toxicity

Not classified based on available information.

#### Components:

##### Propan-1-ol:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Components:

##### **Propan-1-ol:**

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 4,555 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 3,644 mg/l Exposure time: 48 h Method: DIN 38412
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 9,170 mg/l Exposure time: 48 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 21 d

##### **Ethanol:**

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 14,200 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Ceriodaphnia dubia (water flea)): 5,012 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Exposure time: 72 h  EC10 (Chlorella vulgaris (Fresh water algae)): 11.5 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC (Oryzias latipes (Japanese medaka)): >= 79 mg/l Exposure time: 100 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 9.6 mg/l Exposure time: 9 d
Toxicity to microorganisms	:	EC50 (Protozoa): 5,800 mg/l Exposure time: 4 h

#### Persistence and degradability

##### Components:

##### **Propan-1-ol:**

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 75 %
------------------	---	--

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

Exposure time: 20 d

### Ethanol:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 84 %  
Exposure time: 20 d

### Bioaccumulative potential

#### Components:

#### Propan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 0.2

#### Ethanol:

Partition coefficient: n-octanol/water : log Pow: -0.35

### Mobility in soil

No data available

### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Propan-1-ol, Ethanol)  
Class : 3  
Packing group : II  
Labels : 3

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

Environmentally hazardous : no

### IATA-DGR

UN/ID No. : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(Propan-1-ol, Ethanol)  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

### IMDG-Code

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Propan-1-ol, Ethanol)  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 1993  
Proper shipping name : Flammable liquids, n.o.s.  
(Propan-1-ol, Ethanol)  
Class : 3  
Packing group : II  
Labels : FLAMMABLE LIQUID  
ERG Code : 128  
Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.



# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Serious eye damage or eye irritation  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### US State Regulations

#### Pennsylvania Right To Know

Propan-1-ol	71-23-8
Water	7732-18-5
Perfluorosulfonic acid polymer	Trade secret
Ethanol	64-17-5
Propan-2-ol	67-63-0

#### California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.

#### California List of Hazardous Substances

Propan-1-ol	71-23-8
Ethanol	64-17-5

#### California Permissible Exposure Limits for Chemical Contaminants

Propan-1-ol	71-23-8
Ethanol	64-17-5

## SECTION 16. OTHER INFORMATION

### Further information

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS


Version  
7.4

Revision Date:  
10/18/2024

SDS Number:  
1334141-00048

Date of last issue: 05/30/2024  
Date of first issue: 02/27/2017

### NFPA 704:



### HMIS® IV:

HEALTH	/	3
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "/" represents a chronic hazard, while the "0" represents the absence of a chronic hazard.

Nafion™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized Sys-

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Nafion™ PFSA 20% Dispersions - D2021CS

Version	Revision Date:	SDS Number:	Date of last issue: 05/30/2024
7.4	10/18/2024	1334141-00048	Date of first issue: 02/27/2017

tem; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/18/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8