

# SAFETY DATA SHEET



## Opteon™ XL41 (R-454B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2024
6.0	05.03.2025	7729373-00015	Date of first issue: 13.01.2021

---

### SECTION 1: IDENTIFICATION

Product name : Opteon™ XL41 (R-454B) Refrigerant

SDS-Identcode : 130000143545

#### Manufacturer or supplier's details

Company : The Chemours Company (Australia) Pty Ltd (C/O Ashurst Australia)

Address : Level 26, 181 William Street  
Melbourne VIC 3000 Australia

Telephone : 1300 915 623

Emergency telephone number : Medical emergency: 1800 674 415 (24 h) ; Transport emergency: +61 2 9037 2994

#### Recommended use of the chemical and restrictions on use

Recommended use : Refrigerant

Restrictions on use : For professional and industrial installation and use only.  
Do not use product for anything outside of the above specified uses

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable gases : Category 1B

Gases under pressure : Liquefied gas

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H221 Flammable gas.  
H280 Contains gas under pressure; may explode if heated.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

# SAFETY DATA SHEET



## Opteon™ XL41 (R-454B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue:
6.0	05.03.2025	7729373-00015	11.06.2024
			Date of first issue: 13.01.2021

### Response:

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources.

### Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

### Other hazards which do not result in classification

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

May displace oxygen and cause rapid suffocation.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Difluoromethane#	75-10-5	68.9
2,3,3,3-Tetrafluoropropene#	754-12-1	30.9445

# Voluntarily-disclosed substance

## SECTION 4. FIRST AID MEASURES

- |   |   |
|---|---|
| General advice  | : In the case of accident or if you feel unwell, seek medical advice immediately.<br>When symptoms persist or in all cases of doubt seek medical advice.              |
| If inhaled  | : If inhaled, remove to fresh air.<br>If not breathing, give artificial respiration.<br>If breathing is difficult, give oxygen.<br>Get medical attention immediately. |
| In case of skin contact                                     | : Thaw frosted parts with lukewarm water. Do not rub affected area.<br>Get medical attention immediately.   |
| In case of eye contact                                      | : Get medical attention immediately.  |
| If swallowed  | : Ingestion is not considered a potential route of exposure.  |
| Most important symptoms and effects, both acute and delayed | : May cause cardiac arrhythmia.<br>Other symptoms potentially related to misuse or inhalation abuse are   |

# SAFETY DATA SHEET



## Opteon™ XL41 (R-454B) Refrigerant

Version 6.0	Revision Date: 05.03.2025	SDS Number: 7729373-00015	Date of last issue: 11.06.2024 Date of first issue: 13.01.2021
----------------	------------------------------	------------------------------	---

---

Cardiac sensitisation  
Anaesthetic effects  
Light-headedness  
Dizziness  
confusion  
Lack of coordination  
Drowsiness  
Unconsciousness  
Gas reduces oxygen available for breathing.  
Contact with liquid or refrigerated gas can cause cold burns and frostbite.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

---

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.


Specific hazards during fire-fighting : Vapours may form flammable mixture with air  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Hydrogen fluoride  
carbonyl fluoride  
Carbon oxides  
Fluorine compounds

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fight fire remotely due to the risk of explosion.  
Use water spray to cool unopened containers.  
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment : Wear self-contained breathing apparatus for firefighting if nec-

## Opteon™ XL41 (R-454B) Refrigerant



for firefighters      essary.  
Use personal protective equipment.

Hazchem Code : 2YE

Personal precautions, protective equipment and emergency procedures	:	<p>Evacuate personnel to safe areas.</p> <p>Only trained personnel should re-enter the area.</p> <p>Remove all sources of ignition.</p> <p>Avoid skin contact with leaking liquid (danger of frostbite).</p> <p>Ventilate the area.</p> <p>Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).</p>
Environmental precautions	:	<p>Avoid release to the environment.</p> <p>Prevent further leakage or spillage if safe to do so.</p> <p>Retain and dispose of contaminated wash water.</p>
Methods and materials for containment and cleaning up	:	<p>Ventilate the area.</p> <p>Non-sparking tools should be used.</p> <p>Suppress (knock down) gases/vapours/mists with a water spray jet.</p> <p>Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.</p> <p>Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.</p>

Technical measures	:	Use equipment rated for cylinder pressure. Use a backflow preventative device in piping. Close valve after each use and when empty.
Local/Total ventilation	:	If sufficient ventilation is unavailable, use with local exhaust ventilation. If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
Advice on safe handling	:	Avoid breathing gas. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment Keep container tightly closed. Wear cold insulating gloves/ face shield/ eye protection.

## Opteon™ XL41 (R-454B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue:
6.0	05.03.2025	7729373-00015	11.06.2024
			Date of first issue: 13.01.2021

---

Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point.  
Prevent backflow into the gas tank.  
Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.  
Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems.  
Close valve after each use and when empty. Do NOT change or force fit connections.  
Prevent the intrusion of water into the gas tank.  
Never attempt to lift cylinder by its cap.  
Do not drag, slide or roll cylinders.  
Use a suitable hand truck for cylinder movement.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.
- Conditions for safe storage : Cylinders should be stored upright and firmly secured to prevent falling or being knocked over.  
Separate full containers from empty containers.  
Do not store near combustible materials.  
Avoid area where salt or other corrosive materials are present.  
Keep in properly labelled containers.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Keep away from direct sunlight.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable liquids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Explosives
- Recommended storage temperature : < 52 °C
- Storage period : > 10 yr

# SAFETY DATA SHEET



## Opteon™ XL41 (R-454B) Refrigerant

Version 6.0	Revision Date: 05.03.2025	SDS Number: 7729373-00015	Date of last issue: 11.06.2024 Date of first issue: 13.01.2021
----------------	------------------------------	------------------------------	---

Further information on storage stability : The product has an indefinite shelf life when stored properly.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

**Engineering measures** : Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

#### Personal protective equipment

**Respiratory protection** : Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown.

**Hand protection**  
**Material** : Impervious gloves

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

**Eye protection** : Wear the following personal protective equipment:  
Chemical resistant goggles must be worn.  
Face-shield

**Skin and body protection** : Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.

**Protective measures** : Wear cold insulating gloves/ face shield/ eye protection.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : Liquefied gas

# SAFETY DATA SHEET



## Opteon™ XL41 (R-454B) Refrigerant

Version 6.0	Revision Date: 05.03.2025	SDS Number: 7729373-00015	Date of last issue: 11.06.2024 Date of first issue: 13.01.2021
----------------	------------------------------	------------------------------	---

---

Colour	: colourless
Odour	: slight, ether-like
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: -50.9 °C
Flash point	: Not applicable
Evaporation rate	: > 1 (CCL4=1.0)
Flammability (solid, gas)	: Flammable
Upper explosion limit / Upper flammability limit	: Upper flammability limit 23.6 %(V) Method: ASTM E681
Lower explosion limit / Lower flammability limit	: Lower flammability limit 11.3 %(V) Method: ASTM E681
Vapour pressure	: 15,856 hPa (25 °C)
Relative vapour density	: 2.2 (Air = 1.0)
Relative density	: 0.98 (25 °C)
Density	: 0.98 g/cm <sup>3</sup> (25 °C) (as liquid)
Solubility(ies) Water solubility	: No data available
Partition coefficient: n-octanol/water	: Not applicable
Auto-ignition temperature	: 496 °C
Decomposition temperature	: No data available

# SAFETY DATA SHEET



## Opteon™ XL41 (R-454B) Refrigerant

Version 6.0	Revision Date: 05.03.2025	SDS Number: 7729373-00015	Date of last issue: 11.06.2024 Date of first issue: 13.01.2021
----------------	------------------------------	------------------------------	---

---

Viscosity	
Viscosity, kinematic	: Not applicable
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Particle characteristics	
Particle size	: Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.
Possibility of hazardous reactions	: Vapours may form flammable mixture with air Can react with strong oxidizing agents. Flammable gas.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Avoid impurities (e.g. rust, dust, ash), risk of decomposition. Incompatible with acids and bases. Incompatible with oxidizing agents. Oxygen Peroxides peroxide compounds Powdered metals
Hazardous decomposition products	: No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

Exposure routes	: Inhalation Skin contact Eye contact
-----------------	---

#### Acute toxicity

Not classified based on available information.

#### Components:

##### Difluoromethane:

Acute oral toxicity	: Assessment: The substance or mixture has no acute oral toxicity
---------------------	---



## Opteon™ XL41 (R-454B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue:
6.0	05.03.2025	7729373-00015	11.06.2024
			Date of first issue: 13.01.2021

Acute inhalation toxicity : LC50 (Rat): > 520000 ppm  
Exposure time: 4 h  
Test atmosphere: gas  
Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 350000 ppm  
Test atmosphere: gas  
Remarks: Cardiac sensitisation

Lowest observed adverse effect concentration (Dog): > 350000 ppm  
Test atmosphere: gas  
Remarks: Cardiac sensitisation

Cardiac sensitisation threshold limit (Dog): > 735,000 mg/m3  
Test atmosphere: gas  
Remarks: Cardiac sensitisation

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity

**2,3,3,3-Tetrafluoropropene:**

Acute inhalation toxicity : LC50 (Rat): > 405800 ppm  
Exposure time: 4 h  
Test atmosphere: gas  
Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 120000 ppm  
Test atmosphere: gas  
Remarks: Cardiac sensitisation

Lowest observed adverse effect concentration (Dog): > 120000 ppm  
Test atmosphere: gas  
Remarks: Cardiac sensitisation

Cardiac sensitisation threshold limit (Dog): > 559,509 mg/m3  
Test atmosphere: gas  
Remarks: Cardiac sensitisation

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****Difluoromethane:**

Result : No skin irritation

**2,3,3,3-Tetrafluoropropene:**

Result : No skin irritation

## Opteon™ XL41 (R-454B) Refrigerant

Version 6.0	Revision Date: 05.03.2025	SDS Number: 7729373-00015	Date of last issue: 11.06.2024 Date of first issue: 13.01.2021
----------------	------------------------------	------------------------------	---

---

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:****Difluoromethane:**

Result	: No eye irritation
--------	---------------------

**2,3,3,3-Tetrafluoropropene:**

Result	: No eye irritation
--------	---------------------

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:****Difluoromethane:**

Exposure routes	: Skin contact
Result	: negative

**2,3,3,3-Tetrafluoropropene:**

Exposure routes	: Skin contact
Result	: negative

**Chronic toxicity****Germ cell mutagenicity**

Not classified based on available information.

**Components:****Difluoromethane:**

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES)
	Method: OECD Test Guideline 471
	Result: negative
	Test Type: Chromosome aberration test in vitro
Genotoxicity in vivo	Method: OECD Test Guideline 473
	Result: negative
	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
	Species: Mouse
Genotoxicity in vivo	Application Route: inhalation (gas)
	Method: OECD Test Guideline 474
	Result: negative

## Opteon™ XL41 (R-454B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue:
6.0	05.03.2025	7729373-00015	11.06.2024
			Date of first issue: 13.01.2021

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

**2,3,3,3-Tetrafluoropropene:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: positive

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

Test Type: In vivo mammalian alkaline comet assay  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 489  
Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

**Carcinogenicity**

Not classified based on available information.

**Components:****2,3,3,3-Tetrafluoropropene:**

Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

**Reproductive toxicity**

Not classified based on available information.

# SAFETY DATA SHEET



## Opteon™ XL41 (R-454B) Refrigerant

Version 6.0	Revision Date: 05.03.2025	SDS Number: 7729373-00015	Date of last issue: 11.06.2024 Date of first issue: 13.01.2021
----------------	------------------------------	------------------------------	---

### Components:

#### **Difluoromethane:**

- |                                    |   |
|------------------------------------|---|
| Effects on fertility               | : Species: Mouse<br>Application Route: Inhalation<br>Result: negative<br>Remarks: Based on data from similar materials  |
| Effects on foetal development      | : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test<br>Species: Rat<br>Application Route: inhalation (gas)<br>Method: OECD Test Guideline 414<br>Result: negative<br><br>Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test<br>Species: Rabbit<br>Application Route: inhalation (gas)<br>Method: OECD Test Guideline 414<br>Result: negative |
| Reproductive toxicity - Assessment | : Weight of evidence does not support classification for reproductive toxicity  |

#### **2,3,3,3-Tetrafluoropropene:**

- |                                    |   |
|------------------------------------|---|
| Effects on fertility               | : Test Type: Two-generation reproduction toxicity study<br>Species: Rat<br>Application Route: inhalation (gas)<br>Method: OECD Test Guideline 416<br>Result: negative           |
| Effects on foetal development      | : Test Type: Prenatal development toxicity study (teratogenicity)<br>Species: Rat<br>Application Route: inhalation (gas)<br>Method: OECD Test Guideline 414<br>Result: negative |
| Reproductive toxicity - Assessment | : Weight of evidence does not support classification for reproductive toxicity, No effects on or via lactation  |

#### **STOT - single exposure**

Not classified based on available information.

### Components:

#### **Difluoromethane:**

- |                 |  |
|-----------------|--|
| Exposure routes | : inhalation (gas)   |
| Assessment      | : No significant health effects observed in animals at concentrations of 20000 ppmV/4h or less |

# SAFETY DATA SHEET



## Opteon™ XL41 (R-454B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2024
6.0	05.03.2025	7729373-00015	Date of first issue: 13.01.2021

---

### 2,3,3,3-Tetrafluoropropene:

Exposure routes	: inhalation (gas)
Assessment	: No significant health effects observed in animals at concentrations of 20000 ppmV/4h or less

### STOT - repeated exposure

Not classified based on available information.

### Components:

#### Difluoromethane:

Exposure routes	: inhalation (gas)
Assessment	: No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

### 2,3,3,3-Tetrafluoropropene:

Exposure routes	: inhalation (gas)
Assessment	: No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

### Repeated dose toxicity

### Components:

#### Difluoromethane:

Species	: Rat, male and female
NOAEL	: 49100 ppm
LOAEL	: > 49100 ppm
Application Route	: inhalation (gas)
Exposure time	: 13 Weeks
Method	: OECD Test Guideline 413

### 2,3,3,3-Tetrafluoropropene:

Species	: Rat, male and female
NOAEL	: 50000 ppm
LOAEL	: >50000 ppm
Application Route	: inhalation (gas)
Exposure time	: 13 Weeks
Method	: OECD Test Guideline 413

### Aspiration toxicity

Not classified based on available information.

### Components:

#### Difluoromethane:

No aspiration toxicity classification

## Opteon™ XL41 (R-454B) Refrigerant

Version  
6.0Revision Date:  
05.03.2025SDS Number:  
7729373-00015Date of last issue: 11.06.2024  
Date of first issue: 13.01.2021**2,3,3,3-Tetrafluoropropene:****||** No aspiration toxicity classification**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Difluoromethane:**

Toxicity to fish	: LC50 (Fish): 1,507 mg/l Exposure time: 96 h Method: ECOSAR (Ecological Structure Activity Relationships)
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia (water flea)): 652 mg/l Exposure time: 48 h Method: ECOSAR (Ecological Structure Activity Relationships)
Toxicity to algae/aquatic plants	: EC50 (green algae): 142 mg/l Exposure time: 96 h Method: ECOSAR (Ecological Structure Activity Relationships)

**2,3,3,3-Tetrafluoropropene:**

Toxicity to fish	: LC50 (Cyprinus carpio (Carp)): > 197 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EC50 (Selenastrum capricornutum (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201  NOEC (Selenastrum capricornutum (green algae)): > 75 mg/l Exposure time: 3 d Method: OECD Test Guideline 201

**Persistence and degradability****Components:****Difluoromethane:**

Biodegradability	: Result: Not readily biodegradable. Method: OECD Test Guideline 301D
------------------	--

# SAFETY DATA SHEET



## Opteon™ XL41 (R-454B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2024
6.0	05.03.2025	7729373-00015	Date of first issue: 13.01.2021

---

### 2,3,3,3-Tetrafluoropropene:

Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 301F

### Bioaccumulative potential

### Components:

#### Difluoromethane:

Partition coefficient: n-octanol/water : log Pow: 0.714

### 2,3,3,3-Tetrafluoropropene:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2 (25 °C)

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty pressure vessels should be returned to the supplier.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 3161  
Proper shipping name : LIQUEFIED GAS, FLAMMABLE, N.O.S.  
(Difluoromethane, 2,3,3,3-Tetrafluoropropene)  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1

# SAFETY DATA SHEET



## Opteon™ XL41 (R-454B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2024
6.0	05.03.2025	7729373-00015	Date of first issue: 13.01.2021

Environmentally hazardous : no

### IATA-DGR

UN/ID No. : UN 3161  
Proper shipping name : Liquefied gas, flammable, n.o.s.  
(Difluoromethane, 2,3,3,3-Tetrafluoropropene)  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 200  
Packing instruction (passenger aircraft) : Not permitted for transport

### IMDG-Code

UN number : UN 3161  
Proper shipping name : LIQUEFIED GAS, FLAMMABLE, N.O.S.  
(Difluoromethane, 2,3,3,3-Tetrafluoropropene)  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### ADG

UN number : UN 3161  
Proper shipping name : LIQUEFIED GAS, FLAMMABLE, N.O.S.  
(Difluoromethane, 2,3,3,3-Tetrafluoropropene)  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
Hazchem Code : 2YE  
Environmentally hazardous : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-



# SAFETY DATA SHEET



## Opteon™ XL41 (R-454B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue:
6.0	05.03.2025	7729373-00015	11.06.2024
			Date of first issue: 13.01.2021

Montreal Protocol : tions.  
: Difluoromethane

### SECTION 16: ANY OTHER RELEVANT INFORMATION

Other information : Opteon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.  
Chemours™ and the Chemours Logo are trademarks of The Chemours Company.  
Before use read Chemours safety information.  
For further information contact the local Chemours office or nominated distributors.

#### Further information

Revision Date : 05.03.2025

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

#### Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances

# SAFETY DATA SHEET



## Opteon™ XL41 (R-454B) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 11.06.2024
6.0	05.03.2025	7729373-00015	Date of first issue: 13.01.2021

---

es; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN