

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

---

### SECTION 1. IDENTIFICATION

Product name : Capstone™ FS-63 Fluorosurfactant

SDS-Identcode : 130000051604

Other means of identification : No data available

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Canada Company

Address : 151 Bloor Street West - 12th Floor  
Toronto, ON M5S 1S4 Canada

Telephone : 1-844-773-CHEM (2436)

Emergency telephone : 1-866-595-1473 (24 hours)

#### Recommended use of the chemical and restrictions on use

Recommended use : Surfactant

Restrictions on use : For industrial use only., Do not use this product in consumer spray applications except in water-based coatings where the maximum concentration of active ingredient does not exceed 0.1 wt percent.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 1

Eye irritation : Category 2A

Specific target organ toxicity : Category 3  
- single exposure

Specific target organ toxicity : Category 2 (Liver)  
- repeated exposure

#### GHS label elements

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version 6.20	Revision Date: 11/25/2024	SDS Number: 1336746-00051	Date of last issue: 05/29/2024 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Hazard pictograms

:



Signal Word

:

Danger

Hazard Statements

:

H226 Flammable liquid and vapor.  
H319 Causes serious eye irritation.  
H330 Fatal if inhaled.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs (Liver) through prolonged or repeated exposure.

Precautionary Statements

:

### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.  
P284 Wear respiratory protection.

### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314 Get medical attention if you feel unwell.  
P337 + P313 If eye irritation persists: Get medical attention.

### Storage:

P405 Store locked up.

### Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

### Other hazards

Inhalation of decomposition products in high concentration may cause shortness of breath (lung edema).  
Vapors may form explosive mixture with air.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

:

Mixture

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version 6.20      Revision Date: 11/25/2024      SDS Number: 1336746-00051      Date of last issue: 05/29/2024  
Date of first issue: 02/27/2017

### Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Partially fluorinated alcohol, reaction products with phosphorus oxide (P <sub>2</sub> O <sub>5</sub> ), ammonium salts	No data available	Not Assigned	$\geq 30 - < 60$ *
Propan-2-ol	Isopropyl alcohol	67-63-0	$\geq 10 - < 30$ *

\* Actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
If not breathing, give artificial respiration.  
If breathing is difficult, give oxygen.  
Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention if symptoms occur.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Inhalation may provoke the following symptoms:  
Respiratory disorder  
Shortness of breath  
Lung edema  
Cough  
Irritation  
Eye contact may provoke the following symptoms  
Lachrymation  
Redness  
Discomfort  
Causes serious eye irritation.  
Fatal if inhaled.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Hydrogen fluoride  
carbonyl fluoride  
potentially toxic fluorinated compounds  
aerosolized particulates  
Carbon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Only trained personnel should re-enter the area.  
Remove all sources of ignition.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Do not breathe mist or vapors.  
Do not swallow.  
Do not get in eyes.  
Avoid prolonged or repeated contact with skin.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Non-sparking tools should be used.  
Keep container tightly closed.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.  
  
Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version 6.20      Revision Date: 11/25/2024      SDS Number: 1336746-00051      Date of last issue: 05/29/2024  
Date of first issue: 02/27/2017

Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Self-reactive substances and mixtures  
Organic peroxides  
Flammable liquids  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives  
Gases  
Very acutely toxic substances and mixtures

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propan-2-ol	67-63-0	STEL	400 ppm 984 mg/m <sup>3</sup>	CA AB OEL
		TWA	200 ppm 492 mg/m <sup>3</sup>	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	200 ppm	CA QC OEL
		STEV	400 ppm	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

#### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm 0.4 mg/m <sup>3</sup> (Fluorine)	CA AB OEL
		(c)	2 ppm 1.6 mg/m <sup>3</sup> (Fluorine)	CA AB OEL
		C	2 ppm (Fluorine)	CA BC OEL
		C	3 ppm 2.6 mg/m <sup>3</sup>	CA QC OEL

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version  
6.20

Revision Date:  
11/25/2024

SDS Number:  
1336746-00051

Date of last issue: 05/29/2024  
Date of first issue: 02/27/2017

			(Fluorine)	
		TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
Carbonyl difluoride	353-50-4	STEL	5 ppm 13 mg/m <sup>3</sup>	CA AB OEL
		TWA	2 ppm 5.4 mg/m <sup>3</sup>	CA AB OEL
		TWA	2 ppm	CA BC OEL
		STEL	5 ppm	CA BC OEL
		STEV	5 ppm 13 mg/m <sup>3</sup>	CA QC OEL
		TWAEV	2 ppm 5.4 mg/m <sup>3</sup>	CA QC OEL
		TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
Carbon dioxide	124-38-9	TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	CA AB OEL
		STEL	30,000 ppm 54,000 mg/m <sup>3</sup>	CA AB OEL
		TWA	5,000 ppm	CA BC OEL
		STEL	15,000 ppm	CA BC OEL
		STEV	30,000 ppm 54,000 mg/m <sup>3</sup>	CA QC OEL
		TWAEV	5,000 ppm 9,000 mg/m <sup>3</sup>	CA QC OEL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
Carbon monoxide	630-08-0	TWA	25 ppm 29 mg/m <sup>3</sup>	CA AB OEL
		TWA	25 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	35 ppm	CA QC OEL
		STEV	175 ppm	CA QC OEL
		TWA	25 ppm	ACGIH

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.  
Use explosion-proof electrical, ventilating and lighting

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

equipment.

### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates, acidic gas/vapor and organic vapor type

#### Hand protection

Material : butyl-rubber  
Break through time : 480 min  
Glove thickness : 0.89 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : clear, colorless, yellow

Odor : alcohol-like



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

---

Odor Threshold : No data available

pH : 7 - 8.5

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : 26 °C  
Method: Pensky-Martens closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : 13.79 hPa (20 °C)  
Solvent

Relative vapor density : No data available

Density : 1.1 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : soluble

Partition coefficient: n-octanol/water : log Pow: 0.35  
(for a component of this mixture)

Autoignition temperature : No data available

Decomposition temperature : > 200 °C

Viscosity  
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

Particle size : Not applicable

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Flammable liquid and vapor.  
Vapors may form explosive mixture with air.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

#### Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Fatal if inhaled.

#### Product:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : Acute toxicity estimate (Rat): 0.005 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgment  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

---

### Components:

#### **Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:**

Acute oral toxicity	:	LD50 (Rat): > 1,000 mg/kg Method: OECD Test Guideline 425 Assessment: The substance or mixture has no acute oral toxicity
Acute inhalation toxicity	:	Approximate Lethal Concentration (Rat): 0.047 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 (Rat): > 1,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

#### **Propan-2-ol:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 25 mg/l Exposure time: 6 h Test atmosphere: vapor
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg

#### **Skin corrosion/irritation**

Not classified based on available information.

### Components:

#### **Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:**

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation

#### **Propan-2-ol:**

Species	:	Rabbit
Result	:	No skin irritation

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### Components:

#### **Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:**

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

---

### Propan-2-ol:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

### Components:

#### Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative

### Propan-2-ol:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
-----------------------	---	---

	:	Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
--	---	---

Germ cell mutagenicity - Assessment	:	Weight of evidence does not support classification as a germ cell mutagen.
-------------------------------------	---	--

### Propan-2-ol:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
-----------------------	---	--

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

---

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

### Carcinogenicity

Not classified based on available information.

#### Components:

##### Propan-2-ol:

Species : Rat  
Application Route : inhalation (vapor)  
Exposure time : 104 weeks  
Method : OECD Test Guideline 451  
Result : negative

### Reproductive toxicity

Not classified based on available information.

#### Components:

##### Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 415  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative  
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

##### Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

---

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

### STOT-single exposure

May cause drowsiness or dizziness.

#### Components:

##### Propan-2-ol:

Assessment : May cause drowsiness or dizziness.

### STOT-repeated exposure

May cause damage to organs (Liver) through prolonged or repeated exposure.

#### Components:

##### Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:

Routes of exposure : Ingestion  
Target Organs : Liver  
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

### Repeated dose toxicity

#### Components:

##### Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:

Species : Rat, male and female  
LOAEL : 3.6 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408  
Remarks : Based on data from similar materials

Species : Rat, male  
NOAEL : 100 mg/kg  
LOAEL : 1,000 mg/kg  
Application Route : Skin contact  
Exposure time : 28 Days  
Method : OECD Test Guideline 410  
Remarks : Based on data from similar materials

##### Propan-2-ol:

Species : Rat  
NOAEL : 12.5 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 104 Weeks

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

### Aspiration toxicity

Not classified based on available information.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### **Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 36.4 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 3.24 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 22.44 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 22.44 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 0.88 mg/l  
Exposure time: 90 d  
Method: OECD Test Guideline 210  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.0093 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

#### **Propan-2-ol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 24 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 1,050 mg/l

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

Exposure time: 16 h

### Persistence and degradability

#### Components:

**Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:**

Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 301D  
Remarks: Based on data from similar materials

#### **Propan-2-ol:**

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1,19 (BOD5)  
COD: 2,23  
BOD/COD: 53 %

### Bioaccumulative potential

#### Components:

**Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
Bioconcentration factor (BCF): 4  
Remarks: Based on data from similar materials

#### **Propan-2-ol:**

Partition coefficient: n-octanol/water : log Pow: 0.05

### Mobility in soil

No data available

### Other adverse effects

#### Components:

**Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts:**

Results of PBT and vPvB assessment : PBT substance

Additional ecological information : Information given is based on data on the ingredients and the ecotoxicology of similar products.



# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Do not dispose of waste into sewer.
- Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
- Empty containers retain residue and can be dangerous.
- Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
- If not otherwise specified: Dispose of as unused product.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

- UN number : UN 1993
- Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Propan-2-ol)
- Class : 3
- Packing group : III
- Labels : 3
- Environmentally hazardous : no

##### IATA-DGR

- UN/ID No. : UN 1993
- Proper shipping name : Flammable liquid, n.o.s.  
(Propan-2-ol)
- Class : 3
- Packing group : III
- Labels : Flammable Liquids
- Packing instruction (cargo aircraft) : 366
- Packing instruction (passenger aircraft) : 355

##### IMDG-Code

- UN number : UN 1993
- Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(Propan-2-ol, Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts)
- Class : 3
- Packing group : III
- Labels : 3
- EmS Code : F-E, S-E
- Marine pollutant : yes

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

### Domestic regulation

#### TDG

UN number	:	UN 1993
Proper shipping name	:	FLAMMABLE LIQUID, N.O.S. (Propan-2-ol)
Class	:	3
Packing group	:	III
Labels	:	3
ERG Code	:	128
Marine pollutant	:	yes(Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts)

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### Additional regulatory information

Partially fluorinated alcohol, reaction products with phosphorus oxide (P2O5), ammonium salts

This product contains a substance subject to a Significant New Activity (SNAc) as disclosed in the Canada Gazette.

## SECTION 16. OTHER INFORMATION

Capstone™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA AB OEL / (c)	:	ceiling occupational exposure limit

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA BC OEL / C	:	ceiling limit
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value
CA QC OEL / C	:	Ceiling

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <a href="http://echa.europa.eu/">http://echa.europa.eu/</a>
--	---	---

Revision Date	:	11/25/2024
Date format	:	mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text.

# SAFETY DATA SHEET

according to the Hazardous Products Regulations



## Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 05/29/2024
6.20	11/25/2024	1336746-00051	Date of first issue: 02/27/2017

---

Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8