

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ ST-500

Version	Revision Date:	SDS Number:	Date of last issue: 11/01/2023
13.0	09/23/2024	1339695-00051	Date of first issue: 02/27/2017

### SECTION 1. IDENTIFICATION

Product name : Capstone™ ST-500

SDS-Identcode : 130000107333

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Stain and soil repellent

Restrictions on use : For industrial use only.  
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

### SECTION 2. HAZARDS IDENTIFICATION

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

|| Not a hazardous substance or mixture.

#### GHS label elements

|| No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

#### Other hazards

Inhalation of decomposition products in high concentration may cause shortness of breath (lung edema).

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

|| No hazardous ingredients

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ ST-500

Version	Revision Date:	SDS Number:	Date of last issue: 11/01/2023
13.0	09/23/2024	1339695-00051	Date of first issue: 02/27/2017

### SECTION 4. FIRST AID MEASURES

- |   |   |   |
|---|---|---|
| If inhaled  | : | If inhaled, remove to fresh air.<br>Get medical attention if symptoms occur.  |
| In case of skin contact                                     | : | Wash with water and soap as a precaution.<br>Get medical attention if symptoms occur.   |
| In case of eye contact                                      | : | Flush eyes with water as a precaution.<br>Get medical attention if irritation develops and persists.  |
| If swallowed  | : | If swallowed, DO NOT induce vomiting.<br>Get medical attention if symptoms occur.<br>Rinse mouth thoroughly with water.   |
| Most important symptoms and effects, both acute and delayed | : | Inhalation may provoke the following symptoms:<br>Lung edema<br>Shortness of breath<br>Eye contact may provoke the following symptoms<br>tearing<br>Redness<br>Discomfort |
| Protection of first-aiders                                  | : | No special precautions are necessary for first aid responders.  |
| Notes to physician  | : | Treat symptomatically and supportively.   |

### SECTION 5. FIRE-FIGHTING MEASURES

- |                                       |   |  |
|---------------------------------------|---|--|
| Suitable extinguishing media          | : | Water spray<br>Alcohol-resistant foam<br>Carbon dioxide (CO2)<br>Dry chemical  |
| Unsuitable extinguishing media        | : | None known.  |
| Specific hazards during fire fighting | : | Vapors may form explosive mixtures with air.<br>Exposure to combustion products may be a hazard to health.                     |
| Hazardous combustion products         | : | Hydrogen fluoride<br>carbonyl fluoride<br>potentially toxic fluorinated compounds<br>aerosolized particulates<br>Carbon oxides |
| Specific extinguishing methods        | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.                        |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ ST-500

Version 13.0	Revision Date: 09/23/2024	SDS Number: 1339695-00051	Date of last issue: 11/01/2023 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the environment.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ ST-500

Version 13.0      Revision Date: 09/23/2024      SDS Number: 1339695-00051      Date of last issue: 11/01/2023  
Date of first issue: 02/27/2017

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.  
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Gases

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

#### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		C	6 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		TWA	3 ppm 2.5 mg/m <sup>3</sup>	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m <sup>3</sup>	NIOSH REL
		ST	5 ppm 15 mg/m <sup>3</sup>	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	NIOSH REL
		ST	30,000 ppm 54,000 mg/m <sup>3</sup>	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m <sup>3</sup>	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m <sup>3</sup>	NIOSH REL
		C	200 ppm 229 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm	OSHA Z-1

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ ST-500

Version 13.0	Revision Date: 09/23/2024	SDS Number: 1339695-00051	Date of last issue: 11/01/2023 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

			55 mg/m <sup>3</sup>	
--	--	--	----------------------	--

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

### Personal protective equipment

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

|| **Remarks** : Wash hands before breaks and at the end of workday.

|| **Eye protection** : Wear the following personal protective equipment:  
Safety glasses

|| **Skin and body protection** : Skin should be washed after contact.

|| **Hygiene measures** : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : liquid, Aqueous solution

**Color** : clear, opaque, yellow

**Odor** : No data available

**Odor Threshold** : No data available

**pH** : 9 - 11

**Melting point/freezing point** : 32 °F / 0 °C

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ ST-500

Version 13.0	Revision Date: 09/23/2024	SDS Number: 1339695-00051	Date of last issue: 11/01/2023 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

Initial boiling point and boiling range	: 212 °F / 100 °C (1,013 hPa)
Flash point	: does not flash
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Density	: 1.1 g/cm <sup>3</sup>
Solubility(ies) Water solubility	: dispersible
Partition coefficient: n-octanol/water	: Not applicable
Autoignition temperature	: No data available
Decomposition temperature	: > 392 °F / > 200 °C
Viscosity Viscosity, kinematic	: No data available
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Particle characteristics Particle size	: Not applicable

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reac-	: Vapors may form explosive mixture with air.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ ST-500

Version	Revision Date:	SDS Number:	Date of last issue: 11/01/2023
13.0	09/23/2024	1339695-00051	Date of first issue: 02/27/2017

tions  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

### Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride  
Carbonyl difluoride  
Carbon dioxide  
Carbon monoxide

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

### Acute toxicity

|| Not classified based on available information.

#### Product:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate (Rat): > 5.8 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgment  
Assessment: The substance or mixture has no acute inhalation toxicity

|| No observed adverse effect concentration (Rat): >970 mg/m3  
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

### Skin corrosion/irritation

|| Not classified based on available information.

#### Product:

Species : Rabbit  
Result : No skin irritation

### Serious eye damage/eye irritation

|| Not classified based on available information.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ ST-500

Version 13.0	Revision Date: 09/23/2024	SDS Number: 1339695-00051	Date of last issue: 11/01/2023 Date of first issue: 02/27/2017
-----------------	------------------------------	------------------------------	---

### **Product:**

Species : Rabbit  
Result : No eye irritation

### **Respiratory or skin sensitization**

#### **Skin sensitization**

|| Not classified based on available information.

#### **Respiratory sensitization**

|| Not classified based on available information.

#### **Germ cell mutagenicity**

|| Not classified based on available information.

### **Product:**

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

### **Carcinogenicity**

|| Not classified based on available information.

**IARC** No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### **Reproductive toxicity**

|| Not classified based on available information.

#### **STOT-single exposure**

|| Not classified based on available information.

#### **STOT-repeated exposure**

|| Not classified based on available information.

#### **Aspiration toxicity**

|| Not classified based on available information.

## SECTION 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

#### **Product:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 120 mg/l  
Exposure time: 48 h

### **Persistence and degradability**

No data available

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ ST-500

Version	Revision Date:	SDS Number:	Date of last issue: 11/01/2023
13.0	09/23/2024	1339695-00051	Date of first issue: 02/27/2017

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

Not regulated as a dangerous good

### Special precautions for user

Not applicable

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

|| Listed substances in the product are at low enough levels to not be expected to exceed the RQ

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ ST-500

Version	Revision Date:	SDS Number:	Date of last issue: 11/01/2023
13.0	09/23/2024	1339695-00051	Date of first issue: 02/27/2017

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### US State Regulations

#### Pennsylvania Right To Know

Water	7732-18-5
Fluorinated Acrylic Alkylamino Copolymer	Trade secret
Sodium hydroxide	1310-73-2
Potassium hydroxide	1310-58-3

#### California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.

#### Additional regulatory information

Fluorinated Acrylic Alkylamino Co-polymer Trade secret

This material contains one or more substances which are subject to a TSCA Section 5 Consent Order or Significant New Use Rule (SNUR).

This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D:  
P-11-0091

## SECTION 16. OTHER INFORMATION

### Further information

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ ST-500


Version  
13.0

Revision Date:  
09/23/2024

SDS Number:  
1339695-00051

Date of last issue: 11/01/2023  
Date of first issue: 02/27/2017

### NFPA 704:



### HMIS® IV:

HEALTH	/	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Capstone™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
ACGIH / C	: Ceiling limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	: Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-2 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Capstone™ ST-500

Version	Revision Date:	SDS Number:	Date of last issue: 11/01/2023
13.0	09/23/2024	1339695-00051	Date of first issue: 02/27/2017

- International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/23/2024

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8