

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 17.0	Revision Date: 2024/11/25	SDS Number: 1336769-00052	Date of last issue: 2024/07/23 Date of first issue: 2017/02/27
-----------------	------------------------------	------------------------------	-------------------------------------------------------------------

1. PRODUCT AND COMPANY IDENTIFICATION

Chemical product name : Capstone™ FS-63 Fluorosurfactant

SDS-Identcode : 130000051604

Supplier's company name, address and phone number

Company name of supplier : Chemours Kabushiki Kaisha

Address : Kamiyacho Prime Place, 4-1-17, Toranomom, Minato-ku, Tokyo, Japan

Telephone : 050-3823-0500

Emergency telephone number : 0120 081167

Prepared by : Product Stewardship & Regulatory

Recommended use of the chemical and restrictions on use

Recommended use : Surfactant

Restrictions on use : For industrial use only.
Do not use this product in consumer spray applications except in water-based coatings where the maximum concentration of active ingredient does not exceed 0.1 wt percent.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

2. HAZARDS IDENTIFICATION

GHS classification of chemical product

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 1

Serious eye damage/eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3

Specific target organ toxicity - : Category 2 (Liver)

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 17.0	Revision Date: 2024/11/25	SDS Number: 1336769-00052	Date of last issue: 2024/07/23 Date of first issue: 2017/02/27
-----------------	------------------------------	------------------------------	-------------------------------------------------------------------

repeated exposure

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements :
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs (Liver) through prolonged or repeated exposure.
H401 Toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements :
Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P284 Wear respiratory protection.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/ attention if you feel unwell.

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 17.0	Revision Date: 2024/11/25	SDS Number: 1336769-00052	Date of last issue: 2024/07/23 Date of first issue: 2017/02/27
-----------------	------------------------------	------------------------------	-------------------------------------------------------------------

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P391 Collect spillage.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Important symptoms and out- : Inhalation of decomposition products in high concentration may
lines of the emergency as- cause shortness of breath (lung oedema).
sumed Vapours may form explosive mixture with air.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)	ENCS No.
Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts	Not Assigned	$\geq 30 - < 40$	-
Propan-2-ol	67-63-0	20.1768	2-207

4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention immediately.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention if symptoms occur.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 17.0	Revision Date: 2024/11/25	SDS Number: 1336769-00052	Date of last issue: 2024/07/23 Date of first issue: 2017/02/27
-----------------	------------------------------	------------------------------	-------------------------------------------------------------------

- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Inhalation may provoke the following symptoms:
Respiratory disorder
Shortness of breath
Lung oedema
Cough
Irritation
Eye contact may provoke the following symptoms
Lachrymation
Redness
Discomfort
Causes serious eye irritation.
Fatal if inhaled.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates
Carbon oxides
- Specific extinguishing meth- : Use extinguishing measures that are appropriate to local cir-

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 17.0	Revision Date: 2024/11/25	SDS Number: 1336769-00052	Date of last issue: 2024/07/23 Date of first issue: 2017/02/27
-----------------	------------------------------	------------------------------	-------------------------------------------------------------------

ods cumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Only trained personnel should re-enter the area.
Remove all sources of ignition.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

7. HANDLING AND STORAGE

Handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue:
17.0	2024/11/25	1336769-00052	2024/07/23
			Date of first issue: 2017/02/27

- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not breathe mist or vapours.
Do not swallow.
Do not get in eyes.
Avoid prolonged or repeated contact with skin.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
- Do not breathe decomposition products.
- Avoidance of contact : Oxidizing agents
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
- Storage**
- Conditions for safe storage : Keep in properly labelled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:
Oxidizing solids
Oxidizing liquids
- Packaging material : Unsuitable material: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Threshold limit value and permissible exposure limits for each component in the work environment

Components	CAS-No.	Value type	Control parame-	Basis
------------	---------	------------	-----------------	-------

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 17.0 Revision Date: 2024/11/25 SDS Number: 1336769-00052 Date of last issue: 2024/07/23
Date of first issue: 2017/02/27

		(Form of exposure)	ters / Concentration standard / Permissible concentration	
Propan-2-ol	67-63-0	ACL	200 ppm	JP OEL ISHL
		OEL-C	400 ppm 980 mg/m3	JP OEL JSOH
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
hydrofluoric acid	7664-39-3	ACL	0.5 ppm	JP OEL ISHL
		OEL-C	3 ppm 2.5 mg/m3	JP OEL JSOH
Further information: Skin absorption				
		TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
Carbon dioxide	124-38-9	OEL-M	5,000 ppm 9,000 mg/m3	JP OEL JSOH
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
Carbon monoxide	630-08-0	OEL-M	50 ppm 57 mg/m3	JP OEL JSOH
Further information: Group 1: Substances known to cause reproductive toxicity in humans				
		TWA	25 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Target substance	Biological specimen	Sampling time	Permissible concentration	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 17.0	Revision Date: 2024/11/25	SDS Number: 1336769-00052	Date of last issue: 2024/07/23 Date of first issue: 2017/02/27
-----------------	------------------------------	------------------------------	-------------------------------------------------------------------

Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates, acidic gas/vapour and organic vapour type

Hand protection

Material : butyl-rubber

Break through time : 480 min

Glove thickness : 0.89 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : clear, colourless, yellow

Odour : alcohol-like

Odour Threshold : No data available

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 17.0	Revision Date: 2024/11/25	SDS Number: 1336769-00052	Date of last issue: 2024/07/23 Date of first issue: 2017/02/27
-----------------	------------------------------	------------------------------	-------------------------------------------------------------------

Melting point/freezing point	: No data available
Boiling point, initial boiling point and boiling range	: No data available
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: Ignitable (see flash point)
Lower explosion limit and upper explosion limit / flammability limit	
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Flash point	: 26 °C
	Method: Pensky-Martens closed cup
Decomposition temperature	: > 200 °C
pH	: 7 - 8.5
Evaporation rate	: No data available
Auto-ignition temperature	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Solubility(ies)	
Water solubility	: soluble
Partition coefficient: n-octanol/water	: log Pow: 0.35 (for a component of this mixture)
Vapour pressure	: 13.79 hPa (20 °C) Solvent
Density and / or relative density	
Density	: 1.1 g/cm ³
Relative vapour density	: No data available
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 17.0	Revision Date: 2024/11/25	SDS Number: 1336769-00052	Date of last issue: 2024/07/23 Date of first issue: 2017/02/27
-----------------	------------------------------	------------------------------	-------------------------------------------------------------------

Particle characteristics
Particle size : Not applicable

10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Flammable liquid and vapour.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : hydrofluoric acid
Carbonyl difluoride
Carbon dioxide
Carbon monoxide

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Fatal if inhaled.

Product:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : Acute toxicity estimate (Rat): 0.005 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: Based on data from similar materials

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 17.0	Revision Date: 2024/11/25	SDS Number: 1336769-00052	Date of last issue: 2024/07/23 Date of first issue: 2017/02/27
-----------------	------------------------------	------------------------------	-------------------------------------------------------------------

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Acute oral toxicity	: LD50 (Rat): > 1,000 mg/kg Method: OECD Test Guideline 425 Assessment: The substance or mixture has no acute oral toxicity
Acute inhalation toxicity	: Approximate Lethal Concentration (Rat): 0.047 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	: LD50 (Rat): > 1,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

Propan-2-ol:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 25 mg/l Exposure time: 6 h Test atmosphere: vapour
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Propan-2-ol:

Species	: Rabbit
Result	: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Species	: Rabbit
---------	----------

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/07/23
17.0	2024/11/25	1336769-00052	Date of first issue: 2017/02/27

Result	: No eye irritation
Method	: OECD Test Guideline 405

Propan-2-ol:

Species	: Rabbit
Result	: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Test Type	: Local lymph node assay (LLNA)
Exposure routes	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative

Propan-2-ol:

Test Type	: Buehler Test
Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
	Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
Germ cell mutagenicity - Assessment	: Weight of evidence does not support classification as a germ cell mutagen.

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 17.0	Revision Date: 2024/11/25	SDS Number: 1336769-00052	Date of last issue: 2024/07/23 Date of first issue: 2017/02/27
-----------------	------------------------------	------------------------------	-------------------------------------------------------------------

Propan-2-ol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Propan-2-ol:

Species	: Rat
Application Route	: inhalation (vapour)
Exposure time	: 104 weeks
Method	: OECD Test Guideline 451
Result	: negative

Reproductive toxicity

Not classified based on available information.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Effects on fertility	: Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 415 Result: negative Remarks: Based on data from similar materials
Effects on foetal development	: Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 414 Result: negative Remarks: Based on data from similar materials
Reproductive toxicity - Assessment	: Weight of evidence does not support classification for reproductive toxicity

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/07/23
17.0	2024/11/25	1336769-00052	Date of first issue: 2017/02/27

Propan-2-ol:

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative
Effects on foetal development	: Test Type: Embryo-foetal development Species: Rat Application Route: Ingestion Result: negative

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Propan-2-ol:

Assessment	: May cause drowsiness or dizziness.
------------	--------------------------------------

STOT - repeated exposure

May cause damage to organs (Liver) through prolonged or repeated exposure.

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Exposure routes	: Ingestion
Target Organs	: Liver
Assessment	: Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

Repeated dose toxicity

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Species	: Rat, male and female
LOAEL	: 3.6 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days
Method	: OECD Test Guideline 408
Remarks	: Based on data from similar materials

Species	: Rat, male
NOAEL	: 100 mg/kg
LOAEL	: 1,000 mg/kg
Application Route	: Skin contact
Exposure time	: 28 Days
Method	: OECD Test Guideline 410
Remarks	: Based on data from similar materials

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/07/23
17.0	2024/11/25	1336769-00052	Date of first issue: 2017/02/27

Propan-2-ol:

Species	: Rat
NOAEL	: 12.5 mg/l
Application Route	: inhalation (vapour)
Exposure time	: 104 Weeks

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 36.4 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 3.24 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	: ErC50 (Pseudokirchneriella subcapitata (green algae)): > 22.44 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials NOEC (Pseudokirchneriella subcapitata (green algae)): 22.44 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to fish (Chronic toxicity)	: NOEC (Oncorhynchus mykiss (rainbow trout)): 0.88 mg/l Exposure time: 90 d Method: OECD Test Guideline 210 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 0.0093 mg/l Exposure time: 21 d Method: OECD Test Guideline 211 Remarks: Based on data from similar materials
M-Factor (Chronic aquatic	: 10

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 17.0	Revision Date: 2024/11/25	SDS Number: 1336769-00052	Date of last issue: 2024/07/23 Date of first issue: 2017/02/27
-----------------	------------------------------	------------------------------	-------------------------------------------------------------------

toxicity)

Propan-2-ol:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h
Toxicity to microorganisms	: EC50 (Pseudomonas putida): > 1,050 mg/l Exposure time: 16 h

Persistence and degradability

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Biodegradability	: Result: Not readily biodegradable. Method: OECD Test Guideline 301D Remarks: Based on data from similar materials
------------------	---------------------------------------------------------------------------------------------------------------------------

Propan-2-ol:

Biodegradability	: Result: rapidly degradable
BOD/COD	: BOD: 1,19 (BOD5) COD: 2,23 BOD/COD: 53 %

Bioaccumulative potential

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Bioaccumulation	: Species: Oncorhynchus mykiss (rainbow trout) Bioconcentration factor (BCF): 4 Remarks: Based on data from similar materials
-----------------	-------------------------------------------------------------------------------------------------------------------------------------

Propan-2-ol:

Partition coefficient: n-octanol/water	: log Pow: 0.05
----------------------------------------	-----------------

Mobility in soil

No data available

Hazardous to the ozone layer

Not applicable

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 17.0	Revision Date: 2024/11/25	SDS Number: 1336769-00052	Date of last issue: 2024/07/23 Date of first issue: 2017/02/27
-----------------	------------------------------	------------------------------	-------------------------------------------------------------------

Other adverse effects

Components:

Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts:

Results of PBT and vPvB assessment	: PBT substance
Additional ecological information	: Information given is based on data on the components and the ecotoxicology of similar products.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	: Dispose of in accordance with local regulations. Do not dispose of waste into sewer.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number	: UN 1993
Proper shipping name	: FLAMMABLE LIQUID, N.O.S. (Propan-2-ol)
Class	: 3
Packing group	: III
Labels	: 3
Environmentally hazardous	: no

IATA-DGR

UN/ID No.	: UN 1993
Proper shipping name	: Flammable liquid, n.o.s. (Propan-2-ol)
Class	: 3
Packing group	: III
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 366
Packing instruction (passenger aircraft)	: 355

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/07/23
17.0	2024/11/25	1336769-00052	Date of first issue: 2017/02/27

IMDG-Code

UN number	: UN 1993
Proper shipping name	: FLAMMABLE LIQUID, N.O.S. (Propan-2-ol, Reaction mass of mixed (3,3,4,4,5,5,6,6,7,7,8,8,8-tridecafluorooctyl) phosphates, ammonium salts)
Class	: 3
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

Refer to section 15 for specific national regulation.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

ERG Code : 128

15. REGULATORY INFORMATION

Related Regulations

Fire Service Law

Group 4, Type 2 petroleum, Water soluble liquid, (2000 litre), Hazardous rank III

Chemical Substance Control Law

Priority Assessment Chemical Substance

Chemical name	Number
Isopropyl alcohol	102

Industrial Safety and Health Law

Harmful Substances Prohibited from Manufacture

Not applicable

Harmful Substances Required Permission for Manufacture

Not applicable

Substances Prevented From Impairment of Health

Not applicable

Circular concerning Information on Chemicals having Mutagenicity - Annex 2: Information on Existing Chemicals having Mutagenicity

Not applicable

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version 17.0 Revision Date: 2024/11/25 SDS Number: 1336769-00052 Date of last issue: 2024/07/23
Date of first issue: 2017/02/27

Circular concerning Information on Chemicals having Mutagenicity - Annex 1: Information on Notified Substances having Mutagenicity

Not applicable

Substances Subject to be Notified Names

Article 57-2 (Enforcement Order Table 9)

Chemical name	Concentration (%)	Remarks
Propyl alcohol	20.1768	-

Substances Subject to be Indicated Names

Article 57 (Enforcement Order Article 18)

Chemical name	Remarks
Propyl alcohol	-

Skin and Eye Damage Substances for PPE Requirements (ISHL MO Art. 594-2)

Not applicable

Carcinogenic Substances (Article 577-2 of the Occupational Health and Safety Regulations)

Not applicable

Ordinance on Prevention of Hazards Due to Specified Chemical Substances

Not applicable

Ordinance on Prevention of Lead Poisoning

Not applicable

Ordinance on Prevention of Tetraalkyl Lead Poisoning

Not applicable

Ordinance on Prevention of Organic Solvent Poisoning

Organic Solvents Class 2

Enforcement Order of the Industrial Safety and Health Law - Attached table 1 (Dangerous Substances)

Inflammable Substance

Poisonous and Deleterious Substances Control Law

Not applicable

Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof

Not applicable

High Pressure Gas Safety Act

Not applicable

Explosive Control Law

Not applicable

Vessel Safety Law

Flammable liquids (Article 2 and 3 of rules on shipping and storage of dangerous goods and its Attached Table 1)

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/07/23
17.0	2024/11/25	1336769-00052	Date of first issue: 2017/02/27

Aviation Law

Flammable liquid (Article 194 of The Enforcement Rules of Aviation Law and its Attached Table 1)

Marine Pollution and Sea Disaster Prevention etc Law

Bulk transportation : Noxious liquid substance(Category Z)

Pack transportation : Classified as marine pollutant

Narcotics and Psychotropics Control Act

Narcotic or Psychotropic Raw Material (Export / Import Permission)

Not applicable

Specific Narcotic or Psychotropic Raw Material (Export / Import permission)

Not applicable

Waste Disposal and Public Cleansing Law

Specially Controlled Industrial Waste

16. OTHER INFORMATION

In this SDS, if the concentration of substances subject to notification under the Industrial Safety and Health Law is indicated as a range, it includes cases where it is a trade secret.

Other information : Capstone™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.
Chemours™ and the Chemours Logo are trademarks of The Chemours Company.
Before use read Chemours safety information.
For further information contact the local Chemours office or nominated distributors.

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
JP OEL ISHL	: Japan. Administrative Control Levels
JP OEL JSOH	: Japan. The Japan Society for Occupational Health. Recommendation of Occupational Exposure Limits
ACGIH / TWA	: 8-hour, time-weighted average

SAFETY DATA SHEET



Capstone™ FS-63 Fluorosurfactant

Version	Revision Date:	SDS Number:	Date of last issue: 2024/07/23
17.0	2024/11/25	1336769-00052	Date of first issue: 2017/02/27

ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
JP OEL ISHL / ACL	:	Administrative Control level
JP OEL JSOH / OEL-M	:	Occupational Exposure Limit-Mean
JP OEL JSOH / OEL-C	:	Occupational Exposure Limit-Ceiling

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

JP / EN